

Douglas County Surveyor's Record of
Government Corners Renewed

29 T.S. 6 R.W.W.M.

C. Frear
Wit.
Fred Smith
Ora Ronk
Lou Saigisso
May 1919

See Cain 1913 Field
Book 33 Pg. 18, 19.
and Vol. 3 Pg. 77

J. W. Cole Deputy
Witnesses
Walter Aldrich
P. D. Wolford

G. C. Stewart Dep.
Wit.
Ed Walker

G. C. Stewart
Wit.
Geo. Keller
Chas. Voytiela

G. C. Stewart
Wit.
Geo. Keller
Chas. Voytiela
Jesse Davenport

G. C. Stewart
April 17, 1922.
Wit.
Abner Rue
J. H. Adams
Dick Redding
H. Erskine

SINGLE
PROPORTIONED
BY
CAIN.

7-20-1913
C.R.
ALSO SEE F.B. 33 Pg. 18
Bk. Pg. 120

C.S. 37/13
C.S. 5/18

C.S. 44/155
C.S. 6/18

C.S. 34/113

✓ S.W. CORNER OF J. S. BURNETT D.L.C. NO. 42. 18
Re-established from old B.T. by setting a 2" x 36" Iron
Rod from which
A 6" White Oak bears West 1 lk. C.S.B.T.
A 6" White Oak bears S.14°W., 3 lks. C.S.B.T. 202

✓ CORNER BETWEEN SECTIONS 25 and 26. 19
A Maple 8" in dia. marked C.S. 1/4 S. from which
A Fir 30" in dia. marked C.S. 1/4 S., 3.25 B.T.
N.55°E 12 lks.
A Fir 16" in dia. marked as above N.89°W., 59 lks.

✓ CORNER TO SECTIONS 25, 26, 35 and 36. 20
I renewed this corner from two original B.T.s the
stumps of which remain this point was set at the intersection
of the measurements give in the field notes. The bearings
of the old B.T. stumps then bear as follows with a variation
of 21°15'E.
N.56°W., 250.8 ft.
N. 9°45'E., 487.0 ft. SEE CORNER NO. 143 19
New B.T.s properly marked bear as follows
A Pine 40" in dia. N. 9°45'W., 487.0 ft.
A Pine 40" in dia. N. 2°30'W., 485.3 ft.
A Fir 60" in dia. S.60°45'E., 377.8 ft.
A Fir 18" in dia. S. 1°15'E., 365.4 ft.

Note: Fir 18" out by Baker Apr. 12, 1942. Set 14"
Fir S.1°40'W., 383.3 ft.
Baker, Ore. State Hy.
J. M. Ledgerwood, witness
Set an Iron pipe 1 1/2" x 36" also a Cedar post 3" x 3" x 36"
erected mound of rock 2 1/2 ft. high.

✓ SECTION CORNER BETWEEN 5, 6, 7 and 8. 21
Found two original B.T.s. Set at each tree and ran
course and bearing as called for in notes. Points did
not coincide so took the average of two for position of
corner. Set Iron Pipe from which
A 36" Fir S.38°W., 28.6 ft. SEE 1961 DEPENDENT
A 6" Fir N.72°W., 15.0 ft. RESURVEY
A 4" White Oak S.54 1/2°E., 34.5 ft.
A 8" White Oak N.10°E., 32.5 ft.

✓ SECTION CORNER 6, 7, T.29-6 and 1, 12 T.29-7. 22
Find one B.T. and stump of other. Set corner from
these two B.T.s Iron Pipe from which
A 12" Fir bears N.15°W., 13.0 ft. FD. OK 5/92
A 14" Fir bears S.14 1/2°W., 41.2 ft. D.BENTZ M115-35
A 14" Fir bears S.48°E., 28.0 ft.
A 36" Fir bears N.65°E., 45.9 ft.

✓ CORNER BETWEEN 6 and 7. FD. OK 5/92 D.BENTZ M115-35 23
Stake in ground set in 1906 by Brown, D.C.S. No notes
for witness trees. Reset corner. Iron Pipe from which
A 8" Fir N.29°W., 28.0 ft.
A 14" Maple S.15°W., 43.0 ft.
Corner is 2921.1 ft. from East section and 3130.8 ft. from
West corner.

✓ CORNER BETWEEN 3 and 10. SEE CORNER NO. 105 24
Set Iron pipe according to Government field notes
distances from B.T.s. Found both B.T.s, one badly rotted.
Marked
A 8" Laurel S.2°W., 67.7 ft.
A 18" Black Oak N.14°W., 52.1 ft. Old B.T.