

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

6

R. W. W. M.

✓ SECTION CORNER 3, 4, 9 and 10. **SEE CORNER NO. 103** 25

Found four original B.T.s. Set Iron Pipe for corner.
Not all B.T.s checked for bearing but I put in corner from
distances which checked. Marked
A 20" White Oak S.37°W., 84.5 ft.
A 18" Black Oak S.81°E., 65.3 ft. O.B.T.
A 16" White Oak N.42°E., 17.5 ft.
A 30" White Oak North 93.7 ft. O.B.T.

✓ S.E. CORNER OF GILLILAND D.L.C. # 46. 26

Found stake set by previous surveyor who was reputed to
have run it in from S.W. corner. Could not find B.T.s.
Set squared Oak Post and marked
A 12" Fir N.84°E., 27.5 ft.
A 18" Fir N.41½°W., 30 ft.

✓ INTERIOR "L" CORNER OF D.L.C. # 46. 27

Set Iron Bolt 8' long for corner. Found O.B.T. Marked
A 16" Black Oak S. 9°E., 62.0 ft.
A 16" White Oak N.71½°E., 57.8 ft. O.B.T. **106**

✓ EXTERIOR "L" CORNER OF D.L.C. # 46. 28

Set Iron Bolt 3' long for corner at stake set by running
East from Interior "L" corner. There was a marked stake
set at this position by former surveyor, but if set from
O.B.T. or not I could not tell. Several trees chopped into
but any scribe marks they may have had were gone. I marked
A 24" Fir N.31°E., 15.3 ft.
A 24" Fir N.84°W., 59.0 ft. **107**

✓ N.E. CORNER OF D.L.C. # 46. 29

No witness trees could be found and witnesses said they
had washed out. I ran a true line due North from Exterior
"L" corner 2157.7 ft. and set a witness corner. Drove
Galv. Iron Bar for witness corner 86.3 ft. South of true
corner which falls in River. Marked
A 6" White Oak N.88°W., 13.0 ft.
A 6" White Oak S.83°E., 36.6 ft. **102**

✓ SECTION CORNER BETWEEN 16, 17, 20 and 21. 30

Reset from one Original B.T. in Section 21. Drove a
buggy axle. Set Stake marker and marked
A 24" Black Oak N.77°E., 525.5 ft.
A 20" Black Oak S.75°E., 444.6 ft.
A 24" Black Oak N.56°E., 792.3 ft.
(QUESTIONABLE info.) (No Source fd. for this corner)

✓ N.W. CORNER OF D.L.C. # 42. 31

Set 1½" Iron Pipe with pile of rocks around it. Set
from stump in grain field and checked by S.W. corner of
Claim 40. Marked
A 18" Balm N.4°W., 197.8 ft. **NOT FOUND**

✓ ½ CORNER BETWEEN 2 and 11. 32

Set from two Original B.T.s one fallen and other marks
destroyed. Set pointed rock and marked
A 12" Black Oak S.86½°W., 60.0 ft.
A 10" White Oak N.12°W., 22.0 ft. **177**

✓ ½ CORNER BETWEEN SECTIONS 16 and 21. 33

Renewed this corner from 24" Oak B.T., which is alive,
standing and bearing scar, but I did not open it. Set
a Cedar Post for corner and erected a mound of rock 3 ft.
in dia. and 18 inches high from which
Original B.T. bears S.11°W., 112 ft. **98**

SEE CORNER NO. 98

SEE ALSO # 43

G. G. Stewart D.C.S. April 17-19, 1922.
Witnesses
Abner Rue, J. H. Adams, Dick Redding and H. Erskine

#270

G. G. Stewart
Witnesses
C. M. Melcomb
W. S. Crearer
April 1922

J. W. Cole G.S.
Wit.
E. Richardson
H. E. Bergh
chain
Feb. 2, 1922.