

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 6 R. W. W. M.

Arthur Boyer
February 24, 1940

Arthur Boyer Dep. Co. Sur.
Aug. 16, 1941

John H. Markham, Jr. - Eng.
Geo. & Wm. Vaughn - Witnesses
December 2, 9, 1950

Witnesses
Chas. Vortilla
Dorcas Rice

✓ $\frac{1}{4}$ CORNER BETWEEN 8 and 17 T. 29-6. 66
Found original Oak B.T. N.30°E., 25 lks. which Cain remarked in 1913 but all of hear at blaze is decayed. *Ren. 55*
Set a $1\frac{1}{2}$ " x $\frac{1}{4}$ " x 24" Steel Spring leaf (from above original B.T.) on fence line on E. side of road.
A 40" Fir N.3°W., 75 lks., okay Cain, in present road grade.
Marked
A 12" Fir N.81°20'W., 76.5 ft. (chained on slope)
 $\frac{1}{4}$ S. 8 T.29S., R.6W., C.S. B.T.
A 30" Fir on lower side road R/W bark blazed and scribed S.21 $\frac{1}{2}$ °W., 71.5 ft. marked $\frac{1}{4}$ S.17 T.29S., R.6W., C.S.B.T.

✓ N.E. CORNER OF WM. DOOLEY D.L.C. 43 67
Found both B.T.'s bark scribed the Oak N.20°W., 233 lks. and drove a 1" x 40" Steel auto axle for corner marked C. 43 T. 39 S., R. 6 W., C.S.B.T.

✓ INTERIOR "L" CORNER OF HARRISON RICE D.L.C. 47. 68
Found the original 12" White Oak N.4°W., 121 lks. and an old white oak stump on side of County Road N.27°E 94 ft. which Harrison Rice said was a B.T. (th¹³⁷ original on this is N.40°E., 158 lks.) found also a 20" white oak already scribed and N.70°W., 100 ft. Drove a $\frac{3}{4}$ " Gal. Iron Pipe 30" long for corner.

✓ $\frac{1}{4}$ SECTION CORNER BETWEEN SECTION 32 T.28-6 and SECTION 5 T.29-6. 69
Drove 4" x 4" Fir post at corner, measuring from 6" maple which is in, Oak to H.W. is gone, found a 24" Fir which was blazed but no record of it found. Scribed on bark of this 24" Fir which is N.6°W., 5 ft. *Ren. 155*
T.29 S., R. 6 W., C.S.B.T.

✓ $\frac{1}{4}$ SECTION CORNER BETWEEN 5 and 8. 70
Drove $1\frac{1}{2}$ " Pipe at corner, marked 2 new P.V. S.W. Section 5 will be burned over so marked trees out of fire danger. *Ren. 167*
A 20" Fir S40°E., 47.5 ft. on slope $\frac{1}{4}$ S.8 T.29S., R.6W., C.S.B.T. on bark.
A 36" Fir N.89°E., 80 ft. on slope $\frac{1}{4}$ S.5 T.29S., R.6W., C.S.B.T. on bark.

SEC. COR. 22 - 23 - 26 - 27 71
Determined by O. B. T. A Fir 12" diam. bears N 12° E 18.5 ft. distant Scribe legible.
I remark S 23, B.T.
At corner point found scribed post from which
A Fir 10" diam. bears N 57° W 20.5 ft. dist. marked S 22, 2880, B.T.
A Fir 24" diam. bears S 16° W, 9.5 ft. dist. already marked S 27 C.S. B.T.
A Fir 28" diam. bears S 48° E, 14.0 ft. dist. alread marked S 26, B.T.

$\frac{1}{4}$ SEC. COR. 22-27 72
Set at proportional distance.
At corner point set 1" x 30" I.P. 15" in ground, from which
A Fir 36" in diam. bears S 36° W 18.0 ft. distant marked $\frac{1}{4}$ S, S 27, 2880 B.T.
A Myrtlewood 8" diam. bears N 37° E, 44.0 ft. dist. marked $\frac{1}{4}$ S, S 22 2880 B.T.
(see 1958 Dependant Recovery)

SEC. COR. 21-22-27-28. 73
Determined by O.B.T. At cor. point found $\frac{3}{4}$ " I.P. from which
A Fir 36" diam. bears S 6° W, 33.0 ft. dist. already marked S 28, C.S.B.T.
A Fir 15" diam. bears S 26° E 52.0 ft. dist. already marked, I remark S 27, B.T.
A Fir 12" diam. bears East 40.5 ft. dist. marked S 22, 2880, B.T.
A Fir 36" diam. bears N 12° W 5.0 ft. dist. marked S 21, 2880, B.T.

$\frac{1}{4}$ SEC. COR. 22-23 74
Determined by O.B.T. A B. Oak windfall 36" diam. bears S 70° W 60.0 ft. *Ren. 155*
At corner point set 1" x 30" I. P. 20" in ground, from which
A Fir 10" diam. bears N 58° W 26.0 ft. dist. marked $\frac{1}{4}$ S, S 22, 2880, B.T.
A W. Oak 10" diam. bears S 70° E 29.0 ft. dist. marked $\frac{1}{4}$ S, S 23, 2880, B.

Fl. by: BENTE
Apr. '83 - C.S. 58/282