

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

6

R. W. W. M.

SEC. COR. 23 - 24 - 25 - 26

75

Determined by O.B.T. - A Fir 50" diam. bears N 85° E, 38.5 ft. dist.
Remark this O.B.T. S 24, B.T.

A. W. Oak slag 20" diam. bears N 42° W 39.0 ft. dist. - O.B.T.

At corner point found Oak post, and set 1" x 20" I.P., from which

A Fir stump 13" in dia. bears N 20° W, 14.5 ft. dist. marked
S 23, B. T.

A Fir 16" dia. bears S 30° W 39.0 ft. dist. marked S 26, B. T.

John H. Markham, Jr.
Engineer
Witnesses:
Geo. & Wm. Vaughn
Dec. 29, 1950 &
Jan. 14, 1951
C.S. 40/294

1/4 SEC. COR. 24 - 25,

SEE CORNER NO. 130 76

Determined by O. B. T. - A Laurel 16" dia. bears S 30° E 6.6 ft. dist.
Remark 1/4 S 25, T 29 S, R 6 W, 2880, B. T.

At corner point set 4" x 4" x 30" Oak post scribed, from which

A Laurel 11" dia. bears N 43° W 12.0 ft. dist. marked 1/4 S 24, B. T.

SEC. COR. 26 - 27 - 34 - 35

All of the renewed B.T.s blown down except

A Fir 24 in. diam. bears S 54° E, 55.5 ft. dist. - Ren. #49

At corner point set 1" x 24" iron pipe from which

A Fir 40 ins. diam. bears N 10° W, 32.0 ft. dist. marked S 27, B.T.

A Fir 7 ins. diam. bears S 6° E, 14.3 ft. dist. marked S 34, B.T.

1/4 SEC. COR. 26 - 27

Both O.B.T.s standing

A Fir 50 in. diam. bears S 10° W, 16.5 ft. dist.

A Cedar 7 in. diam. bears S 40° E, 12.0 ft. dist.

At corner point set 1" x 24" iron pipe, from which

A U-wood bears S 52° E, 22.5 ft. dist. marked 1/4 S, B. T.

1/4 SEC. COR. 23 - 24,

Set by proportional measurement.

At mid-point of section line, I set a 1" x 24" iron pipe, from which

A Laurel 6 in. diam. bears N 33° W, 18.6 ft. dist. marked 1/4 S,

S 23, T 29 S, R 6 W, 2880, B.T.

A Laurel 6 in. diam. bears S 61° E, 30.5 ft. dist. marked 1/4 S,

S 24, B.T.

SEC. COR. 20 - 21 - 28 - 29

A 10 in. Fir Stump bears East 4.0 ft. scribed O.B.T. - C.S.

A 7 in. Fir. bears N 62° W 31.7 ft. dist. scribed by C.S.

A Fir 14 in. diam. bears S 40° W, 4.5 ft. dist. O.B.T. - C.S.

At corner point found 1 in. pipe from which

A Laurel 36 in. diam. bears S 60° W 48.5 ft. dist. marked S 29,

T 29 S, R 6 W, 2880, B.T.

N.W. COR. WILLIS D.L.C. 45

A B. O. windfall bears S 25° W, 28.3 ft. dist., I found scribe
on this O.B.T.

At corner point set 1" x 24" iron pipe and found scribed post,
from which

A W. O. 5 in. diam. bears N 16° W, 29.5 ft. dist. marked Cl.45, B.T.

A Laurel 9 in. diam. bears S 5° W, 47.2 ft. dist. marked Cl.45,

T 29 S, R 6 W, 2880, B.T.

SEC. COR. 20 - 21 - 28 - 29

SEE CORNER NO. 96 82

This corner has been renewed by some previous surveyor, and I
noted the bearing of the new witness trees as follows.

A Fir 9 in. in dia. S 88° E 4.2 ft.

A Fir 12 in. in dia. N 6° 30' E 4.2 ft.

A Fir 12 in. in dia. S 38° 30' W 5.0 ft.

A Fir 12 in. in dia. N 60° 00' W 31.5 ft.

I also set an iron pipe 1 1/2 in. x 36 in. at the corner. The remains
of three of the original bearing trees could still be seen, but
they were badly decayed.

John H. Markham, Jr. - Engineer
Wm. Vaughn - Witnesses
Geo. Vaughn - Witnesses
March 17 & 18, 1951
C.S. 40/294

J. H. Markham, Jr.
Engineer
Wm. & Geo. Vaughn
Witnesses
March 21, 1951
C.S. 40/294

Jesse W. Cote - Surv.
3 - 7 - 24