

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 6 R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97195

24-19
Corner on range line 25-30 Set Post
Old B.T. gone. Marked New B.T.
Maples 8" N. 54° E. 11 links.
Maples 10" S 74° E 16 links
Maples 12" S 80° W. 19 links
Maples 10" N 25° W. 20 links
Apr. 19, 1891 Briggs

Superseded By MENSCH
SURVEY 1905 See
Gov't. Field Notes. L. L.

83

S.E. CORNER OF SECTION 13

84

As determined by Old Bearing Trees

- A 30" White Oak, bears S. 85° W., 46.0 ft., standing
- A 12" Black Oak, bears N. 15° W., 69.0 ft., dead
- A 30" Black Oak, bears N. 9° E., 128.0 ft., fallen

At corner point set stone and Iron Pipe from which

- A 30" White Oak bears S. 85° W., 46.0 ft. distant. I remarked this old bearing tree S. 24, B. T.
 - A 36" White Oak bears N. 83° W., 76.0 ft. distant marked S. 13, B.T.
 - A 36" Black Oak bears North 71.5 ft. distant--marked S. 18, B.T.
 - A 18" Black Oak bears S. 16° E., 133 ft. distant--marked S. 19, B.T.
- There are old fences running N-S-E-W from this corner.

SECTION CORNER BETWEEN 13 and 24

85

As set by proportional measurement.

- At midpoint on Section Line I set 1" x 30" Iron Pipe from which:
- A Fir 40" diam. bears N. 15° E., 6.5 ft. distant--marked S, B.T.
- A Cedar 36" diameter bears S. 9° E., 28.5 ft. distant marked S., B.T.

SOUTHWEST CORNER of E₂ of the E₂: SECTION 30:

86

Set Jeep axle with flange on top

N. W. Cor. of J. A. Clarke Cl. #40

87

- Set 1" X 1" X 18" Bolt From Which:
- 24" B. O. bears S 85° W, 74.8' M'k'd. C40 T29S R6W - 1581 BT
- Tree is on edge of Field where slope starts to river & about 90' south of Phone line

N. E. Cor. of Cl. #40

88

- Set 2" Bolt From Fd. O.B.T. 30" W. O. S80°W, 226'

Section corner to secs. 7, 8, 17 and 18.

89

- Found O.B.T. - 24" Madrone, bears S.17°E., 10.6 feet (record- S.17°W. 10.6 ft)
- Found Stump of old Madrone BT. - bears N.88E., 52.1 feet.
- Found old decayed scribed post near corner point.
- At corner point set 4" x 4" x 30" Fir stake, blazed and scribed from which:

Rescribe O.B.T., 24" Mad. bears S.17°E., instead of S.17°W..

New B.T.s

- 12" Fir N.75°W., 10.0 feet.
- 8" Fir S.27°W., 29.5 feet.
- 6" Fir N.40°E., 54.5 feet.

SEE ALSO:
1958-11 GLO
C.S. 58/272

corner secs. 7 and 8.

90

- At cor. point I find an old scribed post lying in fence line, and hole in ground containing oak roots, which Harrison Rice swears is the position of the bearing tree for sec. 7, which was a dead 14" oak, and was destroyed in process of building fence--bears S.18W., 17 links from cor. point
- At cor. point:

- Set 4" x 30" Galvanized iron pipe with 4" x 4" x 36" scribed Fir Stake along side, from which:- New BTs:-
- 12" Fir bears S.69°E., 38.0 feet.
- 14" Fir bears S.72½°W., 25.5 feet.

John H. Markham, Jr., Eng.
Geo. Vaughn, Witness

8-14-51
C.S. 40/363
for Stomar Lbr. Co.

Surveyor:
A. Boyer
Witnesses:
Frank Smith,
D. B. Lewis,
Hollenback
April 24, 1952
C.S. 41/24

A. Boyer
1953 / feb.
Wit.
A. Wecks
T. Shattenkirch
41-115-

Gene E. Johnson
November 23, 1953
Wit: Clyde Johnson
Done for Clyde Johnson
Filed in sur. file 41/248.