

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 6 R. W. W. M.

ECRE-CHAPMAN CO., EUGENE, OREGON 97100

99

North East corner of Donation Land Claim No. 45

Found:

Mound of rocks at corner at BT 14 inch fir stump scribed 45-REN. No. 34
Visible checks for bearing and distance to corner.
We found stumps (rotted) that check the other two BTs.

Set:

1 inch iron pipe with brass cap marked County Surveyors Office 1954
DLC 45 N.E. Cor. T29S R6W

Blazed and scribed:

7 inch W.O. S60°W, 29.1 feet distant, NE CL 45 CS BT
12 inch R. Fir S63¹⁰° E, 40.0 feet distant, NE CL 45 CS BT.

Note: 31° East to wire fence.

100

SE corner Donation Land Claim No. 46.

Found:

BTs as established by Stewart, 1922, standing and healthy. -REN. #26

Set:

1 inch by 40 inch bolt (square head) at corner

Blazed and scribed:

6 inch W.O. N 81°E, 6.6 feet distant, C46 CS BT.

We cut out:

Old BT 24 inch Fir S84°W, 27.5 feet distant (bearing record N84°E) Scribing
in good Condition

We did not cut out:

Old blaze 30 inch Fir N 41¹⁰°W, 30.0 feet distant.
Looks good and check for bearing and distance.

101

N.E. corner Donation Land Claim No. 41

Found:

Both old W.O. BTs check for bearings and distances

We cut out:

8 inch W.O. S10°W, 5.3 feet distant, scribed CS C 41 BT., good
condition -REN. #56

Old BTs alive and standing.

Set:

3/4 inch by 30 inch bolt (square head) at corner

Blazed and scribed:

10 inch W.O. S40°E., 3.0 feet distant, C 41 CS BT

102

W.C., N.E. corner Donation Land Claim No. 46.

Found:

1/2 inch bolt at corner -REN. #29

Old BTs established by Stewart, 1922, standing and in good condition.

The 6 inch W.O. N 88°W, 13.0 feet distant has been cut out and
scribing visible, both oak trees check for bearing and distances.

Rescribed:

14 inch W.O. S83°E, 36.6 feet distant, WC NE C 46 CS BT.

Blazed and scribed:

6 inch forked Ash W. C. N. E. C46 CS BT; S61° W 13.6 feet distant

6 inch W.O. W.C. N.E. C46 CS BT.; S37° W 11.8 feet distant.

24 inch W.O. WC NE C46 CS BT.; S 17°E 75.8 feet distant

Note: N.S. fence ends at corner. Corner on bank of river.

103

Section corner 3, 4, 9, and 10.

Found:

1/2 inch iron post at corner -REN. #25

Old 20 inch BT. S37°W 84.5 feet distant, down.

Old 18 inch B.O. BT standing but rotted; S81° E 65.3 feet distant
no scribes visible

Old 16 inch W.O. BT N 42° E, 17.5 feet distant, alive and standing;
blazed and grown over.

Old 30 inch W.O. BT north 93.7 feet distant alive and standing;
blaze grown over.

Note: all old BTs check for bearing and distances.

(over)

Renewal of corners for County
by County Surveyor's Office.
June 7-14, 1954.
See County Surveyor's file No. 46/45.

James M. Byron
Ray Irving
John Fee.