

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Section corner 3, 4, 9, and 10 continued from other side.

104

Blazed and scribed:

14 inch R. Fir, S 70° E 30.8 feet distant; S 10 T29S, R6W CS BT.
6 inch R. Fir S 75° W 18.7 feet distant; S9 T29S R.6.W CS BT.

1/4 section 3, and 10.

105

We found both BTs as established by Stewart- 1922 - Ren. #24

8 inch Laurel S 2° W, 67.7 feet distant standing but dead; scribed
1/4 CS BT

18 inch B.O. N. 14° W, S21 feet distant, standing, dead, blaze
grown over.

Both BTs check for bearings and distances.

Set:

3/4 inch iron rod at corner.

Blazed and scribed:

8 inch R. Fir N 7° W 37.8 feet distant; S 3 CS BT

8 inch R. Fir S 13° E 18.2 feet distant; S 10 CS BT

Note: We could not find pipe set by Stewart- 1922

Interior L. corner Donation Land Claim No. 46.

106

Found:

Bolt and 2 foot post scribed CS C46 - Ren. No. 27

Both BTs as established by Stewart- 1922

16 inch BO S 9° E., 62.0 feet distant, stump only center rotted.

24 inch W.O. N76° E., 57.8 feet distant; (recorded N 71 1/4 E)

Blaze grown over, we did not cut out.

Blazed and scribed:

14 inch R. Fir S 56° E., 66 feet distant; Int. L-C 46 CS BT.

Power pole C 5706 - 1954 - N 60° E 18.2 feet distant

Exterior L. Corner Donation Land Claim No. 46.

107

Found:

3/4 inch iron bolt at 3 way fence corner - Ren. #28

36 inch Fir stump N. 31° E., 15.3 feet distant (which we cut out)
scribed 46

36 inch Fir alive and standing, N 84° W 59.0 feet distant; blaze grown
over. We did not cut it out.

Blazed and scribed:

12 inch R. Fir S 51° W., 20.2 feet distant; S.E. Ext.-L CL 46 CS BT

10 inch R. Fir S60° E., 26.2 feet distant; SE Ext LCL 46 CS BT

1/4 section corner 4 and 9

108

Found:

7 inch by 8 inch by 14 inch pointed rock as set by Minch, 1945. - Ren #54

30 inch original BT N60° E., 42.2 feet distant is down and has been
down several years. Blazed face would be underneath.

10" W.O. orig. BT is standing, center is rotted, but believe I found a scribe
mark; both trees check bearings distance and sizes with record.

Blazed and scribed:

12 inch R. Fir N 53° W., 37.7 feet distant; S 4 CS BT

7 inch W. Oak; S22° W., 22.5 feet distant; S4 CS BT

Set:

3/4 inch by 30 inch iron rod at corner at side of rock.

James W. Byron
Ray Irving
John Fee

Renewal of corners for County
by County Surveyor's Office.
June, 1954.
See County Surveyor's file No. 46/45.

RECORDED & INDEXED
CORNER NO. #234