

Douglas County Surveyor's Record of  
Government Corners Renewed

29 T. S. 6 R. W. W. M.

KOKK-CHAPMAN CO., EUGENE, ORE. 97195

**116**  
~~RENEWED, SEE CORNER NO. 166~~  
 $\frac{1}{4}$  corner to secs. 29 and 32.  
Point for corner determined by O. B. T.:  
A 20 inch Cedar bears S.55°W., 26.4 feet dist.  
At point for corner, set  $1\frac{1}{2}$  inch truck axle with flange up,  
from which:  
A 11 inch Chip. bears S.51°E., 15.0 feet dist. mkd.  $\frac{1}{4}$  S 32 B. T.  
A 7 inch La. bears S.26W., 32.0 feet dist. mkd.  $\frac{1}{4}$  S 32, T29S, R6W.,  
B. T. 2880.  
A 40 inch Fir bears N.78E., 60.0 feet dist., mkd.  $\frac{1}{4}$  S 29 B. T.  
Road bears East 108.0 feet dist.

**117**  
South  $\frac{1}{4}$  corner to section 32 - only.  
At a point on Township line, 2634 feet West of Southeast corner of Sec. 32,  
and 2451.5 feet East of Southwest corner of Section 32, I set a 1 inch  
truck axle with flange up, for  $\frac{1}{4}$  corner,  
From which:  
A 40 inch White Oak bears East 14.7 feet dist. mkd.  $\frac{1}{4}$  S 32 B. T. *BLM*  
A 7 inch Fir bears West 13.3 feet dist. mkd.  $\frac{1}{4}$  S B. T. *SEE 1980*  
North  $\frac{1}{4}$  corner Sec. 5 bears West 635.5 feet. *CORRECTIVE*  
Corner lies along E.- W. fence. *RESURVEY*

**118**  
Section corner to secs. 29, 30, 31 and 32.  
23 inch Fir, S.42°E., 4.6 feet - O. B. T. - rescribed.  
24 inch Fir, N.72°E., 18.0 feet - O. B. T. - rescribed.  
14 inch Fir, S.87W., 8.0 feet - O.B.T. - rescribed.  
10 inch La., N.33W., 23.2 feet - O. B. T. - Dead. *SEE C.S. 4/24*  
At point for corner found stone and set  $\frac{3}{4}$  inch x 30 inch iron pipe, *BOYER*  
from which: *FOR EARLIER REPORT.*  
A 24 inch La. bears N.23°W., 35.5 feet dist. mkd. S 30, T29S, R6W,  
2880 B. T. *CORNER 2/8/103*  
A 20 inch La. bears S.12W., 23.7 feet dist., mkd. S 31, T29S, R6W.,  
W. M., B. T.

**119**  
South section corner to sections 31 and 32 only. (S.W. cor. Sec. 32)  
An 11 inch Fir bears N.63E., 30.0 feet dist.-O. B. T. - found scribe.  
A 6 inch Fir snag bears N.45°W., 13.0 feet dist.- O. B. T.-found scribe.  
At corner point found large stone and set  $\frac{3}{4}$  inch x 20 inch iron pipe,  
from which  
A 20 inch Yew wood bears N.49E., 44.6 feet dist. mkd. S 32, T29S, R6W., B. T. *225*  
A 13 inch Cedar bears S2W., 31.8 feet dist., mkd. S 31, X B. T.  
A 60 inch Fir bears N.65W., 34.4 feet dist., mkd. S 31, T29S., R6W., B. T.  
Corner lies in a E - W saddle. *Amended CC*  
*SEE BLM*  
*NOTES*  
*V. 42*  
*P. 16566*

**120**  
Township corner to secs. 31, 36, 1 & 6, Twps. 29 & 30., Rgs. 6 & 7 W.  
Point for corner determined by O. B. Ts:  
A 24 inch W. O., bears N73E., 14.5 feet dist., - I rescribe S 31 B. T. *163*  
A 20 inch W. O., bears S.20E., 33.0 feet dist., - I rescribe S 6 B. T.  
A 44 inch Y. Pine windfall bears S19W., 30.4 feet dist. - O. B. T.  
At corner point set 2 inch x 36 inch solid steel bolt,  
from which:  
A 21 inch W. O., bears N49W., 177.0 feet dist., mkd. S 36 T29S, R7W., B.T.  
A 22 inch La. bears N4E., 55.0 feet distant mkd. S31, T29S, R6W., B.T.  
A 14 inch W. O., bears S33E., 30.5 feet dist., mkd. S 6, T30S, R6W., B. T.  
An old fence runs N - S.

**121**  
 $\frac{1}{4}$  corner to secs. 31 and 32.  
Location for corner determined by O. B. T.-a 10 inch Fir, bears N.28°E.,  
25.7 feet dist.-O. B. T.-found scribe.  
At corner point found large stone and set 3 inch x 24 inch iron pipe,  
from which:  
A 12 inch White Fir bears S.46°E., 42.2 feet dist., mkd.  $\frac{1}{4}$  S 32 BT.  
A 6 inch Cedar bears N.10°E., 53.0 feet dist. mkd.  $\frac{1}{4}$  S 32 BT.  
A cat road bears East 35.0 feet dist.-it bears N.10°E., and S.10°W.

John H. Markham Jr.  
Work done for Stomar Lumber Co.  
August & October, 1956.  
C. S. File No. 42/190.

John H. Markham Jr.  
Work for Stomar Lumber Co.  
Sept. 17, 1956.  
C. S. File No. 42/191.

John H. Markham Jr.  
Done for Stomar  
Lumber Co.  
Mar. 4, 1957.  
C. S. File No.  
42/254.