

Douglas County Surveyor's Record of
Government Corners Renewed

M. W. W. 29 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

122

$\frac{1}{4}$ corner to secs. 34 and 35.
Original BTs could not be found. Corner set by proportional measurement as per Byars survey of 1871.
Set an iron pipe with brass cap at corner point marked $\frac{1}{4}$ S 34/35, T 29 S, R 6 W, County Surveyor's Office, 1956.
Scribed 2 trees:
18 inch R. Fir, N. 48° 30' E., 33.4 feet mkd. $\frac{1}{4}$ S 35, T 29 S, R 6 W, CS BT.
14 inch R. Fir, N. 84° 45' W., 27.0 feet mkd. $\frac{1}{4}$ S 34 T 29 S, R 6 W., CS BT.
Corner is 42 feet east of fence.

RENEWED, SEE CORNER NO. # 248

123

Section corner to secs. 33 & 34, T29S, R6W., and secs. 3 & 4, T30S, R6W.
Location of corner determined by facing two old BTs not of record.
Found old BT, 50 inch Fir, N. 2° W., 36 feet - found scribe S 34.
Found old BT, White Fir, snag only, S. 7° E., 14 feet - found scribe T.R.W. 35.
Set an iron pipe with brass cap for corner mkd. $\frac{33}{4}$ S 34.
Blazed and scribed new trees:
12 inch W. Fir, N. 19° W., 62.4 feet; mkd. T 29 S, R 6 W, S 33, C. S. BT.
26 inch W. Fir, N. 63° 30' E., 87 feet, mkd. T29S, R6W, S 34, C. S. BT.
18 inch W. Fir, S. 55° 30' E., 39 feet, mkd. T30S, R6W, S 3, C. S. BT.
4 inch R. Fir, S. 60° W., 18.5 feet, mkd. S 4, C. S. BT.

124

$\frac{1}{4}$ corner to sec. 34, T29S, R6W., and sec. 3, T30S, R6W.
Original B. T.s not found. Corner set midway and on true line between section corners.
Set an iron pipe with brass cap mkd. $\frac{1}{4}$ S 34/3 T 29 S, R 6 W, Co. Surveyor's Office, 1956.
Scribed 2 trees:
36 inch Fir, N. 36° E., 22.7 feet, mkd. $\frac{1}{4}$ S 34, T29S, R6W, C. S. BT.
A Fir, S. 60° E., 37.0 feet, mkd. $\frac{1}{4}$ S 3, T29S, R6W., C. S. BT.

125

Section corner to secs. 34 & 35, T 29 S, R 6 W., and secs. 2 & 3, T30S, R6W.
Location of corner determined by facing old BTs found but not of record.
Set an iron pipe with brass cap marked Sec. Cor. $\frac{34}{3} \frac{35}{2}$ T29S, R6W. 1956, County Surveyor's Office.
From which:
A 30 inch R. Fir bears S. 10° E., 33 feet, bark scribed T30S, R6W., S 2 C. S. BT.
A 6 inch R. Fir bears N. 32° E., 56 feet, scribed T29S, R6W, S 35, C.S. BT.

2/22/78
SEE LETTER TO ATTORNEY IN C.S. FILE 47/93

126

$\frac{1}{4}$ corner to sec. 35, T29S, R6W., and sec. 2, T30S, R6W.
Corner set half way between section corners.
Set an iron pipe with brass cap at corner point marked $\frac{1}{4}$ Cor. $\frac{S 35 T29S}{S 2 T30S}$ R6W. Co. Surveyor's Office, 1956.
From which:
A 14 inch W. Oak bears N. 5° 30' E., 29.0 feet scribed $\frac{1}{4}$ S 35, T29S, R6W., C. S. BT.
A 12 inch W. Oak bears S. 51° E., 233.37 feet scribed $\frac{1}{4}$ S 2 T 30 S, R 6 W. C. S. BT.

127

Section corner to secs. 35 & 36, T29S, R6W., and secs. 1 & 2, T 30 S, R6W.
Found mound of rock and scribed post at corner. All BTs as renewed by Ben B. Irving in good condition.
Set an iron pipe with brass cap marked $\frac{35}{2} \frac{36}{1}$ 1956, T 30 S, R 6 W., Co. Surveyor's Office.
Blazed and Scribed:
12 inch R. Fir, S. 36° W., 22.0 feet, T 30, S 2 C. S. BT.

2/22/78
SEE ATTACHED LETTER TO NOTES CS. 47/93

James W. Byron, Deputy County Surveyor. - Survey for Dale Weekly
May 15, 1956
C. S. File No. 47/93.