

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron Deputy  
Dale McFarland and John Powell  
April 25 - 30, 1962  
C. S. File No. 49/139

$\frac{1}{4}$  Corner to Sections 35 and 36. 185  
Found - Orig. 18", now 32" W. Oak S.  $89\frac{1}{2}^{\circ}$ E. 196.0 ft., not 241.6 ft.  
We open & find good scribe mks.  
Find isolated Rock Outcrop S.  $43\frac{1}{2}^{\circ}$ W. 95.0 ft. 13'x3.5" & 4' high.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962  
 $\frac{1}{4}$  S35/S36 T29S R6W  
New BT: 10" W. Oak bears S.  $67\frac{1}{2}^{\circ}$ E. 134.8 ft. scribed  $\frac{1}{4}$  S36 CS BT.  
Chisled 2" + 1.0 ft. below top of Rock Outcrop bears S.  $42\frac{1}{2}^{\circ}$ W. 94.4 ft.

$\frac{1}{4}$  Corner to Sec. 36, T29-6W. & Sec. 1, T30-6W. 186  
Found -  $\frac{3}{4}$ " I.P. at Corner & 3" under surface & under N. S. Fence.  
Both BT's, as recorded by B.B.I., 1929: SEE COR. NO. 14, T. 30-6  
16", now 22" W. Oak N.  $15\frac{1}{2}^{\circ}$ W. 55.4 ft., shows good scribing.  
Set - Brass Cap alongside corner I.P. & Mark County Surveyor's Office, 1962  
 $\frac{1}{4}$  S36 T29S R6W  
S 1 T30S  
Rescribe, now 22" W. Oak N.  $15\frac{1}{2}^{\circ}$ W. 55.4 ft. " $\frac{1}{4}$  S36 CS BT".  
Rescribe, now 10" W. Oak, West 46.0 ft., not N.  $86^{\circ}$ W. 46.9 ft. " $\frac{1}{4}$  S1 CS BT".

Section Corner to Secs. 25 & ~~35~~<sup>36</sup>, T29-6W. & Secs. 30 & 31, T29-5W. 187  
Location identified from C.S. Post and one BT. set by Deputy  
Co. Surv., Roberts, some 20 years ago but not recorded.  
Renewed by setting a 4" Yewwood Post with  $\frac{3}{4}$ " x 36" Gal. I. Pipe  
driven alongside, from which New BT's: #183  
Fir 36" S.  $73\frac{1}{4}^{\circ}$ E. 82 lks., blazed & scribed T29S R5W S31 CS BT.  
Fir 28" S.  $24^{\circ}$ W. 129 lks., blazed & scribed, T29S R6W S36 CS BT.  
Fir 40" N.  $13\frac{1}{2}^{\circ}$ E. 118 lks., blazed & scribed, T29S R5W S30 CS BT.  
Fir 36" N.  $67\frac{1}{2}^{\circ}$ W. 64 lks., blazed & scribed T29S R6W S25 CS BT.  
SEE #183

$\frac{1}{4}$  Corner West Side Sec. 31, T29-5W. 188  
Located by proportional dist. between the S.W. & N.W. Corner  
of Section 31, T29-5W. Drove a Galv. Iron Pipe for corner from which: #251  
A White Oak 10" bears S.  $75^{\circ}$ E. 29 lks.,  
blazed & scribed  $\frac{1}{4}$  S31 CS BT.  
A White Oak 8" bears N.  $62^{\circ}$ W. 20 lks.,  
blazed & scribed  $\frac{1}{4}$  S36 CS BT.

Corner to Sections 36 and 31, and 1 & 6, T29 & 30S., R's. 5 & 6W. #252 189  
Location identified by and East & West blazed line and distance 36/31 T29  
1/6 T30  
R6 R5  
from rocky ridge S. and N. called for in Original notes.  
Drove  $\frac{3}{4}$ " x 36" Galv. Iron Pipe and set in a mound of rock from which:  
20" Pine bears S.  $37\frac{1}{2}^{\circ}$ E. 98 lks., blazed & scribed T30S R5W S6CSBT.  
16" Pine bears N.  $63^{\circ}$ E. 52 lks., blzd & scribed T29S R5W S31 CS BT.  
16" Pine bears S.  $32^{\circ}$ W. 123 lks., blzd. & scribed T30SR6W S1 CS BT.  
20" Pine bears N.  $65^{\circ}$ W. 82 lks., blzd. & scribed T29S R6W S36 CS BT.

$\frac{1}{4}$  Corner to Sec. 4, T29-6W. & Sec. 33, T28-6W. 190  
Found Bolt in Rock from which:  
15" Oak N.  $45^{\circ}$ E. 53.0 ft. Mkd:  $\frac{1}{4}$  S33 BT.  
Corner Conc. Footing S.  $27^{\circ}$ E. 10.0 ft.  
Corner Conc. Footing N.  $80^{\circ}$ W. 13.5 ft.

$\frac{1}{4}$  Corner to Sec. 30, T29-6W. & Sec. 25, T29-7W. 191  
Rock as described in Gov't Field Notes knocked out.  
One Orig. BT., down, other O.K. Reset Original Rock. #162  
Remarked O.B.T.:  
A 14" Fir S.  $60^{\circ}$ E. 18 lks.  
A 36" Fir S.  $78^{\circ}$ W. 23 lks. New BT.

Ben B. Irving  
Wit: H. C. Baird  
Weaver  
August 21, 1929

B. B. Irving  
July 1953  
C.S. File  
No. 45/95

COULD NOT  
LOCATE BT'S  
COL. in this  
FILE - J.B.  
11/92

B.B. Irving  
Wit. Richard  
son  
May 1934  
Map M 1 - 27