

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

234

Gary L. Langlitz  
Larry E Monrean  
Stephen J. Flause  
Douglas County Surveyors Office  
Aug. 16, 1977  
C.S. 59/38

1/4 Corner for Secs. 4 and 9

Found - A pointed stone, 7"x12"x16" (Rec. per Ren. #54, 7"x8"x14"), firmly set and a 3/4" Iron rod, firmly set alongside the stone. The apparent remains of the orig. SW bearing tree, an orig. 10" now 18" W. Oak alive with previously opened balze, center of tree is rotten, bears S.11°W., 66.0 ft. The location of the orig NE bearing tree falls in a fire trail. A 12" D. Fir now a 15" rotten snag, 6 ft. tall with a well healed double blaze bears N.53°W., 36.6 ft. (Rec. N.53°W., 37.7 ft. Ren. #108 .

Set - A 7" now 10" W. Oak alive and well healed bears S.22°W., 22.5 ft. A 1" x 30" Iron pipe with brass cap attached marked:  
Douglas County Surveyor 1977

T 29 S R 6 W

1/4 S 4  
S 9

and deposit stone and 3/4" iron rod along the west side of the B.C

New BT - A 20" D. Fir scribed "1/4 S4 CS BT" on a double blaze, bears N.81°W., 25.9 ft. Tree is located in E-W fenceline.

Note: Corner is located 3.7 ft. south of corner of fences running E-W and south.

8/16/77

235

Section Corner for Secs. 17, 18, 19 and 20

Found - A 1958 Cadastral Brass cap properly marked, on a 2" x 30" I.P. loosely set 20" above ground, cap broken and torn partly off. A 18" now 20" Fir bears N.8°E., 29.7 ft. with single well healed blaze.

A Madrone snag, 4" now 8" 2.0 ft. high and partly pushed over, bears S.63°E., 11.7 ft. (Rec. 12.5 ft.)

A 25" now 28" Fir bears N.37°W., 23.8 ft. with two well healed blazes (one faces east).

Set - A 1" x 36" I.P. with brass cap set 4" above ground and marked:  
"Douglas County Surveyor" T 29 S R 6 W

S 18 | S 17  
S 19 | S 20

1977

New BT's- A 8" Madrone bears S.85 1/2°W., 27.9 ft. double blazed and marked "T29S R6W S19 CS BT".

A 6" W. Oak bears S.32°E., 24.0 ft. double blazed and marked "T29S R6W S20 CS BT".

Corner is located in North South cat trail.

10/3/77

236

1/4 Corner for Secs. 25 and 26.

Found - A 1" x 30" Iron pipe 1.3 ft. south of an 8" now 13" Maple.

A 16" now 24" Fir stump set by Cain resurvey, 1913 (Pg. 18, Field Book #33) uprooted with well healed blaze, opened and found scribing "S26" Stump hole bears N.89°W., 38.9 ft.

A 30" now 44" Fir with well healed blaze bears N.55°E., 7.9 ft.

A 14" now 16" W. Fir with well healed blaze bears N.68°E., 75.0 ft.

A 14" now 18" double trunked Maple with well healed blaze bears N.70°E., 108.0 ft.

A 1" Iron pipe bears S.35 1/2°W., 10.0 ft. set by BLM 8" above ground.

Set - 1" x 30" Iron pipe with brass cap at location of iron pipe set by Markham Ren. #143, 18" above ground in mound of stone 24" dia. to brass cap marked: "County Surveyors Office"

T 29 S R 6 W

S 26 | S 25

1/4 Cor

1977

No new accessories.

8/16/77

R. B. Kimberling  
M. W. Cline  
Doug. Co. Surveyors  
Office  
October 3, 1977  
C. S. 59/40

R. B. Kimberling  
M. W. Cline  
Doug. Co. Surveyors  
Office  
Aug. 16, 1977  
C.S. 59/38

RE-FILED, SEE CORNER NO. #265