

Douglas County Surveyor's Record of
Government Corners Renewed

T 29

T.S.

R 6

R.W.W.M.

266

CONTINUED.....

New Bt's - 6" fir bears North, 13.0 ft., scribed "1/4 S20 BT".
9" fir bears N.79°W., 21.0 ft. scribed "1/4 S19 BT"
6" fir bears N.75°E., 6.9 ft., scribed "1/4 S19 BT"
1958 Cad. BCIP bears N.60°27'39"W., 78.65 ft.

1/4 Section Corner for Sections 17 and 20. Ren #52 267

Found - A 26" fir bears S.8°W., 19 0 ft. (S 2 1/2°E., 18.5 ft.) Pistol
butt chopped out face and fd. scribe. *F.B.33 R. 32*

43" fir bears N.26°W., 30.2 ft., (N.26 1/4°W., 29.7 ft.) healed
Set - 5/8" x 48" Iron rod and alum. cap at record distance from faces of
Cains NW and SE BT's.

New BT's - 16" fir bears S.37°E., 32.0 ft., scribed "1/4 S20BT".
12" fir bears N.89°E., 48.2 ft., scribed "1/4 S17 BT"

1958 Cad. BCIP bears S.53°53'25"W., 102.62 ft.

Center 1/4 Section 20.

Found - 17" maple bears S.15°E., 54.8 ft. chopped out, found scribe.
24" fir bears N.63 1/4°E., 66.0 ft. rotted stump.
18" fir bears S.45°W., 56.8 ft. rotted stump.

Set - 5/8" x 48" iron rod and alum. cap.

New Bt's - 13" fir bears N.69°E., 11.5 ft. scribed "C 1/4 BT".
21" fir bears S 12°E., 15.5 ft. scribed "C 1/4 BT"
18" fir bears S.88°W, 25.5 ft., scribed "C 1/4 BT"

1/4 Section Corner Sections 20 and 29. 269

Found - A 1 1/4" iron pipe.

BT's - 28" laurel bears S.16°E., 41.0 ft., healed. See Ren.#160
20" fir bears S.79°W., 26.2 ft. stump.

New Bt's - 9" fir bears N.1°W., 33.8 ft. scribed "1/4 S20 Bt"

Section Corner for Sections 16, 17, 20 and 21. 270

Found - 36" pine bears N.61°W., 157.1 ft. down. See Ren.#30
22" fir bears N.62°W., 3.3 ft. down scribe visible.
18" fir bears S.62°E., 8.6 ft. stump scribe visible

Set - 5/8" x 48" iron rod and alum. cap from Cain's record of 3 BT's

New BT's - 12" fir bears N.56°W., 57.7 ft. scribed "S 17 BT".
13" fir bears N.36°E., 45.8 ft., scribed " S16 BT".
16" fir bears East, 51.9 ft. scribed " S16 BT"
9" fir bears S.58°W., 36.2 ft. scribed " S20 BT".

1958 Cad. BCIP bears N.29°57'32"W., 50.44.

1/4 Corner for Sections 20 and 21. 271

Found - Axel and 1958 Cad. BCIP

BT's - 18" fir bears N.37 1/2°W. 13.2 ft. healed. See Ren #46
15" fir bears S.89°E., 28.4 ft. stump.
12" fir bears S.45°E., 23.1 ft. stump.

New BT's - 17" fir bears S.38°W., 6.3 ft., scribed "1/4 S20 BT"

Section Corner for Sections 18 and 19; and Secs. 13 & 24 of T.29-7 272

Found - 1957 Cadastral brass cap and iron pipe.
11" Fir, N.52°W., 7.9 ft. rotting, open face. 1910 BT.
8" now 20" Fir, N.47°W., 91.7 ft. healed face. 1957 BT.
17" Madrone, S.82°E., 62.0 ft. visible scribe. 1957 BT.
20" Fir, S.44 1/2°W., 17.8 ft. rotted open face. 1910 BT.

New BTs - 6" Fir, N.84°E., 12.8 ft.
14" W. fir, S.52°E., 8.2 ft.

3/6/90

1/4 Section Corner for Sections 16 and 17. 273

Set - A 5/8" x 48" iron rod and alum. cap.

New BT-s - 13" fir bears N.44°W., 31.6 ft. scribed "1/4 S17 BT".
20" fir bears N.48°E., 35.6 ft., scribed "1/4 S16 BT"
16" fir bears S.44°E., 18.5 ft., scribed " 1/4 S16 BT"
10" fir bears S 2°W., 54.2 ft., scribed "1/4 S17 BT".

1958 Cad. BCIP bears N.22°00'07"W., 26.55.

Howard Johnstone
L.S. #498
For: Roseburg Forest Products Co.
Dec. 28, 1989
M 101 - 73
See Also M 101 - 72

Howard Johnstone
For: Roseburg
Resources, Inc.
March 6, 1990
C.S. 63/95

Howard Johnstone
For: Roseburg Forest
Products Co.
M 101 - 72
Dec. 26, 1989