

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R 6 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91881

18" now 24" dia., 2' high D. Fir stump with a fully healed lower blaze. We open & find good scribe Marks "BT", bears N.81 $\frac{1}{4}$ °E., 100' (rec N.80°E., 100').

SE BT form ren #96 now gone

276

BT's from ren # 169

Unkown dia. now 15" dia., 6' high D. Fir stump with a fully healed single blaze, bears S.43 $\frac{1}{4}$ °E., 94.2' (rec. S.42°E., 94.2')

9" now 24" dia., 3 $\frac{1}{2}$ ' high D. Fir stump with a fully healed double blaze, bears N.38  $\frac{3}{4}$ °W., 6.5' (rec. N.31°W. 6.5')

BT's from 1990 pending Resurvey (rec taken from BT tags)

20" dia., D. Fir with a partially healed single blaze illegible scribing visible, bears S.85 $\frac{1}{4}$ °E., 57.8' (rec S.85 $\frac{1}{4}$ °E., 58.4, dist is to center of trunk)

16" dia., 3' high D. Fir stump with a partially healed single blaze, illegible scribing visible, bears N.21  $\frac{3}{4}$ °E., 43.7' (agrees with rec.)

Douglas County Survey  
Surveyors Office  
Randall Smith  
Stephen Flause  
6/20/94  
C.S. 64/52

New Accessories -

13" dia., Madrone bark scribed "T29S R6W S29 CS BT", bears S.77 $\frac{1}{4}$ °W., 34'.

13" dia., I. Cedar double blazed and scribed "T29S R6W S20 CS BT", bears N.28 $\frac{1}{4}$ °W., 47.7'.

4" dia., D. Fir, double blazed and scribed "X BT", bears N.58 $\frac{1}{2}$ °E., 16.2'.

Corner lies near the intersection of a east - west & south running fence lines. 4 $\frac{1}{2}$ ' east of the intersection and 1 $\frac{1}{2}$ ' north of the east - west fence line. All Brg's taken away form fence line

277