

Douglas County Surveyor's Record of Government Corners Renewed

29 T. S. 7 R. W. W. M.

✓ CORNER TO 13, 14, 23 and 24. 12
Erected rock mound around old stake from which
Fir 24" dia. bears S.66°E., 29.6 ft. O.B.T.
Fir 24" dia. bears N.13°W., 33.0 ft. O.B.T.
Fir 28" dia. bears S.74°W., 17.1 ft. O.B.T.

✓ CORNER OF SECTIONS 2, 3, 10 and 11. 13
I renewed this corner from the original B.T.s. Set a sandstone 8" x 10" x 15" with cross on top and West sides, from which
A White Oak N.15°E., 40.9 ft. alive and bearing scars
A White Oak N.42°W., 33.0 ft. alive and bearing scars
A White Oak S.23°W., 69.5 ft. alive and bearing scars
A Black Oak S. 6°E., 148.1 ft. dead stub
FD. O.K. 9-20 G. BAUGHMAN M85-35

Also: New BT. 8" W. Oak 55°E., 12' 7" Also 1/2" dia. SEE 2/2

Vol 3 Pg. 172

F. W. Cole

✓ CORNER TO SECTIONS 31, 32 and 5 and 6 ON N. BDY. OF T. 29S. R. 7W. 14
I located this corner from the facings of the original B.T.s as they were all very close to the corner but did not check for distance and direction. I set a Fir Stake and raised mound of earth around stake from which the original B.T.s
A Black Oak 12" dia. with scribe marks visible bears N.85°E., 5.0 ft.
A Black Oak 14" S.28°W., 6.0 ft. scribe marks visible
A Black Oak 12" N.48°W., 8.0 ft. scribe marks visible
A Black Oak 12" N.22°E., 12.0 ft. scribe marks visible
I marked new trees as follows
A Fir 14" dia. N.72°30'E., 17.0 ft.
A Fir 10" dia. N. 3°30'W., 12.0 ft.
A Fir 10" dia. S.65°00'W., 18.0 ft.
A Fir 12" dia. N.25°00'W., 16.2 ft.

RE-NEWED CORNER NO. 78 SEE ALSO 78

✓ CORNER TO SECTIONS 13, 14 23 and 24. 15
I found stake nearly decayed and erected mound of Rock 24" in dia. 18" high from which original trees
A Fir 24" in dia. S.66°E., 29.6 ft. (CAMPBELL'S TREES #12)
A Fir 24" in dia. N.13°W., 33.0 ft. (G.L.O. Bureau 12147-48)
A Fir 28" in dia. S.74°W., 17.1 ft. (See Vol. 28, Pg. 12147-48)

FOUND OK 4/9/1913-6

✓ CORNER TO 1, 2, 11 and 12. 16
Set an Oak Post also a Gas Pipe 1 1/2" x 36" from which
A White Oak 12" in dia. N.29°W., 263.6 ft.
A White Oak 9" in dia. S.22°W., 12.5 ft.
A White Oak 30" in dia. S.80°15'E., 225.5 ft.
A Rock Ledge marked S. 1, C.S. B.O. N.8°30'E., 283.8 ft.

✓ CORNER BETWEEN SECTIONS 1 and 12. 17
I set an Iron Pipe 1" x 36" also a Cedar Post 4" x 4" x 36" from which
A Maple 12" in dia. S.76°30'W., 10.7 ft. (FOUND 1963 - Ramsey SEE C.B. 51/258)
A B. Oak 8" in dia. N.43°00'W., 27.0 ft. 188

See OS 4/1/55

Ernst N. Val. 3, 7, 1913

✓ CORNER BETWEEN SECTIONS 2 and 11. 18
I set an Oak Post and a rock 6 x 6 x 12, also a gun barrel, marked 1/2 S. C.S. from which
A Fir 18" in dia. bears S.72°W., 17.2 ft. (SEE 1961)
A Fir 12" in dia. bears S.57°30'E., 22.0 ft. (DEPENDENT RESURVEY)

✓ CORNER BETWEEN SECTIONS 1 and 2. 19
I set a Fir post 4" x 4" x 30" from which
A Fir 30" in dia. bears N.30°E., 3.0 ft.
A Fir 18" in dia. bears S.65°W., 27.5 ft. 186

See C.S. 4/1/55

RE-NEWED CORNER NO. 186