

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 7 R. W. W. M.

H. L. Eppstein Sur
Wit.
Geo. Span
J. K. Falbe
Ed Jennings
Mar. 9, 1926.

CORNER TO SECTIONS 3, 4, 9 and 10.

Set corner from old tree, scribe marks plain on Black Oak. Laurel tree in good condition. Thirty inch fir in good condition. Set 4" x 4" x 3' Laurel Post. Marked trees thus

Laurel 20" dia. N.65°E., 24.5 ft. old tree
Fir 48" dia. N.53°W., 16.2 ft. old tree
Fir 9" dia. S.43°E., 33.0 ft. new tree
Fir 15" dia. S.55°W., 27.2 ft. New tree

ALSO #38

20

Ben. B. Irving
Wit.
Jas Byron
Bill Shepard
Gene Ollivant
May 12, 1927.
CS 37/113

SECTION CORNER BETWEEN SECTION 32 T.28-7 and SECTION 5 T.29-7.

Identified by an O.B.T. Oak N.40°W., 27.7 ft. and Laurel S.53°10'E., 35.0 ft. Set 5" Cedar Post and marked new B.T. Fir 20" dia. S.78°45'W., 51.3 ft.

Gordon Stewart previously used this as a corner. There is also a corner set by Cain for corner some 800 ft. E. and 130 ft. So. Some property owners have been claiming each corner. I believe this to be the corner as originally set by "Ford" but have not gone into it sufficiently to prove. Did not know of Cain's corner until after setting this one.

SEE ALSO #49

21

A. Boyer
D.C.S.
Oct. 15, 1941
Wit.
Geo. Ollivant
May 12, 1927.
V. 4 P. 83
CS 32/16

N. 1/4 CORNER OF SECTION 2 T.29-7

Original corner lost or obliterated. Set corner midway between N.E. Corner 2 and N.W. Corner 2. Drove 4 x 4 post, upon which

A White Fir 12" dia. bears N.35°E., 2.5 ft.
A White Fir 15" dia. bears S.45°E., 12.0 ft.

103

22

H. L. Eppstein, County Surveyor
Witnesses
Harold Bellows
N. E. Richardson
June 7, 1937.
Vol. 4, Pg. 39

MOST SOUTH-EASTERLY OR S.E. EXTERIOR "L" CORNER TO D.L.C. NO. 38.

A square carved rock 12" x 12" above ground in place for corner. B.T. gone. Marked new bearing tree

A 20" White Oak bearing S.61°W., 84.9 ft. marked
Cl. 38 C.S. B.T.

SET I. B. D. 200

23

N.W. CORNER OF CLAIM 38.

Set 1" x 30" Iron Pipe for corner from the old Pine Bearing Tree. Other tree gone. Marked

A 16" White Oak bearing S.13°W., 71.0 ft. marked
Cl. 38 C.S. B.T.

73

24

MOST SOUTHERLY OR SOUTH EXTERIOR "L" CORNER OF CLAIM 38.

Set in from a White Oak Stump bearing N.40°E., 134 lks. Showed sign of old Blaze in wood no scribe marks. Set 1" x 24" Iron Pipe for corner from which

A 10" White Oak bears N.75°45'W., 14.4 ft. marked
Cl. 38 C.S. B.T.

72

25

INTERIOR "L" CORNER OF D.L.C. NO. 38.

This corner was set from bearing and distance from the Exterior "L" corners both East and South. No original witness trees. Set 1" x 30" Iron Pipe for corner from which

A 14" White Oak bears S.74°E., 158.4 ft. marked
Cl. 38 C.S. B.T.

(FOUND) SEE RM 2-35

26

Ben B. Irving
Witness
N. E. Richardson
July 30, 1938.

N.E. CORNER OF SECTION 27.

Corners as recorded in the Government Field Notes in place except that the tree to the N.W. has been destroyed. Blazed and scribed

A Fir 8" diam. which bears N.29°W., 93 lks. T.29 S.,
R. 7 W., S.27 C.S.B.T.

183

27