

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 8 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97198

James W. Byron, Deputy County Surveyor
M. Godfrey
S. Bilow
Sept. 17-19, 1957
C. S. File No. 49/5

48

Section Corner To section 4 & 3, T29S, 33 & 34, T.28S.
Found- Original 20 inch now 36 inch R. Fir N.78°E., 37.6 feet. BT. Good Bark scribing "T.28S., R.8W., S.34" shows good scar near base. I don't open. #159
20 inch Laurel S.4°W., 113.5 feet, now down may be original BT, scribing not found.
18 inch Laurel S.80°E., 37.0 feet, shows old & rotted face. I believe this to be original.

Set Brass Cap at corner marked: $\frac{S33}{S4} | \frac{S34}{S3}$ T.29S. R.8W. County Surveyor's Office, 1957.
T.28S.

New BT's: 15 inch W. Fir S59°E. 18.6 ft. scribed T.29S, R.8W, S.3 CS BT.
15 inch R. Fir S.16°W. 18.8 ft. scribed T.29S, R.8W, S.4 CS BT.
22 inch R. Fir N.73°W. 47.6 ft. scribed T.29S, R.8W, S.33 CS BT.

Note - BT bark scribed. Sept. 19, 1957

49

$\frac{1}{4}$ Section Corner to sections 33 & 4.
Found - Fir tree, now 48 inch diam. N.40°E., 2.6 feet showing bark scribe " $\frac{1}{4}$ "S". Very plain and scar of lower blaze.
Fir Stump, now 48 inch diam. S.65°W., 19.8 feet. Chop out blaze and find scribe mark "B". Did not chop out low enough to find more.
Distances are from face of old blazes.

Set Brass Cap at corner marked: $\frac{S33}{S4}$ T.28S. 148
S 4 T.29S.

Northeast tree in very good condition.
Mark one new tree:
10 inch Red Cedar bears S.38°E., 37.1 feet (Scribed T29S, R8W, S4 CS BT.
Corner lies in bottom of gulch approximately 40 feet West of small creek.
Sept. 17, 1957

James W. Byron
For C.W. Couey
May 5, 1954
C.S. File No. 46/21
Map M 6 - 68

50

$\frac{1}{4}$ Section Corner to Sections 2 & 11.
Found - $1\frac{1}{2}$ " X $1\frac{1}{2}$ " Angle Iron at corner. Both BTs. as scribed by Boyer, in 1935 in poor condition. Parts of scribing visible. REN #24
30" B.O. N.3°E. measures 116.0 ft.
14" W.O. S.19 $\frac{1}{2}$ °W. " 128.0 ft.
We moved angle iron 4.7 ft. N.3°E. to fit Boyer's BTs. for bearings and distances. 154

Blazed & Scribed: 8" R. Fir N.39°E. 11.2 ft. $\frac{1}{4}$ S2 CS BT.
9" R. Fir S.29°W. 12.0 ft. $\frac{1}{4}$ S11 CS BT.

51

Section Corner to Sections 3, 2, 10, & 11.
Found - 7" X 3" Sandstone 2' above ground marked S2 T29S R8W. on #158
East side & Mound of Rocks.
Old Laurel 40" BT. S.30°E. 25 lks., parts of scribing visible.
Old rotted Oak Stump N.70°W. 41 lks., no scribing visible.
Old BT. 36" Laurel N.57°W. 34 lks., no scribing visible - rotted.

Blazed & Scribed: 14" R. Fir N.81°W. 16.0 ft. S3 T29S R8W CS BT.
6" R. Fir S.46°W. 42.4 ft. S10 T29S R8W CS BT.
6" R. Fir S.86 $\frac{1}{2}$ °E. 40.5 ft. S11 T29S R8W CS BT.
6" R. Fir N.64°E. 30.3 ft. S 2 T29S R8W CS BT.

7-5-72 - FOUND BRASS CAP SET BY ? J.M.P. C.S. FILE NO. 54/38

FOOK PER
PIESKE
JAN. 1986
M101-13

James W. Byron, Deputy
M. Godfrey
S. Bilow
July 17, 1958
C. S. File No. 49/100

52

$\frac{1}{4}$ Section Corner to Sec. 31, T29S R8W & Sec. 36 T29S R9W.
Found - Fir Stump, now 28" diam. S.33°E. 21.8 ft. Chopped out lower blaze & found "BT" scribed in wood. More recent bark scribing " $\frac{1}{4}$ " S BT".
Fir Stump, now 48" diam. N.42°W. 5.9 ft. Lower scar has been chopped into but not opened to original blaze.
Found more recent bark scribing " $\frac{1}{4}$ " CS".

Set Brass Cap at Corner Mkd: R9W S36/S31 R8W T29S County Surveyor's Office, 1958

New BT's: 12" W. Fir N.11°E. 32.3 ft. scribed " $\frac{1}{4}$ " S31 CS BT".
8" W. Fir S.28°W. 13.0 ft. scribed " $\frac{1}{4}$ " S36 CS BT".

53

Township Corner T29S-T30S, R8W-R9W.
Found - Sugar Pine Tree, now 45" at Twp. Corner.
Sugar Pine, now 45" N.80°E. 3.3 ft.
D. Fir, now 25" diam. S.88°W. 18.5 ft. Cut into this tree
(continued over)