

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

7

R. W. W. M.

KOYE-CHAPMAN CO., EUGENE, ORE. 97106

Ben B. Irving - James W. Byron - County Surveyor's Office
Ray Irving
February, 1954 - Work done in cooperation with County Engineer's Office in connection with County road No. 38.
Ordered by County Court. County Surveyor's File 46/36.

$\frac{1}{4}$ corner secs. 16 and 17.

Corner positively identified from old BT in good condition. Recorded N.46°E., 25 lks. Should be N.46°W. Also we found a 1 inch axle for corner. This tree is scribed BT X - 1 inch axle is from this tree. Tree was blazed and scribed about 35 to 40 years ago. An old fence post is N.10°E. 3.2 ft. Part of an old fir stump alongside a (upper) 24 inch Laurel bears N.46°E., 19 feet. Probable old BT for $\frac{1}{4}$ corner.

Replaced Axle with 1 inch X 36 inch iron pipe with brass cap - mound of rock 36 inches dia., X 18 inches high.

Blazed and scribed three new trees:-

Red Fir, 14 inches in dia., S.64 $\frac{1}{2}$ °W., 50.6 feet dist., mkd. $\frac{1}{4}$ S 17 CS BT.
B. O., 12 inches in dia., N.21°W., 17.8 feet dist., mkd. $\frac{1}{4}$ S 17 CS BT.
B. O., 6 inches in dia., N.39°E., 26.6 feet dist., mkd. $\frac{1}{4}$ S 16 CS BT.

Section corner to secs. 16, 17, 20 and 21.

Corner renewed from Orig. B T-42 inch Fir N.20°E., 44.9 feet. We cut out to old blaze and found several scribe marks.

Note: We found 3 inch by 3 inch scribed yewood post, from which

a 18 inch fir stump scribed BTX N 44 ° W 27.5 feet and

a 18 inch red fir stump, S.38°E., 8.8 feet scribed S x.

Bearing trees were scribed 30 or 40 years ago but were not recorded.

Set 1 inch iron pipe with brass cap mkd. 17, 16, 20, 21, County Surveyor's Office, T 29 S, R 7 W., 1954. From which

Blazed and scribed-

Red Fir, 10 inches in dia., N.52°E., 1.0 feet, mkd. T29S, R7W., S 16 C.S.BT.

Red Fir, 10 inches in dia., S.58°E., 18.7 feet, mkd. T29S, R7W., S 21 C.S.BT.

Red Fir, 10 inches in dia., N.75°W., 14.6 feet, mkd. T29S, R7W., S 17 C.S.BT.

Red Fir, 8 inches in dia., S.22°W., 25.8 feet, mkd. T29S, R7W., S 20 C.S.BT.

(This corner renewed again in 1957-see later notes)-REN. NO. 84.

Section corner to secs. 20, 21, 28 and 29.

Location identified from

Snag, 3 feet high, 9 inch B. O., S.20°E., 81 lks.-visible reverse 8 BT.

Snag, 12 feet high, 16 inch B. O. (now 24 inches), N.21°E., 19 lks., bottom blaze has been chopped out and is rotten.

18 inch W. O. (now 24 inches) dead, N.24°W., 80 lks. Blaze chopped out and tree rotten.

8 inch B. O., S.64°W., 62 lks.-gone-pieces of oak roots visible.

Set a 1 inch by 36 inch iron pipe with brass cap stamped County Surveyor's Office, T29S, R7W., S 20, S 21, S 28, and S 29., 1954.

From which

A Fir, 15 inches in dia., N.28°E., 18.8 feet, blazed and scribed, T29S, R7W., S 21 CS BT.

A Fir, 10 inches in dia., N.19 $\frac{1}{2}$ °W., 28.9 feet, blazed and scribed, T29S, R7W., S 20 CS BT.

A Fir, 7 inches in dia., S.50 $\frac{1}{2}$ °W., 15 feet, blazed and scribed, T29S, R7W., S 29 CS BT.

A Fir, inches in dia., S.33°E., 38.4 feet, blazed and scribed, T29S, R7W., S 28 CS BT.

Section corner to secs. 28, 29, 32, and 33.

Corner positively identified from brass cap at corner.

10 inch W. O., S.62 $\frac{1}{2}$ °W., 11 lks.

5 inch W. O., N.66°E., 40 lks. Ren.#52

Blazed and scribed two new trees-

Red Fir, 10 inches in dia., N.52°W., mkd. S 29 C.S. BT. 25 feet dist.

W. Fir, S.17°W., 12 inches in dia., mkd. S 32 C. S. BT. 70 feet dist.

$\frac{1}{4}$ corner to secs. 29 and 32.

Corner positively identified from brass cap at corner. Old Fir BT down and B. O. BT rotted in center.

Blazed and scribed two new trees:-

Red Fir, 14 inches in dia., S.1°E., 20.5 feet dist., Mkd. $\frac{1}{4}$ S 32 C.S. BT.

Red Fir, 10 inches in dia., N.75°E., 54.2 feet dist., Mkd. $\frac{1}{4}$ S 29 C. S. BT.