

Douglas County Surveyor's Record of
Government Corners Renewed

29

T. S.

7

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97186

James Byron, Deputy County Surveyor
Ray Irving John Fee
Work done for Engineers Office in connection with
work on Road No. 38.
1954.
C. S. File No. 46/36.

Southeast corner of the Daniel Wells Donation Land Claim No. 39. 75
(Angle point No. 6.)

The brass cap set by the government in 1924 survey was found in
Olalla creek bed by Carl Brady in 1953. Had been washed out in
previous flood.

No B. T.s could be found. Believe they have been washed out or destroyed.
We establish the So. line of D. L. C. 39 by using the existing fence line
and its projection.

We project the north-south Byron Brady property fence line to south
for intersection - See Ren. #37

This point of intersection gives the So. line distance as 3962.3 feet,
(record 3960.0 feet). Also checks record distance to creek.

Reset Brass Cap at point of intersection.

Blazed and scribed two trees:

A 12 inch Cedar, S. $46\frac{1}{2}^{\circ}$ E., 80.3 feet, marked A P 6 DLC 39 CS BT.

A 3 pronged Cedar, 6 ft. diam at base, N. 52° W., 204.6 feet dist.,
marked A P 6 DLC 39 CS BT.

W. P. to the S. E. cor. of the Dan'l Wells D. L. C. No. 39 (Angle Point No. 6) 76
Set Brass Cap for W. P., N. $2^{\circ}26\frac{1}{2}$ E., 90.9 feet from A. P. No. 6,

marked Co. Sur. Off. 1954, W. P. A P 6, 90.9 North, DLC No. 39.,

T 29 S, R 7 W.

Blazed and scribed two trees:

A 24 inch W. O., N. $52^{\circ}45'$ W., 139.5 feet dist., marked W P A P 6 CS BT,
D.L.C. No. 39.

A 40 inch Pine, N. $24\frac{1}{2}^{\circ}$ E., 532.3 feet dist., marked W P A P 6 CS BT DLC 39.

Corner found by crew
from County Surveyor's
Office. 1954.

A. P. No. 2 (Most northerly Ext. L cor. of the Dan'l Wells D.L.C. No. 39.) 77

At this corner was found an Iron Pipe with brass cap set by government
survey in 1924. There are no field notes pertaining to this corner
but the brass cap is marked by them and the bearing tree was marked
by them. Correspondence with the government office in Portland
disclosed that there were no notes for the corner. Although the
Portland office had no information as to how it was set, they
expressed confidence that it was set properly since it was done
out of their office. The County Surveyor's office did not check the
location of this corner and so cannot verify its validity.

One tree marked by government:

An 8 inch madrone, S. $77\frac{1}{2}^{\circ}$ W., 5.8 feet dist.

Section corner to secs. 5 & 6 (T29S, R 7W) and secs. 31 and 32 (T28S, R7W).
Found:

30 inch Fir stump, S. 83° E., 78.2 feet, bark scribed BT. - REN. No. 48 78

8 inch Fir, S. 20° W., 38.9 feet, some scribing visible. Tree pushed over.

24 inch Fir, Stump, N. 32° E., 54.4 feet. Log against scribing.

Set 1 inch x 30 inch Iron Pipe with brass cap mkd. $\frac{31}{6} \frac{32}{5} \frac{28}{29} \frac{S}{S}$ R 7W,
County Surveyor's Office, 1954.

Chisled 3 inch cross on high point of rock 12 feet x 10 feet, 8 feet high,
N. $78\frac{1}{2}^{\circ}$ W., 90.7 feet.

No trees near.

Var. $20\frac{1}{4}^{\circ}$ E.

SEE ALSO #14

James W. Byron, Deputy County Surveyor
Ray Irving
John Fee
April, May, 1955.
C. S. File No. 46/130.

$\frac{1}{4}$ sec. cor. to secs. 5 and 6.

Found 4 inch by 4 inch square stake scribed $\frac{1}{4}$ S.

The 10 inch B. O., S. 8° W., 4 lks. has been cut into and all scribing
destroyed. checks tree for bearing and distance.

Set brass cap mkd. $\frac{1}{4}$ S 6/5 T 29 S R 7 W Co. Su. Office 1955.

Corner 6 feet west of old wire fence.

Blazed and scribed:

7 inch R. Fir, N. 85° W., 17.0 feet, mkd. $\frac{1}{4}$ S 6 CS BT.

10 inch R. Fir, S. 19° E., 25.4 feet, mkd. $\frac{1}{4}$ S 5 CS BT.

79