

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 - S. T. S. R 7 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Eyrton, Deputy County Surveyor
Dale McFarland and John Powell
May - June 1962
C. S. File No. 49/139

$\frac{1}{4}$ Corner to Sections 8 and 17.
Found - 1 $\frac{1}{2}$ " I.P. at corner & both BT's, as recorded by Cain. - Ren #34
The S.W. BT. now snag.
New BT: 16" R. Fir bears S.2 $^{\circ}$ W. 13.0 ft. scribed $\frac{1}{4}$ S17 CS BT.

147

Renew

S31	T29S	R7W
S31	T29 $\frac{1}{2}$ S	

Found - Brass Cap at Cor. & both BT's., now down.
N.E. BT. shows scribing.
New BT's: 22" R. Fir bears N.69 $^{\circ}$ E. 18.0 ft. scribed S31 T29S R7W CS BT.
6" Chinquipin bears S.15 $^{\circ}$ E. 30.4 ft. scribed S31 T29 $\frac{1}{2}$ SR7W CS BT.

148

Renew W. P. 5.6 chains West of

S36	S31	T29S
	S31	T29 $\frac{1}{2}$ S

Found - Brass Cap at Corner. R8W R7W
Both BT's., now stumps.
New BT's: 7" Cedar bears S.75 $\frac{1}{2}$ $^{\circ}$ W. 37.1 ft. scribed W.P. CS S36 BT.
18" Laurel bears N.4 $^{\circ}$ W. 71.0 ft. scribed W.P. S36 CS BT.

149

Renew East $\frac{1}{4}$ Corner to Section 36 only, T29-8W.
Found - Brass Cap at Corner & under 3 ft. Fir Log.
N.W. BT., now low stump. S.W. BT., now down.
New BT's: 24" Laurel bears S.17 $^{\circ}$ W. 18.5 ft. scribed $\frac{1}{4}$ S36 CS BT.
10" Cedar bears S.82 $^{\circ}$ W. 42.0 ft. scribed E $\frac{1}{4}$ S36 CSET.

150

Renewed Corner to

T29 $\frac{1}{2}$ S	T29S
S34	S35
S 3	S 2
	T30S.

 R7W
Found - Brass Cap at Corner & all BT's, except N.E. BT.
New BT: 6" R. Fir bears N.39 $^{\circ}$ E. 5.3 ft. scribed S35 CS BT.
FD. O.K. H. JOHNSTONE

151

Section Corner to Sections 17 - 18 - 19 - 20.
Found - Orig. 24", now R. Fir S.16 $^{\circ}$ W. 9.2 ft., shows good scar.
We do not open.
16", now 20" Maple N.14 $^{\circ}$ W. 50.2 ft., shows scar.
Other 1924 BT's, not snags.
Note End of Wire Fence to East S.70 $^{\circ}$ E. 10.0 ft.
New BT's: 16" R. Fir bears S.34 $^{\circ}$ E. 8.3 ft. scribed S20 T29S R7W CS BT.
7" W. Fir bears N.52 $^{\circ}$ E. 46.7 ft. scribed S17 CS BT.

152

Section Corner to Sections 7 - 8 - 17 - 18.
Found - Brass Cap at Corner & Stump of S. W. BT., shows scar.
S.E. & N.E. BT's. down. N.W. BT. not found.
New BT's: 10" R. Fir bears S.59 $^{\circ}$ E. 17.5 ft. scribed S17 T29S R7W CS BT.
4" R. Fir bears N.40 $^{\circ}$ E. 21.6 ft. scribed S8 CS BT. #230
9" R. Fir bears S.9 $^{\circ}$ W. 33.5 ft. scribed S19 T29S R7W CS BT.
No trees near to N.E.

153

Section Corner to Sections 19 - 20 - 29 - 30.
Found - Brass Cap & BT's. set in 1924 as follows:
10" Fir N.38 $^{\circ}$ E. 17 ft. (down)
18" Fir S.65 $^{\circ}$ E. 38 ft. O.K.
12" Fir S.23 $^{\circ}$ W. 26 ft. O.K.
12" Fir N.17 $^{\circ}$ W. 37 ft. O.K.
New BT: 14" Fir N.68 $\frac{1}{2}$ $^{\circ}$ E. 17.7 ft. mkd: T29S R7W S20 CS BT.

154

$\frac{1}{4}$ Corner to Sections 29 and 30.
Found - Brass Cap set in 1924 and Laurel BT. bearing S.11 $\frac{1}{2}$ $^{\circ}$ W. 86 ft. (O.k.)
30" Pine gone.
New BT: 9" Fir N.89 $^{\circ}$ E. 18.4 ft. mkd: $\frac{1}{4}$ S29 CS BT.

155