

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

217

Sec. Corner for Secs. 17, 18, 19 and 20
 Found - 1924 GLO brass cap on a 2" I.P. approx. 7" above ground.
 An orig. 40" now 50" Fir, rotted stump, bears N.51°E., 9 ft. to center (rec. 7.92 ft.). No visible scribing.
 An orig. 14" Fir now an 18" windfall bears S.42 1/2°E., 7.92 ft. no visible scribing.
 An orig. 24" Fir now 33" bears S.16°W., 9.24 ft. Alive and well-healed with healed over blaze.
 An orig. 30" Fir now a stump bears N.47°W., 7.26 ft. I do not open.
 1924 BT, a 14" Cedar, now a 15" dead windfall bears N.24 1/2°E., 55.4 ft. Faint scribing visible
 A 22" Fir now a 26" down Fir, 1924 BT, bears S.69°E., (rec. S.71°E.) 9.4 ft. Broken off at root crown. Faint visible scribing "R7W"
 1924 BT, a 16" Maple, now an 18" down Maple, bears N.14°W., 50.16 ft. Tipped out and well rotted. Healed over blaze.
 The S.W. BT in the 1924 resurvey is gone.
 A 7" W. Fir, now 13" bears N.52°E., 46.7 ft. Alive and well with well healed blaze. Ren. #152
 A 16" R. Fir, now dead and down bears S.34°E., 8.3 ft. No scribing visible. Healed blaze.
 New BT's-A 17" W. Fir bears S.68°E., 82.8 ft. Double blazed and scribed T29S R7W S20 CS BT.
 A 18" D. Fir bears N.64°W., 48.9 ft. Doubled blazed and scribed T29S R7W S18 CS BT.
 Note - Fence line as recorded by Byron in Ren. #152 still in recorded place. 1/10/77

218

1/4 Corner for Secs. 20 and 21. *FD OK BY HEIMBURGER 1992-0035*
 Found - 1966 BLM brass cap on 2 1/2" I.P. set flush in the ground near the bottom of the cutbank, approx. 10 ft. west of the west edge of the asphalt concrete of Olalla Road, cap properly marked.
 Note - This cap is oriented facing south with steel fence post alongside.
 From Which:
 A 13" now 14" D. Fir alive and well healed, bears S.65°E., 96.4 ft.
 13" now 13" D. Fir Snag, burned and well healed bears N.76°W., 28.4 ft.
 New BT - A 13" D. Fir bears N.50 1/2°E., 192.3 ft. scribed "1/4 S21 CS BT" on a double blaze. 1/10/77

219

Corner for Tr. 50
AP 3
AP 2
 Tr. 51
 Found - a 1" I.P. 14" high with 1924 GLO brass cap properly stamped. Corner is at the northwest corner of a large natural clearing. (Rock bluff).
 A B. Oak, 6" now 38" bears S.71°E., 73.9 ft. (rec. S.73°E.) Due to size of tree, blaze not visible, I do not open for scribing.
 A B. Oak, 8" now 30" bears N.0 1/2°E., 70.5 ft. (rec. N.0 1/2°W., 69.3 ft.) Due to size of tree, blaze not visible, I do not open for scribing.
 A B. Oak 15" now down and rotting bears N.28°E., 27.7 ft. Tree has old blaze (SE BT per 1924 survey is not found.)
 A R. Fir, 8" now 15" bears N.12°E., 28.7 ft. Tree has well healed double blaze. Ren. #136
 A R. Fir 14" bears S.16°E., 11.3 ft. (Rec. 10.9 ft.) Tree has well healed double blaze. Ren. #136 2/3/77

220

1/4 Corner for Secs. 8 and 17.
 Found - 1 1/4" I.P. approx. 14" above ground. Ren. #147
 A D. Fir, 8" now 27" bears N.20 1/2°E., 19.8 ft. Blaze has been previously partially opened, is now well healed. Ren. #34
 A R. Fir, 16" now 22" bears S.2°W., 13.0 ft. Tree has pitched over blaze. Ren. #147
 Note: SE BT per Ren. #34 is now down. Lying ENE of rec. position approx. 10 ft.
 Set - 1" x 30" I.P. with brass cap attached at 1/4 cor. stamped:
 "Douglas Co. Surveyor" T29S R7W
 1977 1/4 S 8
 S 17
 Set 1 1/4" x 36" I.P. beside cap. 1/10/77

L. E. Monrean
 Karen Cheney
 P. L. Earle
 Jan. 10, 1977
 C.S. 59/29

Douglas County Surveyors Office

Gary L. Langlitz
 A. Victor Cangie
 Mike Tompkins
 Jan. 10, 1977
 C.S. 59/29

Larry E. Monrean, Douglas County Surveyors Office
 Karen Cheney
 Pete L. Earle
 Jan. 13, 1977; Feb. 3, 1977
 C.S. 59/29