

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 29 T. S. R 7 R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

Gary L. Langlitz, Doug. Co. Surveyors Office
Stephen J. Flause
P. Earle
June 1977
C.S. 59/34

RM 3-8

237

South 1/16 between Secs. 17 and 18.
Set - 5/8" x 30" Iron rod with alum. cap attached marked "Douglas Co. Surveyor S 1/16 S18 S17
Placed steel fencepost with survey marker witness sign attached alongside 5/8" Iron rod.
No accessories.

6/2/77
238

Southwest 1/16 Sec. 17.
Set - 5/8" x 30" Iron Rod with alum. cap attached, marked "Douglas Co. Surveyor SW 1/16 S17.
Placed steel fencepost with survey marker witness sign attached alongside 5/8" Iron rod.
No accessories.

6/2/77
239

South Center 1/16 Sec. 17.
Set - 3/4" x 24" Iron pipe 20" in the ground with anchor rod extended and brass cap attached marked "Douglas County Surveyor" T29S R7W C S1/16 S17 C 1977.
BT's- A 10" D. Fir scribed "CS 1/16 S17 CS BT" on a double blaze bears S.3°E., 16.3 ft.
A 10" P. Pine scribed "CS 1/16 S17 CS BT" on a double blaze, bears N.80°W., 32.7 ft.
Corner set from survey by proportionate measurement.

6/8/77

1/4 Corner for Secs. 17 and 20.
Set - 1" x 30" I. Pipe 26" in the ground with brass cap attached marked Douglas County Surveyor 1977
T 29 S R 7 W
1/4 S 17
S 20
Corner location determined by single proportionate measurement.
BT's - A 10" W. Oak scribed "1/4 S17 CS BT" on a double blaze bears N.61°W 21.5 ft.
A 28" I. Cedar, scribed "1/4 S20 CS BT" on a double blaze bears S. 2 1/2°W., 23.6 ft.
Note - Approx. 50 ft. south of a small ravine, course S.50°W.

240

6/8/77

Center West 1/16 Sec. 17.
(Corner location determined by proportionate measurement)
Set - 3/4" x 24" I. Pipe 20" in ground on steep southerly slope with Brass cap attached marked: Douglas County Surveyor T29S R7W 1977
W 1/16
C-----C
S17
BT's- A 8" D. Fir scribed "CW 1/16 S17 CS BT" on a double blaze, bears S.21°W., 31.5 ft.
A 8" D. Fir scribed "CW 1/16 S17 CS BT" on a double blaze, bears S.61°E., 34.2 ft.

241

Note: Corner of fences running North and East bears S.68°W., 27.4 ft.

6/14/77

242

Center 1/4 Corner for Sec. 17
(Corner location determined by intersection of lines connecting opposite 1/4 corners of Sec. 17.)
Set - 1" x 30" I. Pipe 26" in the ground on steep and brushy NW slope with Brass cap attached marked: Douglas County Surveyor T29S R7W C 1/4+S 17
BT's - A 15" D. Fir scribed C 1/4 S17 CS BT" on a double blaze, bears N.31°E., 45.8 ft.
A 22" D. Fir scribed C 1/4 S17 CS BT" on a single blaze, bears S.54°E., 23.8 ft.

6/14/77