

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

North 1/16 Corner for Secs. 19 and 20.

247

Corner location determined by survey.

Set - At the corner point we set a 1" x 30" I.P. 20" in the ground to bedrock with brass cap attached marked: Douglas County Surveyor

T 29 S R 7 W
N 1/16
S 19 S 20
1977

BT's - An 8" P. Pine scribed "N 1/16 S19 CS BT" on a double blaze, bears N.51°W., 31.4 ft.

A 12" I. Cedar, scribed "N 1/16 S20 CS BT" on a double blaze, bears N.18°E., 20.0 ft.

Corner located along old N-S cutting line.

10/12/77

248

Center 1/4 for Sec. 20.

Location of corner determined by intersection of lines from opposite exterior 1/4 corners.

Set - A 1" x 30" I.P. 26" in the ground with brass cap attached marked: Douglas County Surveyor

T 29 S R 7 W
C 1/4 S 20
1977

BT's - A 34" B. Oak scribed "C 1/4 S20 CS BT" on a double blaze bears N.38 1/2°W., 23.2 ft.

A 12" D. Fir scribed "C 1/4 S20 CS BT" on a double blaze bears N.2°E., 45.7 ft.

Located along edge of meadow, approx. 50 ft. east of Berry Creek and approx. 250 ft. south of a house. Placed steel fence post with survey marker witness sign attached 1.0 ft. west of corner.

10/11/77

249

Center west 1/16 Section 20.

At corner position as determined by survey:

Set - 1" x 30" I.P. with brass cap attached 3" above ground marked: "Douglas County Surveyor"

T 29 S R 7 W
C $\frac{W 1/16}{S 20}$ C

Small mound of stone around cap. 1977

BT's - A 14" D. Fir bears N.48°E., 31.3 ft. scribed "CW 1/16 S20 CS BT" on a double blaze.

A 8" D. Fir bears N.85 1/2°W., 48.0 ft. scribed "CW 1/16 S20 CS BT" on a double blaze.

5/8" I. Rod with unmarked alum. cap bears N.41 1/2°W., 82.0 ft.

See County Surveyor file M 57 - 76.

10/11/77

250

North 1/16 Section 20.

Corner location determined by survey.

At the corner point WE SET a 1" x 30" I.P. 26" in the ground on a steep west slope with brass cap attached marked: Douglas County Surveyor

FD OK

T 29 S R 6 W
C
N 1/16 S 20
C
1977

BT's - An 8" D. Fir scribed "CN 1/16 S20 CS BT" on a double blaze, bears S.23°E., 31.3 ft.

A 12" I. Cedar, scribed "CN 1/16 S20 CS BT" on a double blaze, bears N.79°E., 14.4 ft.

Corner located approx. 70 ft. south of an E-W fenceline.

Douglas County Surveyors Office
Gary L. Langlitz
Larry E. Monrean
Peter L. Earle
Stephen J. Flause
October 1977
RM 3-8
C.S. 59/40