

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 29                      T. S.                      R 7                      R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97401

Douglas Co. Surveyors Office  
Gary Langlitz  
Peter Earle  
Larry Monrean  
Steve Flause  
October 1977  
C.S. 59/40

RM 3-8

Douglas County Surveyors Office  
Gary L. Langlitz  
Larry E. Monrean  
P. Earle - K. Cheney - S. Flause  
November, 1977  
C.S. 59/42

**251**

Northwest 1/16 Section 20.  
Corner position determined by survey.  
Set - A 1" x 30" I.P. 27" in the ground with brass cap attached marked:  
"Douglas County Surveyor"  
T 29 S R 7 W  
NW 1/16 S 20  
1977  
BT's - A 9" D. Fir bears S.24°E., 32.6 ft. tree scribed "NW 1/16 S20 CS BT" on a double blaze.  
A 12" Grand Fir bears S.41°W., 19.8 ft. Tree scribed "NW 1/16 S 20 CS BT" on a double blaze.

10/12/77

**252**

Northeast 1/16 Section 20.  
Corner position determined by survey.  
Set - 3" brass cap with 4" shank in bedrock 1" below rock surface at corner. Cap is marked "Douglas Co. Surveyors Office"  
T 29 S R 7 W  
NE 1/16 + S20 1977"  
Mound stone approx. 3 ft. at base and approx 10" high around cap. Top of stone mound approx. flush with top of ground.  
BT's- A 6" White Oak bears N.40°E., 25.0 ft. scribed "NE 1/16 S20 CS BT" on a double blaze.  
A 18" P. Pine bears S.74°E., 29.2 ft. scribed "NE 1/16 S20 CS BT" on a double blaze.  
N.37°W., 86 ft. to a fence corner. Fence runs West and random South. Corner lies on a south slope approx. 80 ft. south of the northerly end of a natural clearing.

10/17/77

**253**

Center East 1/16 Corner for Sec. 18.  
Corner determined by single proportionate measurement.  
Set - A 1" x 30" I.P. 26" in the ground with brass cap attached marked:  
Douglas County Surveyors                      T 29 S R 7 W                      1977  
E 1/16  
C ← C  
S 18  
BT's - A 16" W. Oak bears S.10°E., 140.2 ft. scribed "CE 1/16 S18 CS BT" on a double blaze.  
A 10" D. Fir bears S.89°E., 79.4 ft. scribed "CE 1/16 S18 CS BT" on a double blaze.  
Note: Placed steel fence post with survey marker sign attached one foot north of the corner.

11/21/77

**254**

Southeast 1/16 for Sec. 18.  
Corner determined by survey.  
Set - A 5/8" Iron rod 30" long 26" in the ground with Douglas County Surveyor Alum. cap stamped "SE 1/16 S 18 1977".  
Set - Metal fence post and survey marker sign 1 foot south of corner.

11/21/77

**255**

Center south 1/16 for Sec. 18.  
Corner determined by single proportionate measurement.  
Set - 5/8" x 30" Iron rod 26" in the ground with alum. cap attached marked: Douglas Co. Surveyor S 1/16 C S 18  
C  
1977

Placed steel fence post with survey marker witness post attached one foot south of the corner.

11/9/77

**256**

Center east 1/16 for Section 20.  
Corner point determined by single proportion.  
Set - A brass cap 3" diam. with a 4" shank in drill hole in rock. Cap marked: "Douglas County Surveyors Office T29S R7W C  $\frac{E\ 1/16}{S\ 20}$  C 1977". Cap set approx. 10" below natural ground cover.  
BT's - A 22" P. Pine bears N.26°E., 92.3 ft. Tree scribed "CE 1/16 S20 CS BT" on a double blaze.  
A P. Pine 10" bears S.71°E., 147.4 ft. Tree scribed "CE 1/16 S20 CS CT" on a double blaze. Set sign and metal fence post S.19°E., 1.9  
Mound of stone around base of post.

11/7/77