

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29

T. S. R 7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21801

267

Center 1/4 Corner for Sec. 15  
 Found - A 13" D. Fir now a dead standing snag bears S.35°E., 172.5 ft.  
 Tree has a partially healed blaze with scribing visible  
 "CS 15 CS". Ren. #185  
 A 15" D. Fir now a stump bears S.17°E., 158.2 ft. scribing  
 visible "BT" on an unhealed blaze. Ren. #185  
 Brass cap monument set in 1965 NOT found. Ren. #185 and M29 - 48  
 Set - A 1" x 36" I.P. with brass cap attached at corner position.  
 Cap is stamped "Douglas Co. Surveyor T 29 S R 7 W C 1/4 S15  
 1981"  
 New BT's A 4" Fir blazed "X" bears S.79 1/2°W., 4.4 ft.  
 A 9" D. Fir scribed "C 1/4 S15 CS BT" on a double blaze bears  
 N.34 1/2°E., 64.0 ft.  
 A 10" Pine scribed "C 1/4 S15 CS BT" on a double blaze bears  
 N.27 1/2°W., 93.1 ft.  
 No other trees in area suitable for scribing.

Larry E. Monrean  
 Deputy, Doug. Co.  
 Surveyors Off.  
 Witnesses: G.E.  
 Quibell - K.  
 Mosley  
 March 3, 1981  
 C.S. 61/19

3/3/81

268

Cor between Sec's. 26 and 26 1/2, on the South boundary of Sec. 23.  
 Found - An unrecorded I.P. w/alumina cap, B.L.M. monument firmly  
 in place; cap is stamped: T29S R7W S23 S26 1/2 S26 1981  
 Along Southeast edge of BLM mon. is a stone buried nearly  
 flush with ground. The stone measures 6 1/2 " x 7" across  
 the top. Top of stone is marked: 2 26 1/2; East face has 2 notches.  
 BT's - NO original or 1924 Resurvey bearing trees were found. The  
 following brng. trees are from Ren.# 28.  
 8" Cedar with well healed double blaze, bears S.18°W., 16.1-ft.  
 (Rec. S.15°W., 16.5-ft.  
 8", now 14" Fir with well healed double blaze, bears S.17 1/2 °W.,  
 14.5-ft. (Rec. S.20°E.).  
 New BT's- 12" Fir, scribed T29S R7W S26 CS BT on a double blaze, bears  
 S.54°E., 11.2-ft.  
 8" Fir, scribed S23 CS BT on a double blaze, bears N.44 1/2°W.,  
 8.6-ft.  
 NOTE = Brngs. & Dist. recorded are from BLM Cap position. 10/6/81

Larry E. Monrean  
 Deputy Douglas County  
 Surveyors Office  
 T.L. Buley, witness  
 Oct. 6, 1981  
 C.S. 61 / 29

269

Witness Point to Sec. corner common to Sec's. 6, & 7 of T.29-7, only.  
 Found - Did NOT find the 1924 B.C. as it appears to be buried by a new  
 driveway fill, approximately 7-ft. deep.  
 BT's - 32" now 42" W. Oak w/good scar (Rec. N.55°E., 89.8-ft. per Resurvey.)  
 (Rec. N.57°E., 89.0-ft. per Ren.# 31 in T.29-7).  
 12" now 18" W. Oak stump in poor condition, w/scribed "WP BT"  
 visible. (Rec. S.21°E., 110.2-ft. per Resurvey.).  
 BO - B.C. for Sec. corner common to Sec's. 6 & 7 of T.29-7, only,  
 (Rec. West 119.0-ft. per Ren.#31), mkd. T29S S6 S7 R7W 1924  
 Set - Using both Orig. BT's, I set a B.C. at Record bearing & dist.,  
 marked: Douglas Co Surveyor WP 1981.  
 1981 B.C. bears S.55°W., 89.8-ft. from 32", now 42" W. Oak.  
 1981 B.C. bears N.21°W., 110.2-ft. from 12", now 18" W. Oak.  
 1981 B.C. is on Westly edge of driveway & protrudes 3" above ground  
 New BT's- 20" Fir scribed "WPCS BT" in dbl.blaze bears S.64°W., 19.1-ft.  
 20" Cedar scrbd "WPCS BT" in dbl.blaze bears N.56°W., 6.3-ft.  
 12" Fir scribed "WPCS BT" in dbl.blaze bears S.33°E., 85.4-ft.  
 The found B.C. for Sec. cor. to Sec's.6 & 7 of T.29-7 only,  
 bears S.89°E., 119.2-ft.  
 Note - For sketch, see C.S. 61 / 29 11/3/81

Gregory E. Quibell  
 Deputy Douglas County  
 Surveyors Office  
 Teresa Buley, witness  
 Nov. 3, 1981  
 C.S. 61/29

TREE TO BE REMOVED  
 BY LANDOWNER  
 C.S. 62/7

270

Section corner for Secs. 6 and 7 only  
 REFERENCED NOTES ONLY  
 Found - 1924 resurvey brass cap buried 2 ft. in edge of roadbed.  
 1 1/4" x 44" drill steel, protruding 12" out of ground, along side.  
 Drill steel apparently used as a guard stake.  
 10" now 17" fir bears S.22°E., 50.8 ft. Tree has good scar. Ren.141  
 Old 1" I.P. per Ren. #141 bears S.1°W., 47.0 ft. I.P. is located in  
 old N-S fence.

Gregory Quibell  
 Deputy, Doug. Co.  
 Surveyors Office  
 Teresa Buley  
 Nov. 2, 1981  
 C.S. 59/30

RE-RELEASED  
 FILED NO. # 282

CONT NEXT PAGE