

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ Section Corner to Sections 14 & 23. 80
Found - Orig. 10", now 26" Cedar Snag S.41°E. 39.6 ft., previously
opened, shows good scribing "18".
No trace of Original N.E. BT.
Set Brass Cap at Corner Mkd: $\frac{1}{4}$ $\frac{S14}{S23}$ T29S R8W County Surveyor's
Office, 1958
New BT's: 16" Cedar bears S.58 $\frac{1}{2}$ °W. 17.5 ft. scribed $\frac{1}{4}$ S23 CS BT.
14" R. Fir bears N.29°E. 27.0 ft. scribed $\frac{1}{4}$ S14 CS BT.

Section Corner to Sections 3, 4, 9, & 10. 81
Found - Orig. 30", now 36" Fir Stump N.70°W. 8.6 ft., shows good bark
scribing "T29S R8W".
Orig. 30", now 40" Fir S.60°W. 15.8 ft., shows good bark
scribing "T29S R8W S BT". This BT. has been rebark scribed
10 years ago more or less.
No trace of S.E. or N.E. BT's.

Set Brass Cap at Corner Mkd: $\frac{S4}{S9}$ $\frac{S3}{S10}$ T29S R8W County Surveyor's
Office, 1958 156

Note : I find 3/8" Iron Rod bears N.80°E. 1.9 ft.
New BT's: 7" W.Fir bears S.7 $\frac{1}{2}$ °E. 22.7 ft. scribed S10 T29S R8W CS BT.
11" W.Fir bears N.61°E. 41.1 ft. scribed S 3 T29S R8W CS BT.
24" D.Fir bears N.87 $\frac{1}{2}$ °W. 8.0 ft. bark scribe T29S R8W S9 CS
Scribed "BT" in wood.

$\frac{1}{4}$ Section Corner to Sections 3 & 4. 82
Found - Both Orig. BT's:
20", now 30" Fir, down, shows good bark scribing "BT",
S.52°E. 10.6 ft.
12", now 20" Laurel S.45°W. 29.7 ft. Rotted face, no
scribing found.
Set Brass Cap at Corner Mkd: $\frac{1}{4}$ S4/S3 T29S R8W County Surveyor's
Office, 1958
New BT's: 10" W.Fir bears S.80°W. 15.5 ft. scribed $\frac{1}{4}$ S4 CS BT.
8" W.Fir bears S.59°E. 42.7 ft.

Section Corner to Sections 29, 30, 31, & 32. 83
Renewed - Set Pitch Limb Post & Iron Pipe $\frac{1}{4}$ "
Orig. BT's: 20" Fir, dead, N.60°W. 48 lks. = 32"
15" Oak, about dead, N.77°E. 106 lks. = 70".
30" Fir S.8°W. 115.5 ft.
New Trees: 18" Fir S.49 $\frac{1}{2}$ °E. 29.0 ft.
30" Fir N.60 $\frac{1}{2}$ °W. 53.0 ft. (Same as #4)

Section Corner to Sections 28, 29, 32, & 33. 84
Set 4" x 4" x 36" Fir Stake REN #23
Orig. Trees: 60" Fir N.57°W. 51 ft.
12" Laurel N. E. Laying down.
New Trees: 12" Fir S.43°W. 35 $\frac{1}{2}$ ft.
30" Cedar S.5°E. 33 ft.
8" Fir N.35 $\frac{1}{2}$ °E. 22.8 ft.

$\frac{1}{4}$ Section Corner to Sections 21 & 22. 85
Found - Orig. 18", now 36" Stump, previously opened, shows good
scribe, "1" N.25°E. 11.2 ft.
Orig. 12", now 18", down & partly rotted Chinquipin, shows
rotted face, checks for bearing & dist. for Orig. S.W. BT.
Boyer's 40", now Stump W.40°W. 36.5 ft., shows bark scribing. REN #26
Set Brass Cap at Corner Mkd: $\frac{1}{4}$ S21/S22 T29S R8W County Surveyor's
Office, 1958
New BT's: 10" E. Fir bears S.57°W. 33.8 ft. scribed $\frac{1}{4}$ S21 CS BT.
12" Cedar bears N.59°E. 21.0 ft. scribed $\frac{1}{4}$ S22 CS BT.

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
September & October, 1958
C. S. File No. 49/100

Cole
Richardson
Stobie
April, 1923
C. S. File No. 16/25

James W. Byron, Deputy
Milo Godfrey
S. A. Bilow
Oct. 8, 1958
C. S. File No. 49/100

RE-RENEWED SEE CORNER NO. #199