

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 8 R. W. W. M.

KOKS-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron, Deputy County Surveyor
Milo Godfrey
S. A. Bilow
October 29, 1958
C. S. File No. 49/100

Fd 10/4ew
Post. 3/90
1990-0028

S. E. Corner of D. L. C. No. 43. 92
Found - 1 1/4" Iron Pipe at Fence Corner. - Ren. #5
Orig., now 20" W. Oak N.11°W. 38.9 ft., shows old scar,
rotted face, checks bearing & distance.
Both Stumps of BT's recorded by Cole, 1923., No scribing
found, bearing recorded N.43 1/2°E. should be N.38 1/2°E.
Other bearing to S. E. BT. O.K. Both Distances Check.
I do not Set Brass Cap at Corner.
New BT's: 6" W.Oak bears S.30°W. 37.3 ft. scribed S.E. Cl. 43 CS BT.
Rescribe Orig., now 20" W.Oak N.11°W. 39.9 ft., scribed
S.E. CL. 43 CS BT.

Section Corner to Secs. 32 & 33, T.29S.R.8W. & Secs. 4 & 5 T.30S., R.8W. 93
Found - Scribed Stake Set by Boyer, 1939. C.S. 16/25
Orig. Cedar, now 32" diam., this had been chopped open to
expose scribing "T30 R8W S5", can be plainly read. #186
Orig. Laurel, now 24" bears N.46°W. (instead of N.50°W.) 19.1 ft.
Center has entirely rotted away, but was rescribed by Boyer,
scribing "S32 29S R8W CS & T" can be plainly read.
No trace found of other 2 Orig. BT's.
Found 30" Fir N.41°E. 25 ft. bark scribed "S33 T29S R8W CS BT".
Found 60" Fir S.9°E. 50 ft., on slope, bark scribed "S4 30/8 CS BT".
All distances measured from face of blaze.
At Corner Set Iron Pipe with Brass Cap Mkd. "County Surveyor's Office, 1958."

S32	S33	T29S R8W
S 5	S 4	T30S R8W

Blaze & Scribe 7" W. Fir N.36°W. 39.6 ft. Mkd. "T29S R8W S32 CS BT."

Section Corner to Sections 8, 9, 16, & 17. 94
Found - Scribed Stake at Corner & at Fence Corner. Ren. No 36
Orig. 10", should have been 5" R. Fir, now 14", down,
S35°E. 30.2 ft., I open near base & find good scribing "T",
I find bark scribing by B.B.I. on this BT., recorded by him,
12" D. Fir S.40°E. 29.0 ft.
Down & partly covered 36" Fir that checks bearing & distance
for Orig. N. W. BT.
No other BT's. found.
Set Brass Cap at Corner Mkd:

S 8	S 9	T29S R8W	County Surveyor's
S17	S16		Office, 1958

New BT's: 10" R.Fir bears S.55°E. 47.4 ft. scribed S16 T29S R8W CS BT.
17" Cedar bears N.86°E. 78.0 ft. scribed S9 T29S R8W CS BT.
8" W.Fir bears S.71°W. 47.1 ft. scribed S17 T29S R8W CS BT.
19" Cedar bears N.10°W. 60.0 ft. scribed S 8 T29S R8W CS BT.

South 1/4 Section Corner to Section 32. 95
Found - 3" x 4" Cedar Stake (scribed) set by Boyer in 1939. (C.S. 16/25)
Red Cedar, now 10", N.10 1/4°W. 4.3 ft. blaze nearly covered but
traces of scribing can be seen.
Dense Cedar, approx. 62" diam. with scribing "S5 CS BT" plainly
visible. (Distances to Face)
At Corner Set Iron Pipe with Brass Cap Mkd.: "County Surveyor's Office,
1958 T29S R8W South 1/4 S32
T30S R8W
Blaze & Scribe one new tree in Sec. 32: 10" D. Fir N.88°W. 21.5 ft.
Mkd. "1/4 S32 CS BT."

1/4 Section Corner to Sections 32 & 33. (C.S. 16/25) 96
Found - Both BT's as filed by Boyer. I do not find either Orig. BT.
40" Cedar N.55 1/2°E. 23.0 ft., good condition, scribing visible.
36", now down Fir S.48°W. 14.8 ft., shows good bark scribing.
Find Scribed Stake at Corner
Set Brass Cap alongside Stake & Mark: 1/4 S32/S33 T29S R8W County
Surveyor's Office, 1958
New BT: 7" W. Fir bears S.79°W. 17.2 ft. scribed 1/4 S32 CS BT.