

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 8 W. R. W. W. M.

MOKE-CHAPMAN CO. EUGENE, ORE. 91891

Orig. BTs fd. per CS 52/114: 46" W.Oak S.60°E, 38.9'. Shows old axe work, face rotted. No scribing fd. (orig. NW BT not fd.) Corner lies in field. (this info

Witness Corner to

1/4 Corner to Sections 7 and 8.
From Orig. Bearing Trees.

Set - 3/4" I. Rod at 1/4 Cor. 8" under.

Brass Cap in Fence Corner Mkd: Withess Cor. 21' West to 1/4 Cor. S7/S8, T29S R8W.

New BT's: 17" R.Fir S.44°E. 9.7 ft. scribed W.C. 1/4 S8 CS BT.
33" W.Oak S.39°W. 95.0 ft. scribed W.C. 1/4 S8 CS BT.

Fd. by NORTH CRAFT FEB, 1983

100

Section Corner to Sections 7 - 8 - 17 - 18. - By Double Proportion.

Set - Brass Cap Mkd: County Surveyor's Office, 1962

S7	S8
S18	S17

T29S R8W

New BT's: 12" Myrtle bears S.64°E. 12.9 ft. scribed S17 T29S R8W CS BT.
30" Maple bears N.79°W. 39.0 ft. scribed S7 T29S R8W CS BT.
11" R.Fir bears N.43°E. 121.0 ft. scribed S8 T29S R8W CS BT.
6" Myrtle bears S.51°30'W. 43.0 ft. scribed S18 CS BT.

101

1/4 Corner to Section 8 and 17. - By Proportion.

Set - Brass Cap Mkd: County Surveyor's Office, 1962

S8
S17

T29S R8W

New BT's: 14" R.Fir S.38°30'W. 42.4 ft. scribed 1/4 S17 CS BT.
10" W.Oak N.17°E. 136.6 ft. scribed 1/4 S8 CS BT.

SEE AFFIDAVITE C.S. 42/404 52/114

102

1/4 Corner to Sections 7 and 18. - By Proportion.

Set - 3/4" I. Rod flush with pavement, 4.5ft. W. of centerline Co. Road from which a 26" Dble. R.Fir bears S.52°E. 38.3 ft. scribed 1/4 S18 CS BT.

Also set 3/4" I.R. 24' west of 1/4 cor. (info added 1/28/85) per CS 52/114.

103

1/4 Corner to Sections 18 and 17. W.C.

Set - Brass Cap 262.0 East of Cor. Mkd: County Surveyor's Office 262.0 ft. to 1/4 S18/S17 T29S R8W from which:

10" R.Fir bears N.2°E. 33.9 ft. scribed W.C. 1/4 S17 CS BT.
12" R.Fir bears S.71°E. 2.0 ft. scribed W.C. S17 CS BT.

Found - Sandstone Rock 12" under with + on top. Set 3/4" I. Rod at 1/4 Corner flush with top of rock. *SEE REN NO. 17*

104

Section Corner to Sections 17 - 18 - 19 - 20.

Found - Stone with + on top 12" under & 10' West of Creek Bank.

Set - Brass Cap alongside Stone Mkd: County Surveyor's Office, 1962

S18	S17
S19	S20

T29S R8W

New BT's: 14" Ash N.9°30'E. 30.3 ft. scribed S17 T29S R8W CS BT.
9" Ash S.18°E. 30.0 ft. scribed S20 CS BT.

22" fir (blank) 617.1 ft. shows old scars. 24" ash stump N.7 1/2°W, 733.9' now N.18°33'W. scribing.

105

Renew W. P. 5.6 chains West of Corner

S36	S31
R8W	R7W

T29S T29 1/2

Found - Brass Cap at Corner & Both BT's. now stumps.

New BT's: 7" Cedar bears S75 1/2°W. 37.1 ft. scribed W.P. CS S36
18" Laurel bears N. 4°W. 71.0 ft. scribed W.P. S36 CS BT.

106

East 1/4 Corner to Section 36.

Found - Brass Cap at Corner & under 3 ft. Fir Log.

N. W. BT., now low stump. S.W. BT. now down.

New BT's: 24" Laurel bears S.17°W. 18.5 ft. scribed 1/4 S36 CS BT
10" Cedar bears S.82°W. 42.0 ft. scribed E 1/4 S36 CS BT.

107

Renew A P #3 Tract 48, T29S R7W.

Found - Brass Cap at Corner & BT. as recorded, now 36" W.Oak N.79 1/2°E. 106.9 ft., center rotted. We rescribe TR. 48 A P 3 CS BT.

108

Renew Corner

Tr. 50
AP 3
AP 2 Tr. 51

T29S R8W

Found - Brass Cap at Cor. & N.E. BT., now snag, shows good scar. SE BT gone.

109

(continued over)

James W. Eyrton, Deputy County Surveyor
For Douglas County Health Dept.
Dale McFarland and John Powell
April 6 - 1962
C. S. File No. 52/114 RM 2 - 20

James W. Eyrton, Deputy
Dale McFarland & John Powell
May and June 1962
C. S. File No. 49/139

Also fd. per 52/114:
(this info added to
ren. 1/28/85):
22" fir (blank) 617.1