

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 97401

117

Sec. Cor. to Secs. 30 & 31, T29-8W. & Secs. 25 & 36, T29-9W.  
Found - Orig. 36", now 40" W.Oak S.88°W. 210.5 ft. Old face rotted.  
No scribing found. No other BT's. found. - REN. No. 9  
See Statement signed in file by John R. Standley as follows:  
I, John Standley, state that the B.T. used on this date to renew  
this section corner is the original S.W. BT. that I have seen scribing  
on this W. Oak at various times during the past 40 years.  
Set - Brass Cap at Cor. Mkd: 

S25	S30	T29S
R9W	S36	S31
	R8W	

 County Surveyor's  
Office, 1962  
New BT's: 6" Ash bears N.5½°E. 43.0 ft. scribed S30 CSBT.  
4" W.Oak bears N.21°W. 45.5 ft. scribed S25 CS BT.  
Rescribe Orig., now 40" W.Oak S.36 T29S R9W CSBT.  
50 feet North to small creek.  
Note - This corner is in old mill pond area. I.P. set at Corner not found.

B. Co. 2/24/62  
FD. 8/27/62  
OSND  
CS 43/9

118

¼ Corner to Sec. 30, T29-8W. & Sec. 25, T29-9W.  
Found Corner, Bearing Trees, gone.  
Set Witness Trees: A 26" Oak bears S.66½°E. 372.2 ft. to center of tree.  
This Oak is 7 ft. West of the Middle Fork of the Coquille River.  
7 ft. West of the Right Bank.  
A 4" Ash bears S.23¾°S. 6.3 ft.  
This corner is a 1½" Iron Pipe flush with the ground.  
Both Trees are scribed ¼ W. T.

James W. Byron, Deputy Co. Surv.  
John Powell, Chairman  
July 3, 1962  
C. S. File No. 49/139  
  
Bonneville Survey-  
Party A-53  
C.S. 41/251  
1953

119

¼ Corner to Sections 6 and 7.  
Found - 34" Cedar Stump S.20°W. 11.9 ft., shows good scar & burlwood  
about right size & shape for BT. scar & faces in right  
direction, however, center is rotted away, no scribing left.  
No trace of other Orig. Bearing Trees.  
30" Yew Tree N.3°W. 8.5 ft. with scribing "¾ S6 BT CC",  
scribing approx. 50 yrs. old, faces corner.  
Corner position also fits old tie in gov't notes to middle fork  
of Coquille River.  
Set - Brass Cap at Corner Mkd: County Surveyor's T29S R8W ¼ 

S 6
S 7

  
Office, 1963  
New BT's: 15" D.Fir S.16°W. 29.8 ft. Mkd: ¼ S7 CS BT.  
11" W.Fir N.27°W. 22.2 ft. Mkd: ¼ S6 CS BT.

Milo E. Godfrey, Deputy  
Vernon Tracy and  
Mike Stone  
Jan. 24, 1963  
C.S. File No. 49/139

120

N. E. Corner D. L. C. No. 43.  
Set - 2" I. Rod flush from which:  
A 25" D.Fir bears N.38°E. 60.2 ft. scribed NE. DLC 43 CS BT.  
A W.Oak bears N.61°W. 108.6 ft. scribed NE. DLC 43 CS BT.  
Dec. 6, 1963

RE-RENEWED. SEE CORNER NO. #204

James Byron  
& Crew  
For E.P.  
Standley  
Map M 27-13

121

¼ Corner to Sections 20 and 29.  
Found - 1" Steel Shaft & live BT. as recorded in Ren. # 3. FD. 12/21 E. Bloom 1198-14  
18", now 27" Fir S.77°20'E. 74.3 ft., open & shows partial "S".  
26", now 35" S. Pine N.62°40'E. 150.0 ft., now stump, no scribe vis.  
New BT: 6" D.Fir N.48°E. 14.3 ft. Mkd: ¼ S20 CS BT.  
Note - This corner is in E.-W Fence 22.0 ft. east of fence corner  
with fence going E - W & S.

V.R. Tracy  
T. Connell  
June 1965  
C. S. File  
No. 54/387

122

¼ Corner to Sections 12 and 13.  
Found - GLO Brass Cap, 1924, properly marked.  
Orig. 40", now 36" W.Oak, N. 30° E. 68.0 ft., shows good scar.  
Orig. 16", now 14" W.Oak, S. 64° E. 56.8 ft., opened for scribe "¾".  
15" W. Oak N. 10° E. 34.0 ft., shows "BT" scribing. (Now a stob)  
New BT: 21" W. Oak S. 83° E. 24.8 ft. scribed ¼ S13 CS BT.  
Note - This corner lies in open on top of small ridge, running N & S.  
(FD. 5/2/77 - CONDITION REPORT - C.S. 59/34 R. KIMBERLING - OFFICE) Nov. 28, 1966  
NOTE: COR. LIES AT EDGE OF CLEARING - ON TOP OF SMALL RIDGE  
RUNNING N & S, 300' WEST OF GRAVEL RD.

V. "Ray"  
John M.  
Powell  
F. Jones &  
C. Stone  
C. S.  
File  
54/38