

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

John M. Powell  
Frank Jones & Joe Brady  
April, 1967  
C. S. File No. 54/38

Section Corner to Sections 1 and 2 only, T30-8W. 141  
Found - 10", Cedar Now, 13" S. 67° W. 43.8 ft. (Record S. 59° W. 40.3')  
Opened for scribe "T".  
15", now 30" D. Fir, N. 2° E. 19.8 ft., faint bark scribe, "T R".  
24" D. Fir, now 30" Stump, N. 33° E. 49.5 ft. (Record S. 27° E.)  
Faint bark scribe "B S".  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 8 W  
Office S 35  
1967 S 2 S 1  
T 30 S R 8 W  
New BT: 30" D. Fir N. 84° E. 27.6 ft. mkd. T29S R8W S35 CS BT.  
No good trees in section 1.  
Note - This corner lies 5.0 ft. east of ravine.

South  $\frac{1}{4}$  Corner to Section 36 only, T29S-R8W. 142  
Found - 30", now 38" D. Fir, N. 19° W. 11.2 ft., bark scribed  $\frac{1}{4}$ S",  
good "BT" Scar.  
No trace of S. E. Bearing Tree.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 8 W  
Office  $\frac{1}{4}$  S 36  
1967 T30S 157  
New BT's: 6" W. Fir N. 4° E. 31.2 ft. mkd.  $\frac{1}{4}$  S36 CS BT.  
15" Cedar S. 11° E. 20.2 ft. mkd. S1 CS BT.  
No other good trees in north to scribe.

Arthur Boyer  
For F. Hurd.  
C.S. File  
No. 55/35  
May 13, 1967

$\frac{1}{4}$  Corner to Sections 3 and 10. 143  
Set  $\frac{1}{4}$  corner by prop. measurement. 157A  
Drove -  $\frac{1}{2}$ " x 18' Iron Pipe, Brass elbow. ( $\frac{1}{2}$ " pipe is inside 1" Pipe)  
Bearing Trees: 12" Fir bears S. 66° W. 2.3 ft. scribed  $\frac{1}{4}$  S10 1581 BT.  
8" Pencil Cedar bears N. 23 $\frac{1}{2}$ ° E. 45.4 ft. on +18° Slope,  
scribed  $\frac{1}{4}$  S 3, 1581 BT.

MICROFILM TO HERE 10/67

Wm. Stiles  
For Frank  
Kinnan  
8/14/68  
C.S. File 55/63

$\frac{1}{4}$  Corner to Sections 5 and 6. 144  
Set - 3" Brass Cap mkd: SEEK, INC.  
S 6 S 5  
T29 S R 8 W  
1968  
Bearing Trees: 10" Red Cedar bears N. 5° 55' W. 44.0 ft. scribed  $\frac{1}{4}$  S 6.  
12" White Fir bears S. 5° 29' E. 57.5 ft. scribed  $\frac{1}{4}$  S 5.

$\frac{1}{4}$  Corner Sec. 3, T29-8 and Sec. 34, T28-8W. 145  
Set Brass Cap for  $\frac{1}{4}$  Corner at the proportional point midway between  
Section Corners Mkd: County Surveyor's T28S R8W  $\frac{1}{4}$  S 34  
Office, 1969 T29S R8W  $\frac{1}{4}$  S 3  
New BT's: 14" D. Fir N. 72° E. 89.2 ft. mkd:  $\frac{1}{4}$  S34 CS BT".  
12" D. Fir S. 64° E. 65.1 ft. mkd:  $\frac{1}{4}$  S3 CS BT.  
No trace of Original BT's. This corner lies between old cat logging  
roads on moderate S.E. slope approx. 400 ft. west of Muns Creek.

Vernon "Ray" Tracy  
Frank Jones & V. Perron  
January, 1969  
C.S. File No. 54/80 M 37 - 25

$\frac{1}{4}$  Corner to Sec. 2, T29-8 and Sec. 35, T28-8W. 146  
Set Brass Cap for  $\frac{1}{4}$  Cor. at the proportional point midway between  
section corners mkd: County Surveyor's T28S R8W  $\frac{1}{4}$  S 35  
Office, 1969 T29S R8W  $\frac{1}{4}$  S 2  
New BT's: 12" D. Fir N. 55° W. 42.5 ft. mkd:  $\frac{1}{4}$  S35 CSBT".  
13" D. Fir S. 60° W. 47.9 ft. mkd:  $\frac{1}{4}$  S2 CS BT".  
This corner lies 10 ft. east of creek 2 ft. wide, course S.E.,  
curving to south. We find no trace of original BT's.