

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29 T. S. R 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

176

1/4 Corner for Secs. 9 and 16.  
Found - A 1" I.P. with 1958 County Brass cap set 13" above ground. Ren. #91  
A 22" now 30" D. Fir bears N.48°E., 22.7 ft. with a well healed double blaze. Ren. #35  
A 18" Fir stump bears S.76 1/4°W., 21.5 ft. with cut out section of blaze on top of stump showing reverse scribing "BT".  
A 28" now 32" D. Fir bears S.34 1/2°E., 21.6 ft. with a well healed double blaze.  
No new monument set.  
New BT- A 10" D. Fir bears N.31°W., 77.4 ft. double blazed and marked "1/4 S9 CS BT".  
Note: Corner is approx. 300 ft. east of Hwy #42.

FD - 7/1/80  
O.S.M.S.  
C.S. 63/19

3/1/78 177

R. B. Kimberling  
P. L. Earle  
Doug. Co. Surveyors Office  
March 1, 1978  
C.S. 59/46

Section corner for Secs. 9, 10, 15 and 16.  
Found - A 1" I.P. with 1958 County brass cap set 4" above ground. Ren. #72  
A 40" now 50" Fir (OBT) bears N.10°E., 24.4 ft. (Rec. 22.4 ft. Good to orig. face) with visible bark scribing "S T29S R8W S"  
A 40" now 60" Fir, uprooted with center of root hole bearing approx S.55°E., 5.0 ft. (Rec. 3.3 ft. good to orig. face) with visible bark scribing "T2 T29S R8W S15".  
A 12" now 17" D. Fir bears N.41°W., 141.6 ft. with a well healed double blaze.  
A 5" now 12" Cedar bears N.46°E., 8.0 ft. with a well healed blaze. 5 ft. above ground.  
A 3" now 10" D. Fir bears S.59°W., 41.0 ft. (Rec. S.58°W.) with a well healed double blaze.  
No new monument set.  
New BT's-A 6" D. Fir bears N.82°E., 118.5 ft. double blazed and marked "T29S R8W S10 CS BT".  
A 7" D. Fir bears S.13°E., 34.0 ft. double blazed and marked "T29S R8W S15 CS BT".  
Note: Corner is in root hole of 60" dia. O.B.T.

3/1/78 178

R. B. Kimberling  
P.L. Earle  
Doug. Co. Surveyors  
Office  
May 31, 1978  
C.S. 60/11

Witness Corner for the East 1/4 corner of Sec. 13.  
(1/4 corner to be lost) See Ren. #166  
Set - A 1" x 36" I.P. with brass cap set 4" above ground marked:  
"Douglas County Surveyor"  
T 29 S  
W.C. 120 ft.  
S 0° 03' 30" E  
R 1/4 to R  
8 ↓ 7  
W S13 W  
1976

New Accessories:

A 7" White Fir bears S.62 1/2°W., 6.5 ft.  
A 8" White Fir bears N.36°W., 2.7 ft.  
I double blaze and scribe both trees "WC 1/4 S13 CS BT".

5/31/78 179

Gary L. Langlitz  
Frank C. Silagy  
Terrie Plouff  
Doug. Co. Surveyors  
Office  
Oct. 2, 1978  
C.S. 60/17

1/4 Corner for Sec. 12 only. (east)  
Found - A 1" I.P. firmly set extending 10" above ground on a steep westerly slope, with a properly marked 1924 GLO brass cap. An orig. 10" Laurel (madrone), now an 18" snag, no markings visible on a previously opened blaze, bears S.60°E., 18.5 ft. An orig. 36" Fir, now a 70" D. Fir snag with faint scribing "1/4" visible on deteriorating bark blaze, bears N.3°W., 73.9 ft. (Rec. N.7°W., 73.9 ft.)  
A 1924 BT, a 24" now 36" D. Fir alive with well healed single blaze, bears S.19 1/2°W., 37.0 ft.  
No trace or original corner post.  
No new monument set.  
New BT - A 13" D. Fir, scribed "1/4 S12 CS BT" on a double blaze, bears N.5°W., 48.6 ft.

10/2/78