

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 T. S. R 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

183

C O N T. -----

Gary L. Langlitz
Karen Reed
Virginia Laugen
Deloris Keady
Doug. Co. Surveyors
Office
Dec. 18, 1978
C.S. 60/24

A 14" D. Fir, bears S.53°W., 29.2 ft. dist. marked "C 1/4 S12 CS BT" in a double blaze.
A 22" Incense cedar bears N.77°W., 43.8 ft. dist. marked "C 1/4 S12 CS BT" in a double blaze.
A 4 x 7 ft. Conglomerate Rock outcropping with 2 ft. vertical face bears N.15°E., 10.6 ft. marked "B0 +". "+" is 4 ins. high.
A steel fence post bears North, 1 ft. with Surveyor marker sign attached.
Note: Located on fairly steep hill side.

12/18/78

184

Howard Johnstone
For: Roseburg Lumber
Company Jan. 1980
M 81 - 75

Center 1/4 Corner for Section 24
Set - 5/8" Iron rod and alum. cap.
BT's - 20" Cedar bears S.56°W., 26.5 ft.
20" Fir, bears N.37°W., 38.5 ft.

RENEWED, SEE CORNER NO. 222

1/10/80

185

Center 1/4 Corner for Section 34
Set - 5/8" x 48" Iron rod and alum. cap.
BT's - 17" Hemlock bears N.48°E., 34.5 ft.
13" Cedar bears N.35°W., 39.0 ft.

1/9/80

186

Section corner for Secs. 32 and 33; and 5 & 4 of T30-8
Found - 1958 County surveyor BCIP. Ren. #93
36" Cedar bears S.23°W., 25.0 ft. 1882 survey.
36" Fir bears N.3°E., 25.0 ft.
56" Fir snag bears S.13°E., 50.0 ft. (Boyer ?)

1/9/80

187

Closing Corner for Secs. 3 and 4 of T.30-8 only.
Found - 1967 County Surveyor brass cap and iron pipe. Ren. #140
Set - 5/8" x 36" IR and Alum. cap. South 5.30 ft. on true Tp. line.
BT's - 16" Fir, S.79°E., 8.6 ft.
14" Fir, S.18°W., 18.5 ft.
12" Fir N.7°E., 19.1 ft.

Howard Johnstone For:
Roseburg Lumber Company
January 9, 1980
M 79 - 15

188

Section corner for Secs. 33 and 34 only.
Set - 5/8" x 48" IR and Alum. cap.
BT's - 22" Fir bears N.60 1/2°W., 16.7 ft.
14" Fir, N.28°E., 46.6 ft.
26" Fir S.20°E., 44.9 ft.

189

South 1/4 Corner for Sec. 34 only.
Set - 5/8" x 48" I.R. and Alum. cap.
BT's - 22" Fir N.77°E., 41.6 ft.
15" Fir, S.42°E., 19.5 ft.
Found 1" I.P. N.12°02'22"E., 17.14 ft. not of record.

190

Section corner for Secs. 1 and 2 only - T.30-8.
Found - 1970 County Surveyor BCIP (Rec. 1967, Ren. #141)
30" Cedar, S.59°W., 40.3 ft. Orig. Rec. (Ren. #141, S.67°W, 43.8 ft.)
New BT -12" Maple bears S.50°E., 57.4 ft. 5.81 ft. North of Tp. line.

1/9/1980

191

1/4 Corner for Sections 5 and 8
Set - 1/4 corner by proportion with a 5/8" iron rod.
New BT's - 5" W. Fir, N.46°37'W., 20.1 ft. scribed "1/4" S5 BT.
9" W. Fir, S.19°25'E., 21.1 ft. scribed "1/4" S8 BT.

Russell D. Hendrick For:
Marion Mooney
June 27, 1980
M 84 - 19

192

Center 1/4 corner for Section 8.
Set - by proportion with 5/8" iron rod.
New BTs - 8" W. Fir, N.16°12'W., 21.3 ft. scribed "C 1/4 S8 BT.
11" D. Fir, N.61°10'E., 22.5 ft. scribed C 1/4 S8 BT.