

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 T. S. R 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

James Byron, Deputy
For: Doug. Co.
Health Dept.
April 1962
C.S. 52/114
R.M. 2-20

FD. OK 12/84
E. Bloom
M 98-13

1/4 Corner for Sections 20 and 21 197
Found - Now 34" fir stump, S. 20° E., 10.6 ft. No scribing found, bark gone, may have been bark scribed.
Now 12" fir, N. 79° E., 219.9 ft. Shows good scars, NW BT, 1954 renewal, not found. Ren. #42
We do not find geared axle set for corner. BLM men state geared axle was in place and at fence corner in Sept. 1961.
Set Brass cap at corner marked: County Surveyors Office 1962 1/4 S 20/ S21 T29S R8W.
New BT - 17" Cedar bears N. 18° W., 207.2 ft. scribed 1/4 S20 CS BT.

1/4 Corner for Sections 20 and 21. 198
Found - 1962 1" iron pipe with brass cap set firmly 10" high. Is along top of 3 1/3 ft. high cut bank.
(Distances to found trees are record per Ren. #197. Residentail area - considerable brushing necessary.)
Orig. 15" fir now a 34" stump bears S. 20° E., 10.6 ft. No scribing.
From Ren. #42, an 8" now 25" fir with well healed single blaze bears N. 79° E., 219.9 ft.
From Ren. #197, a 17" now 30" cedar with well healed blaze bears N. 18° W., 207.2 ft.
Note: Surveys Numbers M 98 - 13 and M 98 - 14, report no bearing trees.
New Accessories:
Chisled X in top and at east end of 12" diam., concrete culvert running easterly-westerly on S. side of road "Our Lane" bears S. 88 1/2° E., 27.0 ft.
A utility pole 9" diam. and marked "1 248 10" bears N. 31 1/2° E., 37.9 ft.

Larry E. Monrean,
Deputy, Doug. Co.
Surveyors Office
R. W. Smith and
S. J. Flause
April 2, 1985
C. S. 62/28

FD OK
BY K. DeGroot
1/95 M 121-33
C.S. 63/52

1/4 Corner for Sections 21 and 22 199
Found - A 1" x 36" galv. I.P. with attached County Surveyors brass cap, properly marked. Ren. #85. Cap has been pushed over apparently during fire trail construction. This monument is still in good condition. We use the position of the base of the monument as the corner location perpetuated by Ren. #85.
From this position, a wooden hub and tack bears N. 60° W., 1.0 ft.
Original monument not found. From the point used as 1958 perpetuation, references are tied as follows:
Found - Orig. BT, an 18" fir now a 30" DBH stump 5 ft. tall with scribing "1/4S" visible on previously opened blaze bears N. 25° E., 12.7 ft to center, 11.6 ft. to face. (Rec. N. 25° E., 11.2 ft.) Blaze on S. 54° W. side of stump.
A 40" fir now a stump 36" dia. 2 1/2 ft. tall bark scribed "S BT" bears N. 40° W., 38.4 ft., 36.9 ft. to face.
(Rec. 36.5 ft.) Blaze on S. 5° E., side of stump. Ren. No. 26
A 10" now 20" fir with well healed double blaze bears S. 58° W., 33.8 ft. (Rec. S. 57° W.) Blaze on N. 26° E. side of tree.
A 12" now 19" cedar with well healed double blaze bears N. 57 1/2° E., 20.8 ft. (Rec. N. 58° E., 21.0 ft.) Ren. No. 85
Set - At position as previously described, we reset the found monument in an upright position. We add the marks "Reset 1986" to cap.
New BT - A 6" dia. pine double blazed and scribed "X BT" bears N. 39° W., 28.9 ft.
Located in E-W cutting line. Area to south harvested.

Douglas County
Surveyors Office
Larry E. Monrean
Deputy
R. W. Smith
S. J. Flause
March 6, 1986
C.S. 62/34

FD OK
BY K. DeGroot
1/95 M 121-33
C.S. 63/52

Section corner for Secs. 6 and 7 only of T 29-7 200
Found - 17" D. fir with healed scar bears S. 20° E., 50.8 ft. Ren. #110
5 1/8" Iron Rod bears N. 40° W., 38.51 ft. See Ren. No. 270 in T. 29-7
5 1/8" Iron Rod bears N. 18 1/2° E., 39.88 ft. See Ren. No. 270 in T. 29-7
Set - Hub and Tack for Section corner Secs. 6 and 7 only.
Note: Witness Point for Secs. 6 and 7 bears N. 89° 16' 26" W., 119.40 ft. Found DCSO brass cap mkd. "WP".

Eugene A. Bloom
L.S. No. 492
For: Lucille Okeeffe
March 1986
M 100 - 50

RE-REVIEWED, SEE CORNER NO. # 206