

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S T. S. R. 8 W R. W. W. M.

FOXE-CHAPMAN CO., EUGENE, ORE. 97331

Douglas County Surveyors Office
August 23, 1993
C.S. File 64/46

217

1/4 Corner to Sections 16 & 17.
Found - 2 1/2" dia. DCSO Brass Cap on a 1 1/2" dia. iron pipe set flush with ground. See ren. # 90.
Large stone is found along east edge of BC/IP exposed top measures 12" x 8" set flush with ground, no marks visible. (orig. stone)
30" now 38" dia. 15 ft. tall dead and rotting Oak snag. Axe marks visible, no scribing or blazes found. Bears N.85°E., 79.9 ft. (orig. BT)
14" now 30" dia. double trunked dead Cedar with a fully healed double blaze on southerly trunk, bears N.14 1/2°E., 30.6 ft. (rec. N.18°E., 30.6 ft.)
8" now 22" dia. Cedar with a fully healed double blaze, bears S.72°W., 70.0 ft.
New Accessories -
A 3 5/8" dia. N.G.S. disk stamped "N741x 1987" set in exposed rock, bears S.73 1/2°E., 69.7 ft.
11" dia. W.Oak double blazed and scribed "1/4 S17 CS BT" bears S.8 1/2°W., 54.9 ft.
8" dia. double trunked W.Oak double blazed and scribed "1/4 S16 CS BT" on westerly trunk bears N.28°E., 61.0 ft.
Note - Corner is approx. 190 ft. north of the centerline of Hwy. 42.

Kristian DeGroot, L.S. # 1941
For: Joel & Ora Kuhse, Lone Rock Timber, &
Silver Butte Timber Co.
January 1995
M 121-33 C.S. File 63/52

218

1/4 Cor. Secs. 16 & 21
No orig. corner evidence remains. Corner position restored by single proportionate measurement.
Set - 1"x30" galv. I.P. 28" in the ground w/2 1/2" brass cap stamped:
T29S R8W
1/4 S 16
S-21
1994
PLS 1941 from which,
7" D.Fir, bears N.26°W., 30.9', scribed "1/4 S16 BT"
13" D.Fir, bears S.71°W., 20.1', scribed "1/4 S21 BT"
5/8"x30" iron rod w/plastic cap "BTS ENG-SURV" bears, S.26°E. 19.6'
5/8"x30" iron rod w/plastic cap "BTS ENG-SURV" bears, N.71°E. 25.1'
and a monument not of record:
1" iron pipe bears, S.10°50'52"E., 1.51'.

219

C 1/4 sec. 21
Set - 5/8"x30" iron rod 34" in the ground w/2 1/2" alum. cap stamped:
T29S R8W
C 1/4 - S21
1994
PLS 1941 from which
8" D.Fir, bears N.6°30'W., 16.1', scribed "C 1/4 S21 BT"
16" D.Fir, bears N.85°W., 36.9', scribed "C 1/4 S21 BT"
5/8"x30" iron rod w/plastic cap "BTS ENG-SURV", bears N.39°E. 34.4'
5/8"x30" iron rod w/plastic cap "BTS ENG-SURV", bears S.6 1/2°E. 21.8'

Mark Smalley
For: Kenneth Ford
Dec. 1994
M 121-51

1/4 Corner Secs. 13 & 24 (Ren # 148)
Found - GLO brass cap & iron pipe
36" Fir, N.73°W., 37.3'. Stump.
28" Fir, N.28°W. 11.2'. Rotten snag, Original.
7" Fir, S.88°E 12.6'. Healed.
24" Fir, S.29°E., 8.4'. Snag, scribe visible, Original.
9" Fir, S.60°W., 17.6'. Down.
Scribed -
10" Fir, N.5°W., 25.8', "1/4 S BT"
10" Fir, N.22°E., 22.7' "1/4 S BT"
5" Fir, S.8°E., 28.2' "1/4 S BT"

220