

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 S T. S. R 8 W R.W.W.M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97401

1/4 Corner Secs. 23 & 24 221
 Found - 1958 County brass cap & iron pipe. (Ren. # 89)
 34" Cedar, S.10°E., 11.9', snag, scribe visible, Original.
 32" Fir, S.55°W., 30.2', rotten snag.
 New BTs-16" Cedar, N.85°E., 63.5', scribed "1/4 S BT"
 12" Fir, N.24°E., 40.2', scribed "1/4 S BT"
 14" Maple S.43°E., 33.0', scribed "1/4 S BT"
 10" Cedar, S.28°W., 51.3', scribed "1/4 S BT"

C 1/4 Corner Sec. 24 222
 Set - 5/8"x48" iron rod & aluminum cap mkd: LS 2354
 NO TREES LARGE ENOUGH TO SCRIBE WITHIN REASONABLE AREA
 Tagged- 2" Fir, N.74°E., 16.0'.
 2" Fir, N.76°W., 16.5'
 Set - 5/8"x48" iron rod bears S.45°E., 10.0'
 5/8"x48" iron rod bears S.45°W., 10.0'
 NOTE - This monument bears N.86°37'14"E. 169.9; form the monument
 set for the center 1/4 by Howard Johnstone, M81-75, (Ren.
 #184). I pulled Johnstone's monument, his SW BT is down and
 the NW BT is a 20' snag.

E 1/4 Corner Sec. 24 only 223
 Found - 1924 GLO brass cap & iron rod.
 24" Madrone, N.12°W., 19.8', snag.
 19" Fir, N.69°W., 21.1', healed.
 24" Madrone, S.81°E., 13.2', stump.
 34" Fir, S.5°W., 24.4', healed.
 New BTs-14" Fir, North 13.6', "1/4 S BT"
 10" Cedar, N.84°E., 21.3', "1/4 S BT"

1/4 Corner Secs. 24 & 25 224
 Found - 1924 GLO brass cap & iron pipe.
 14" Cedar, S.8°W., 17.3', healed.
 New BTs-11" Fir, N.17°E., 21.9', scribed "1/4 S BT"
 11" Cedar, S.1°E., 28.7', scribed "1/4 S BT"

C 1/4 corner of sec. 8 225
 Mon. Fd. - 5/8" I.R. 2/21/95
 New Accessories - (Ren # 192)
 13" Fir, North 50.7', "C 1/4 BT"
 12" Fir, S.80°E. 20', "C 1/4 BT"
 6" Fir, S.51°E 1.8', "C 1/4 BT"
 7" Fir, S.56°W., 5.1' "C 1/4 BT"

Sec. cor. 7,8,17 & 18 226
 Mon. Fd. - 1973 Cadastral BCIP (Ren # 101)
 BT's Fd. - 40" Maple, N.72°W. 22.8', healed
 14" Myrtle, S.83°E. 30.4', scribe visible
 8" Myrtle, S.28°W. 33.7', scribe visible
 18" Fir, S.50°W. 19.8', healed
 1962 County BCIP, bears S.73°29'E. 18.5'
 New BT - 9" Cedar, N.61°E. 11.8' "S 8 BT"

1/4 Cor of sec. 5 & 8 227
 Mon. Fd. - 1980 Cadastral BCIP (Ren # 2191)
 BT's Fd. - 10" Hemlock, S.17 1/2°E., 21.8', snag scribe visible
 New BT's - 8" Chinguapin, S.2°E., 36.8', "1/4 S BT"
 6" Fir, S.22°W. 32.9', "1/4 S BT"
 6" Fir, S.60°W. 32.3', "1/4 S BT"

Mark Smalley, L.S. 2354
 For: Kenneth & Hallie Ford
 Dec. 1994
 M 121-51

Mark Smalley
 for: Roseburg Resource & Ninette West
 M 119-69
 Aug. 1995