

Douglas County Surveyor's Record of
Government Corners Renewed

T 29. T. S. R 9 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

James W. Byron, Deputy
Milo Godfrey
Clete E. Putnam
Oct. 20, 1959
C. S. File No. 49/100

Section Corner to Secs. 34 & 35, T29S R9W, & Secs. 2 & 3, T30S R9W.
Found - Orig. 6", now 12" Cedar, record S.54°E. 33.7 ft. I find
should be S.48°E. 22.7 ft., shows good scribing "39W S2".
Orig. 15", now 34" W. Fir S.51°W. 4.6 ft. I open & find
good scribing "BT". No trace of other BT's found.
Find scribed Stake at Corner.

Set Brass Cap alongside scribed stake Mkd:

S34	S35
S 3	S 2

 T29S R9W
County Surveyor's Office, 1959

New BT's: 16" W. Fir bears N.11°E. 24.3 ft. scribed S35 T29S R9W CS BT.
11" Cedar bears N.40°W. 29.3 ft. scribed S34 T29S R9W CS BT.

ADD BLM 1966 TO BRASS CAP
Vol. 34 P. 14027

Section Corner to Sec. 34, T29S R9W, & Sec. 3, T30S R9W.
Found - Orig. 24", now 30" Fir Snag S.25°W. 26.4 ft. I open & find
good scribing "BT".
No trace of Orig. N. E. BT. found.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1959
New BT's: 6" R. Fir bears N.28°E. 18.0 ft. scribed $\frac{1}{4}$ S34 CS BT.
8" R. Fir bears S.10°W. 14.0 ft. scribed $\frac{1}{4}$ S 3 CS BT.

RE-RENEWED SEE CORNER NO. # 102

Claude Kerr
March 10, 1960
C.S. File No. 51/76

Section Corner between Sections 3 and 4.
Found one of the original B.T.'s, a Cedar, bearing North 41°E. 29 lks.
I chopped in and found the scribe markings. I rescribed
this tree on a new face with $\frac{1}{4}$ S 3 BT.
I set a 3" x 4" Cedar Limb as the $\frac{1}{4}$ Corner Stake.
A new B.T., a 28" Hemlock was faced and marked $\frac{1}{4}$ S 4 BT,
bearing S 58° West for 35.7 feet from the $\frac{1}{4}$ corner stake.

Section Corner to Secs. 3 & 4, T29-9W. & Secs. 33 & 34, T28-9W.
Found - Orig. 18", now 20" Hemlock S.59°W. 21.8 ft., previously
opened, shows good scribing "1/2 S".
Orig. 24", now 30" Hemlock S.49°E. 17.2 ft., shows scar.
N. E. & N. W. Bearing Trees not found.

Set - Brass Cap at Cor. Mkd: Coos Co.

S33	S34
S 4	S 3

 T28S R9W
Douglas Co. 1962

New BT's:
46" Fir bears N.76°W. 20.0 ft. bark scribed S33 T28S R9W CS BT.
7" Yewood bears N.69°E. 33.6 ft. scribed S34 CS BT.

FD. 1976 BLM
SEE GIS FILE

James W. Byron
D. McFarland &
J. Powell
April 18, 1962
C. S. File
No. 49/100

Sec. Corner to Secs. 25 & 36, T29-9W. & Secs 30 & 31, T29-8W.
Found - Orig. 36", now 40" W.Oak S.88°W. 210.5 ft. Old face rotted,
no scribing found. No other BT's. found. (REN. NO. 2)
I, John Standley, state that the BT. used on this date to renew this
this section corner is the original S.W. BT. That I have seen scribing
on this W.Oak at various times during the past 40 years.

See signed statement in file.
Set - Brass Cap at Corner & Mkd:

S25	S30
S36	S31

 T29S R9W County Surveyor's
R9W Office, 1962

New BT's: 6" Ash bears N.5 $\frac{1}{2}$ °E. 43.0 ft. scribed S30 CS BT.
4" W.Oak bears N.21°W. 45.5 ft. scribed S25 CS BT.
Rescribe Orig., now 40" W.Oak S36 T29S R9W CS BT.
50 feet North to Small Creek.

FD. 1975
ORE. ST. DEPT.
HWJ. N. B.
SEC

James W. Byron, Deputy Co. Surveyor
John Powell, Chairman
July 3, 1962
C. S. File No. 49/139

Note - This corner is in old mill Pond Area. I. P. set at corner not found.

S. W. Corner D. L. C. No. 37.
Found - Orig. 20" R. Fir N.45°E. 20.5 ft., shows good scribing "BT" on old
face, now stump.
Set - Brass Cap at Cor. & Mkd: County Surveyor's Office, 1962
S.W. D.L.C. 37, T29S R9W

New BTF 10" W. Fir bears N.22°W. 11.7 ft. scribed CL 37 CS BT.

FD. 1975
ORE. ST. DEPT.
HWJ. N. B.
DEPT.

66

67

68

69

70

71