

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S.T.S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

Corner to Sec. 31, T29-9W. & Sec. 36, T29-10W.

Wright's Corner.

Found - 2' x 1 1/2" x 6" Rock with "29 CO", six notches & an "X" from which:
60" D.Fir Snag, with scribes "36 BT" visible, bears N.55°W. 92.4 ft.
Old Cedar Snag, with scribe "BT 3-T29-R9" visible, bears
N.21°E. 14.5 ft. (record - 66.0 ft.)
D.Fir Stump bears S.22°E. 4.6 ft.

Scribed - 16" D.Fir, I scribed "S36 BT", bears N.24°W. 19.5 feet.
12" D.Fir, I scribed "S31 BT", bears N.29°E. 8.3 feet.

RE-RENEWED SEE CORNER NO. #94

Bruce A. Shaner
For Evans Products Co.
Jan. - April 1963 Map File R.M. 1 - 36

Northeast Corner Section 1, T30S R10W.

Porter's Corner - Found a Rock with 6 notches on S. side & 7 notches
on W. side. I set a Nail from which a
6" Ching. BT (record, Myrtle) bears S.64°W. 9.9 feet.
(old face is all rotted out)
18" D.Fir, I scribed "S1 T30S R10W BT" bears S.38°W. 34.0 ft.

RE-RENEWED SEE CORNER NO. #96

Northwest Corner Section 6, T30-9W.

Hathorn's Corner - Found: 32" x 32" x 18" Stone mka. "BO" with
6 notches on both S. & E. sides.
I set a nail from which an:
"X" on 2' x 1' x 1' Rock bears S.70°E. 14.7 ft. (record 13.2')
"X" on 4' x 5' Rock, (also scribed "BO") bears N.68°E. 18.5 ft.

RE-RENEWED SEE CORNER NO. #95

1/4 Section Corner to Sec. 3, T29-9W. & Sec. 34, T28-9W.

Found - Stump of Orig, now 30" Fir Stump, N.10°W. 19.1 ft., shows
good bark scribing "1/4". We nail yellow tag near base.
Note - Water falls bears N.55°E. 1200. Corner is on top of spur.
Set - Brass Cap at Cor. Mkd: County Surveyor's 1/4 S34 T28S R9W
Office, 1963 S 3 T29S
New BT: 62" Cedar bears S.54°W. 169.6 ft. scribed 1/4 S3 CS BT.
No trees near to North.

RE-RENEWED SEE CORNER NO. #93

James W. Byron, Deputy
Mike Darby & Em. Stoffel
June 20, 1963
C.S. File No. 49/100

1/4 Section Corner to Sections 27 and 28.

Found - 1" I.P. at Corner & 8", now 9" W.Fir S.5°E. 48.3 ft.,
shows scribing. Ren. #11 & 63
S.W. Bearing Tree, now down.
New BT: 9" W.Fir bears S.6 1/2°W. 68.0 ft. scribed 1/4 S27 CS BT.
Note - Corner is 25 ft. East of small stream.

RE-RENEWED SEE CORNER NO. #93

Section Corner to Secs. 32 & 33, T29-9W. and

Secs. 5 and 4, T30-9W.

Found - Orig. 12", now 20" Hemlock S.74°E. 22.4 ft. shows "9S"
scribe in opened scar.
Orig. 15", now 24" Hemlock N.74°W. 25.7 ft., shows good scar.
Orig. 36", now 54" Fir Stump S.38°W. 7.9 ft., shows face
on top of stump.
No trace of N. E. Bearing Tree.

Set - Brass Cap set for Cor. & Mkd: Doug.Co.Surv. T29S R9W S 32 | S 33
Off. 1964 T30S S 5 | S 4

New BT's: 17" Hemlock N.12°E. 28.8 ft. Mkd: T29S R9W S33 CS BT.
9" Hemlock S.22°W. 26.9 ft. Mkd: T30S R9W S5 CS BT.

Note - This corner is on that portion of the county line between
Coos and Douglas County that runs E. & W. on the north line
of T.30S. R.9W.

FWD OK
4/9/11/3-20

Vernon R. Tracy
& Crew
Sept. 22, 1964
C.S. File No. 53/53