

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

John M.
Powell &
Crew
Dec. 7,
1965
C. S. File
No. 53/53

1/4 Corner to Sections 22 and 27.

Found - Brass Cap at Cor. Mkd. County Surveyor's Office, 1959
See Ren. #54.

Orig. 26" Fir Stump S. 44° E. 8.6 ft.
20" Fir Stump N. 22° W. 9.0 ft.
16" R. Fir, now 17", N. 22° W. 41.4 ft., shows 2 good faces.

New BT's: 17" Fir S. 10° W. 33.5 ft. scribed 1/4 S27 CS BT.

Note - This corner is on top of ridge just before descending, going west. Possible to walk to corner on old road from N. W. Section Corner of Section 27. # 105

MICROFILM TO HERE - 10/67

1/4 Corner for Secs. 14 and 15.

Found - 3/4" I.R. buried & bent in center of abandoned skid trail on top of spur ridge. Ren. No. 48

Record 22" D. Fir, now 26", bears S. 3 1/2° E., 30.6 ft. blazes plainly visible and partly grown over. (Rec. S. 3 1/2° E., 30.6 ft.)
Orig. 12", now 21" D. Fir, bears N. 62° W., 44.9 ft. was opened previously & now healing over. (rec. N. 62° W., 44.9 ft.)
No trace of Orig. SE tree.

Set - Removed I. R. and set brass cap, buried 4" below surface of ground, mkd. COUNTY SURVEYORS T 29 S
OFFICE 1/4 S 15 S 14
1974 R 9 W

New BT - 14" D. Fir, bears S. 19° W., 46.4 ft. scribed 1/4 S15 CS BT.

1/4 Corner for Sec. 33; and Sec. 4 of T30-9.

Found - An orig. 18" D. Fir now a 30" stump, bears N. 23° E., 20.5 ft. We open and find good scribing "T".

An orig. 15" D. Fir, now a 36" stump bears S. 32° W 27.8 ft. (rec. S. 32° W., 26.4 ft.) showing a good scar and faint scribe marks on the bark above the scar.

Set - At the corner point we set a 1" x 30" I.P. with brass cap: COUNTY SURVEYORS T 29 S
OFFICE 1/4 S 33 R
1974 S 4 9
T 30 S W

New BT's: a 12" Hemlock bears N. 77 1/2° E., 16.3 ft. scribed "1/4 S33 CS BT".

An 11" Port Orford cedar bears N. 12° E., 14.2 ft. scribed "1/4 S33 CS BT".

Compass declination setting: 20° East.

1/4 Corner for Secs. 3 and 4.

See Ren. #68.

Found: 15" now 24" Cedar (orig. NE BT) already opened. Scribe marks from orig. survey and renewal done by Claude Kerr. Both visible and in different depths in tree. Tree is alive and in fair condition bearing N. 41° E., 19.1' dist.

22" Hemlock recorded in 1960 to be 28". I find the recorded bearing and dist. to be in error and change it from S. 58° W. 35.7' to S. 56° W. 43.2'. Tree alive and well, scribing visible.

I found no trace of other BT's or monument.

Set: At corner point established from orig. 15" Cedar a 1" X 30" I.P. with brass cap stamped: Douglas County Surveyor 1976

T 29 S R 9 W
1/4 Corner
S4 S3

New BT: 19" Hemlock bears S. 4° W. 17.8' dist. and mkd. "1/4 S4 CS BT" in a double blaze.

Compass dec. 20° S.

3/23/76

Gary Lenglitz, Surveyors office
P. Earle
Jan. 17, 1974
C.S. 56/43

Gary Langlitz
P. Earle
Office
11/6/74
C.S. 57/12

A Victor Cangie
James H. Cook
County Surveyors
March 23, 1976
C.S. 59/8

78

FD. 1980
BLM ADMIN
SURVEY
SEE GIS FILE

79

80

81