

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 29 T. S. R. 9 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORG. 91881

Continued - - - -

New Accessories:

101

An 18" dia. breast high Maple scribed "X BT" on a
dbl. blaze bears N.05°E., 407.6 ft.

A 32" dia. breast high White Oak scribed "T29 R8W S19 CS BT"
on a dbl. blaze bears S.34½°E., 709.8 ft.

Monument is near center of northbound lane of Westside Rd. (Co. Rd.
129) in Camas Valley just South from curve in road where direction
changes from east-west to north-south direction.

see prev. renewal # ~~67~~ 61

102

SOUTH ¼ COR. OF SEC. 34

MON. FD.- 1959 DO. CO. BRASS CAP IN GOOD CONDITION

BT'S FD.- 6½" D.Fir, bears S.67°W., 10.8' (rec. unknown) well healed
face and BLM tag.

14" D.Fir, bears N.26½°E., 18.8' (rec. N.28°E., 18') well
healed face and BLM tag.

26" OR. BT., very rotten stump, bears S.24°W., 27.5' (rec.
S.25°W., 26.4').

corner is 1.5' above ground on steep east facing slope. 190' south of
ridge with old skid road and location tag.

CENTER ¼ CORNER OF SEC. 34

103

MON. SET- 5/8" X 40" Iron rod with 2½" aluminum cap marked Lone Rock
Timber T29S R9W C¼ S34 1996 PLS 2291.

BT's Fd.- 15" D.Fir, bears N.29°W., 37.7', we scribed C¼ S34 B.T.
and tag tree.

10½" D.Fir, bears N.59½°E., 35.55', we scribed C¼ S34 B.T.
and tag tree.

12" D.Fir, bears S.28°E., 27.1', we scribed C¼ S34 B.T.
and tag tree.

15" D.Fir, bears S.34°W., 39.2', we scribed C¼ S34 B.T.
and tag tree.

12" W.Fir snag, with location tag or approximate C¼, bears
S.72½°W., 37.8'.

corner sits on flat bench approximately 250' west of creek.

KEN HOFFINE - Lone Rock Timber
Mar. 1996 - M 123 - 59

Center 1/4 Corner Sec. 22

104

Set - 2" iron pipe with 2" brass cap, mkd: T29S R9W C¼ S22 LS 2052
1996"

5" Chinguapin, S.12°E., 25.5', barked scribed "C ¼ S22 BT"

10" D.Fir, S.62°W., 52.6', blazed & scribed "C ¼ S22 BT"

11" D.Fir, N.82°W., 49.9', blazed & scribed "C ¼ S22 BT"

8" Chinguapin, N.32°E., 15.7', blazed & scribed "C ¼ S22 BT"

**Note - All measurements to BTs established this survey are to a
spike set in the side center of the tree, & angles were
measured to the center of the tree. A tag was attached to
the tree facing the corner.**

John Minor
For: Menasha Corp.
9/96
M 125-76

105

1/4 Corner for Sections 22 and 27

Found - From renewal #54 the following monument: A 2½" dia. D.C.S.O.
brass cap on a 1½" O.D. galv. iron pipe, firmly set and
protruding approx 18" out of the ground. See renewal # 78

A buried stone on the north edge of the brass cap monument
with the marks "1/" visible, protrudes approx. 4" above
ground. Record from 1882 retracement survey calls for a
12" x 10" x 6" basalt stone; The found stone is sandstone
but the size is reasonable and the markings appear to be
time worn.

Accessories Found -

Remains of two original BT's:

A Fir, 12" dia. now a 28" dia. 3 ft. tall rotted Fir stump
with no original markings found, bears S.44°E., 9.3 ft.
(rec. S.44°E., 8.6 ft. a face measurement).

Douglas County
Surveyor's Office
Stephen Flause
John Pike
Oct. 15, 1996
C.S. File 65/9-28

(Cont. Next Page)