

Douglas County Surveyor's Record of
Government Corners Renewed

29 1/2 T. S. 7 R. W. W. M.

Ben B. Irving
James Byron
Ray Irving
Work done on
order from County
Court in connection
with Co. road
No. 38.
February, 1954
See File 46/36

COPE-CHAPMAN CO. EUGENE, ORE. 97196

North 1/4 corner Section 32.
Corner positively identified, brass cap at corner. 18 inch R. Fir, S.41°E.,
22 lks. Stump only left.
Blazed and scribed two trees:
10 inch W. Fir, S.0°30'E., 90.0 ft. dist., marked T29 1/2 S R7W 1/4 S 32 CS BT.
10 inch R. Fir, N.83°E., 93.4 feet dist., marked T29 1/2 S R7W 1/4 S 32 CS BT.

Section Corner to S31/S32 T29S R7W. 2
Found - Brass Cap at Corner. 12", now 20" Fir N.70°E. 54.1 ft., alive
and in good condition.
12", now 18" Maple N.4 1/2°W. 28.4 ft., center rotted. I rescribe
this BT. S31 CS BT.

Renew S31/S32 T29 1/2 S R7W. 3
Found - 10", now down 14" Fir S.53°W. 27.1 ft., shows good scribing "S".
Dogwood to S. E. not found but we do find 12" Yewwood, checks
bearing and distance to SE. BT.

Note - Brass Cap set for corner not found. Falls in old Cat Road &
about 10 feet south of Creek Channel.
New BT's: 12" Yewwood bears S.66°E. 23.2 ft. scribed S32 T29 1/2 S R7W CS BT.
18" W. Fir bears S.81 1/2°W. 79.7 ft. scribed S31 T29 1/2 S R7W CS BT.

Renew S31 T29S R7W
S31 T29 1/2 S
Found - Brass Cap at Corner. Both BT's. now down.
N.E. BT. shows scribing.
New BT's: 22" R. Fir bears N.69°E. 18.0 ft. scribed S31 T29S R7W CS BT.
6" Chinquipin bears S.15°E. 30.4 ft. scribed S31 T29 1/2 S R7W CS BT.

Renew W. P. 5.6 ft. chains West of S36/S31 T29S
R7W S31 R7W T29 1/2 S
Found - Brass Cap at Corner - Both BT's now stumps.
New BT's: 7" Cedar bears S.75 1/2°W. 37.1 ft. scribed W.P. CS S36 CS BT.
18" Laurel bears N.4°W. 71.0 ft. scribed W.P. S36 CS BT.

Renew North 1/4 Corner Section 32, T29 1/2 S. R7W. 6
Found - Brass Cap set in 1924 & BT's. as follows: Ren. No. 1
14" W. Fir S.0°30'E. 90.0 ft.
10" R. Fir (snag) N.83°E. 93.4 ft.
New BT: 7" Cedar S.53°E. 42.2 ft. scribed N 1/4 S32 CS BT.

South 1/4 Corner Section 32, T29-7W. 7
Found - Brass Cap set in 1924 & BT's. as follows:
8" R. Fir scribed by B. Irving 1954, now 5' snag, scribing vis.
10" R. Fir N.51°E. 12.0 ft. O.K.
New BT: 7" R. Fir N.62°W. 20.8 ft. scribed S 1/4 S32 CS BT.

Renew T29S T29 1/2 S
R8W S36/S31 R7W
Found - Brass Cap at Cor. & Both BT's. N.E. BT., now stump, shows
scribing. We open N.W. BT. & find good scribing.
New BT's: 13" R. Fir bears N.15°E. 33.7 ft. scribed T29 1/2 S R7W S31 CS BT.
8" W. Fir bears S.72°W. 37.1 ft. scribed T30S R7W S 6 CS BT.

Section Corner to Sections S32/S33 T29 1/2 S
S 5/S 4 T30 S R7W
Found - All 4-1924 BT's. N.E. BT., now down. Corner Stone, not found,
Set - Pk Nail & chisled 3" on exposed flat sandstone Rock. We
also chisled CS in rock near cross.
New BT: 19" Fir bears N.65°E. 21.2 ft. scribed S33 T29 1/2 S R7W CS BT.

RE-RENEWED CORNER NO #21

James W. Byron, Deputy County Surveyor
Dale McFarland and John Powell
May 1962
C. S. File No. 49/139

James Byron & Crew
June 1962
C. S. File No. 49/139