

Douglas County Surveyor's Record of
Government Corners Renewed

T 29½

T. S.

R 7

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

23

1/4 Corner for Section 31; and Sec. 6 of T.30-7

Found - 2½" dia. 1924 GLO brass cap on a 1" O.D. Iron pipe, protrudes
6" above ground.

12" down and rotted 14" Chinquapin, root hole bears S.15°E.,
27.8 ft. (agrees with record. Orig. BT

22" now 20" dia. 1½ ft. high rotted D.Fir stump, with a
rotted blaze, bears N.4°W., 21.8 ft. (agrees w/Rec.) 1924 BT.

17" now 21" dia. W.Fir with a partially healed double blaze
illegible scribing visible, bears S.32°E., 36.2 ft. (Rec.
S.32°E., 32.6 ft. error in rec.?) Ren. No. 18

7" now 10" dead Chinquapin with a fully healed double blaze,
bears N.34°W., 11.3 ft. (agrees with rec) Ren. No. 18

6" dia. D.Fir with a partially healed pitched over blaze, bears
N.68°E., 11.3 ft. (tag reads N.68°E., 12.0 ft. dist. to
center of trunk) Unrecorded 1988 BLM tree.

New BTs -18" R.Cedar double blazed and scribed "1/4 S31 CS BT" bears
N.62½°W., 17.6 ft.

6" D.Fir double blazed and scribed "1/4 S6 CS BT" bears
S.40°W., 17.0 ft.

Douglas County
Surveyors Office
Randall Smith
Stephen Flauss
December 20
1991
C.S. File
64/21

12/20/91

24