

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T. S. 1 R. W. W. M.

Frank Cain Dep. Co. Sur.  
recorded by  
P. C. Frear County Sur.  
Nov. 24, 1920

F.B. 107 Pg. 70

✓ 1/4 CORNER TO SECTIONS 9, 10, 15 and 16. SEE CORNER NO. 68 1  
Renewed and post set from which  
A Pine 36" dia. bears S.40°E., 51 lks. REMARK  
A Fir 10" dia. bears N.89°E., 59 lks.  
No trees in West, all burned.

✓ 2 CORNER TO SECTIONS 15 and 16. SEE CORNER NO. #157 2  
Renewed by set from which  
A Pine 10" dia. bears S.57°E., 143 lks.  
A Pine 8" dia. bears S.57°05'W., 144 lks.

✓ 3 SECTION CORNER BETWEEN SECTIONS 14 and 15. SEE CORNER NO. #151 3  
Renewed by Rock 6" x 8" x 12" on a true line and at  
41.09 ch. being a pt. equidistant to the two adjacent  
Section corners from which  
A Yellow Pine 2 1/2" dia. bears S. 3° E., 163 lks.  
A Fir 5" dia. bears N.89°35'W., 226 lks. SEARCHED FOR - NOT FOUND  
2/26/68 J.M.P.

Briggs  
Mar. 12, 1889  
Pg. 130

1/4 Corner 29-28 (Copied from Next Page) 11(?) 4  
Set Post.  
Old B.T. down. Marked New B.T.  
Fir 4" S. 50°W. 5 links  
Fir 6" S. 70°E. 12 links.  
RE-RENEWED, SEE CORNER NO. #210

A. R. Evans  
& Grant  
C. S. File  
No. 41/66

1/4 Corner to Sec. 18, T30S RLW, & Sec. 13, T30S R2W. 5  
Set Fir Stake from 2 O. B. T.'s., scribe Marks Plain  
48" Fir S.10°W. 8 lks.  
30" Fir, now 42", S. 50°E. 12 lks. November 1951  
RE-RENEWED, SEE CORNER NO. 85

John H. Markham, Jr.  
For Stomar Lumber Co.  
Wit. J. R. Markham  
August 1, 1960  
C.S. File No. 51/121

N. E. Corner Section 6, as det. by O.B.T.'s: T29S  
22" W. Fir S.38°E. 32.9 ft. O.B.T. S31 | S32 RLW  
30" La. bears N.88°E. 36.3 ft., O.B.T., S 6 | S 5  
I rescribed S32 T29S RLW BT. T30S 6  
24" Fir Stump, logged, N.61°W. 25.1 ft. O.B.T.  
At Corner Point Found Stone & Set 1" x 30" I. B. from which: 125  
8" W. Oak bears N.85°W. 9.6 ft. dist. mkd. S31 RLW BT  
10" W. Fir bears S11W 19.3 ft. mkd. S6 RLW BT.  
Road bears East 400.0 ft.

North 1/4 Corner Section 6, as det by O. B. T.'s: 7  
30" Fir Stump, logged, bears N.70°W. 21.8 ft. O.B.T.'s.  
30" Fir Stump, logged, bears S.88°E. 31.8 ft. O.B.T.  
At Corner Point Set 1" x 30" Iron Rod from which: 126  
15" Sugar Pine S.15°W. 9.0 ft. mkd. 1/4 S6 BT.  
12" Fir bears N.75°W. 19.0 ft. mkd. 1/4 S31 BT.  
8" Fir bears N. 4°E. 17.4 ft. mkd. 1/4 S31 BT.  
14" Alder " S.67°E. 7.5 ft. mkd. 1/4 S 6 BT.

John H. Markham, Jr.  
For Stomar Lbr. Co.  
Wit: R. G. Boyd  
Oct. 25, 1960  
C. S. File No. 51/121

1/4 Section Corner 21/22. 8  
At a point 214.5 ft. South of W. C. 21/22, I set a point  
which falls in Jackson Creek from which:  
15" Fir bears N.70°W. 47.0 ft. dist. mkd. 1/4 S21 B.T.  
22" Cedar bears S.88°E. 70.0 ft. dist. mkd. 1/4 S22 B.T.  
Jackson Creek Road bears East 95.0 feet.

Witness Corner to 1/4 Corner 21/22, as det. by O.B.T.: 9  
15" dead Alder Snag N.55°E. 28.4 ft. dist. O.B.T., fd. scribe.  
Corner Point fell on West edge of gravel bar, from which:  
6" Fir bears West 31.0 ft. W.C.X. BT.  
9" Alder bears S.57°W. 7.6 ft. dist. mkd. W.C.X. B.T. RLW.  
No Trees O.K. 12/21/67 cc. 54/59 #164