

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & Joe Brady
June 6 - 7, 1966
C. S. File No. 54/28

Vernon "Ray" Tracy
Jack Heritage & V. Perron
November 1, 1967
C. S. File No. 54/59

John M. Powell
Frank Jones & W. Penley
December 20, 1967
C. S. File No. 54/59

Sec. Cor. to Secs. 31 & 32, T30-1W. & Secs. 6 & 5, T31-1W.
Found - 10" Fir, now 11", S. 35° W. 9.2 ft., opened for scribe "6"
6" Fir, now stump, S. 28° E. 14.6 ft.
18" Fir, now 27", N. 20° W. 15.2 ft., faint bark scribed S31 BT scar. #197
24" Fir, now stump, N. 2° E. 10.0 ft.
Set - Brass Cap at Cor. Mkd. County Surveyor's Office, 1966

T30S	RLW	S 31	S 32
T31S	RLW	S 6	S 5

New BT's: 11" D. Fir N. 80° E. 40.8 ft. scribed T30S RLW S32 CS BT.
17" D. Fir S. 52° E. 51.3 ft. scribed T31S RLW S5 CS BT.
26" D. Fir S. 72° W. 21.2 ft. scribed T31S RLW S6 CS BT.

Township Corner T.30 & 31S., R. 1 & 2 W.
Found - 15" Fir, now 36" Corner Tree, Had been opened, scribing.
18" Fir, now stump, S. 70° W. 18.5 ft., shows good scar.
15" Fir, now stump, N. 66° W. 79.9 ft., shows scar.
48", now 49" Fir, N. 48° E. 19.8 ft., very old bark scribe.
15", now 34" Fir S. 40° E. 13.2 ft., shows good scar.
Set - Brass Cap at Township Corner on N-W. side of Corner Tree Mkd:
County Surveyor's Office, 1966

T30S	R2W	S 36	S 31	RLW
T31S	R2W	S 1	S 6	

New BT's: 12" D. Fir N. 19° W. 81.3 ft. scribed T30S R2W S36 CS BT.
11" D. Fir S. 12° W. 109.3 ft. scribed T31S R2W S 1 CSBT.
(Distances to center of corner tree)
Note - Corner lies on top of main ridge, running East-West.

MICROFILM TO HERE 10767

Section Corner to Sections 2 - 3 - 10 - 11. See M 36 - 14
Found - 1967 U.S. Plywood Alum. Cap, properly marked but unrecorded
Orig. 12", now 18" Maple, alive, S. 8° W. 25.7 ft., rotted out, no scribe.
Orig. 48", now 60" Fir, N. 85° E. 34.3 ft., no scar or bark scribe.
No trace Hathorn's BT's. S.E. or N.W.
We find other Orig. BT's. unrecorded.
40" W. Fir S. 75½° E. 83.8 ft., alive, previously opened & shows scribe.
72" D. Fir, alive, N. 36° W. 39.7 ft., shows good scar.
Shrum's New BT's., as follows: See M 36 - 14.
9" W. Fir S. 63° W. 14.5 ft. mkd. "S10 BT".
9" W. Fir N. 66° W. 28.5 ft. mkd. "S 3 BT".
Note - We do not find a branch 1 lk. wide, 6.6 ft. S. of corner
as called for. Nov. 1, 1967

Section Corner to Sections 27 - 28 - 33 - 34.
Found - Mound of Stone at section corner.
18", now 31" D. Fir N. 32° W. 15.2 ft., faint bark scribe visible. #220
10", now 13" D. Fir, S. 87° E. (Record S. 82° E.) 29.7 ft., opened
for scribe "S 3".
No trace of other BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967

T 30 S	R 1 W	S 28	S 27
		S 33	S 34

New BT's: 10" D. Fir N. 74° E. 19.4 ft. mkd. T30S RLW S27 CS BT.
12" Cedar S. 72° E. 31.5 ft. mkd. T30S RLW S34 CS BT.
11" D. Fir S. 19° W. 28.4 ft. mkd. T30S RLW S33 CS BT.
31" D. Fir N. 72° W. 18.0 ft. mkd. T30S RLW S28 CS BT.

Section Corner to Sections 13 - 14 - 23 - 24.
Found - G.L.O. Brass Cap, properly marked in 1923.
5", now 8" Oak, S. 20° E. 13.9 ft., shows scar.
14" D. Fir, now dead, S. 65° W. 36.7 ft., opened for scribe "BT".
12" D. Fir, now dead, N. 71° W. 32.0 ft. (Record 29.7 ft.) opened for scribe.
No trace of N.E. Bearing Tree.
New BT's: 7" W. Oak N. 15° W. 16.0 ft. mkd. T30S RLW S14 CS BT.
6" W. Oak N. 10° E. 16.3 ft., mkd. T30S RLW S13 CS BT.
18" D. Fir S. 9° W. 42.0 ft., mkd. T30S RLW S23 CS BT.

16

17

18

19

20