

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

27

Section Corner to Sections 28 - 29 - 32 - 33.
Found - Orig. 18" Firm now 22" Snag, N.55°W. 25.7 ft., opened for scribe.
Orig. 48" Pine, now stob, S.48°E. 23.8 ft., shows scar.
Stump Hole S.35°W. 4.6 ft. - No trace of N.E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 1 W
Office S 29 | S 28
1967 S 32 | S 33
New BT's: 17" D.Fir N.25°W. 43.8 ft.mkd. T30S R1W S29 CS BT.
20" Cedar N.56°E. 28.2 ft. mkd. T30S R1W S28 CS BT.
14" Cedar S.28½°E. 73.6 ft.mkd. T30S R1W S33 CS BT.
21" Cedar S. 8°W. 47.2 ft. mkd. T30S R1W S32 CS BT.

28

Section Corner to Sections 20 - 21 - 28 - 29.
Found - Orig. 12" D.Fir, now 30" dead, N.60°W. 20.8 ft. #211 opened for scribe.
Orig. 9", now 12" Cedar, dead, S. 37° E. 50.8 ft., burnt out.
No trace of N. E. nor S. W. BT's.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's T 30 S R 1 W
Office S 20 | S 21
1967 S 29 | S 28
New BT's: 28" Cedar S. 3½°E. 72.2 ft. mkd. T30S R1W S28 CS BT.
20" Cedar S.53°W. 39.5 ft. mkd. T30S R1W S29 CS BT.
34" D.Fir N.81°W. 68.0 ft. mkd. T30S R1W S20 CS BT.
10" Laurel N.79°E. 25.6 ft. mkd. T30S R1W S21 CS BT.

29

¼ Corner to Sections 28 and 33.
Found - Orig. 6", now 13" D. Fir, S.85°W. 44.9 ft., tree previously
opened, reopened for ring count, scribe visible, "¼S",
ring count, rings very close, approx. right age.
No trace of N. W. BT.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's T 30 S R 1 W
Office ¼ S 28
1968 S 33
New BT's: 17" D.Fir N. 10° W. 36.3 ft. mkd. ¼ S28 CS BT.
13" D.Fir S. 36° W. 15.2 ft. mkd. ¼ S33 CS BT.

30

¼ Corner to Sections 29 and 30.
Found - Orig. 6", now 15" D.Fir, N. 10° E. 7.3 ft. #214 opened for scribe "¼S".
No Trace of 6" Corner Tree nor 6" S.W. BT.
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's T 30 S R 1 W
Office, 1968 ¼ S 30 | S 29
Reblazed & Rescribed: 15" D.Fir N.10°E. 7.3 ft. scribed ¼ S29 CS BT.
New BT: 28" D.Fir S. 84° W. 14.4 ft. mkd. ¼ S30 CS BT.

31

¼ Corner to Sections 5 and 6.
Found - 30" Red Fir Corner Tree, now 34" Stump, found scribe on W. face.
18" W. Fir, now 20" Stump, N.80°W. 15.8 ft., opened & found scribe.
Set - Brass Cap on N. side of Corner Tree at ¼ Cor. Mkd: #194
County Surveyor's T 30 S R 1 W
Office, 1968 ¼ S 6 | S 5
New BT's: 11" W.Fir S. 89°E. 46.1 ft. mkd. ¼ S 5 CS BT.
8" W.Fir S. 61° E. 32.6 ft. mkd. ¼ S 5 CS BT.
Note - There are no trees in west within scribing distance. Fence is 5.0 ft.
north of the ¼ corner running E. and W.

32

Section Corner to Sections 5 - 6 - 7 - 8.
Found - 18 x 10 x 8" Corner Stone.
15", now 22" R. Fir, N.65°E. 11.9 ft., shows good face.
18", now 22" R.Fir Snag, S.68°E. 58.7 ft., opened & found scribe "B".
10", now 20" R.Fir, S.70°W. 28.3 ft. (Record 46.2 ft., shows good face.
8", now 18" R. Fir, N.10°W. 30.4 ft., shows a good face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 1 W
Office S 6 | S 5
1968 S 7 | S 8
New BT: 10" R.Fir S. 38° E. 34.1 ft. mkd. T30S R1W S 8 CS BT.
Note - This corner lies 250.0 ft. west of a logging road.

1/8/68

John M. Powell
Frank Jones & W. Penley
January, 1968
C. S. File No. 54/59

RE-RENEWED SEE CORNER NO. #211

RE-RENEWED SEE CORNER NO. #214

RE-RENEWED SEE CORNER NO. #194