

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21891

33

$\frac{1}{4}$ Corner to Sec. 31, T30-1W. & Sec. 36, T30-2W.
Found - Orig. 30", now 42" D.Fir, N. 86°E. 15.2 ft., opened for scribe.
No trace of S.W. Bearing Tree.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's R T 30 S R
Office 2 S 36 | S 31 1
1968 W W

New BT: 30" D.Fir N. 71° W. 68.0 ft. scribed $\frac{1}{4}$ S36 CS BT.
N. E. Bearing Tree in good condition.

34

Township Corner- Found GLO Brass Cap R T 29 S R
1917 2 S 36 | S 31 1
W S 1 | S 6 W
T 30 S

Found -Orig. 30" Pine, now down & burnt, S.8°W. 24.4 ft.
Orig. 18" Oak, now rotted out, N.70°W. 37.0 ft.
Orig. 18" Oak, now stub, N. 47°E. 47.5 ft.
Orig. 12", now 17" Oak, S.82°E. 118.8 ft., opened for scribe "BT".
(Fell this tree as was very rotten & would be a hazard)
New BT's: 16" D.Fir N.44°W. 26.8 ft. mkd. T29S R2W S36 CS BT.
15" D.Fir N.73°E. 17.5 ft. mkd. T29S R1W S31 CS BT.
Reblzd. & Rescrbd: 16" D.Fir S.9°E. (Rec.S.12°E.) 13.0 ft. mkd. T30S R1W S6 CS BT.
1904 BT's: 10" D.Fir S.41°W. (Rec.S39°W.) 33.0 ft. mkd. T30SR2WS1CS BT.

35

$\frac{1}{4}$ Corner Sec. 12 only, T30-2W.
Found - 10" ,now 18" D.Fir, S.69°W. 17.8 ft., scribe visible "S12B"
5", now 6" W.Oak, N.58°W. 31.7 ft., shows good scar.
Corner Stone with $\frac{1}{4}$ W face.
Set - Brass Cap at $\frac{1}{4}$ Cor.Mkd: County Surveyor's R T 30 S R
Office 2 $\frac{1}{4}$ S 12 | 1
1968 W 1968 W

Bearing Trees in good condition, tagged same.
Note - This cor. lies 33.0 ft. south of $\frac{1}{4}$ Cor. Sec. 7, T30-1W.
Also on E-W cutting line.

John M. Powell
Frank Jones & W. Penley
January, 1968
C. S. File No. 54/59

$\frac{1}{4}$ Corner to Section 7 only, T30-1W.
Found - 30" Corner Tree, now 36", tree opened & visible.
8", now 12" B.Oak, S.85°E. 20.5 ft., shows good scar.
18", now 22" Pine, N.71°E. (Rec.N.35°E) 23.8 ft., shows good scar.
Set - Brass Cap on East Side of Corner Tree Mkd: R T 30 S R
County Surveyor's 2 $\frac{1}{4}$ | S 7 1
Office, 1968 W W

Bearing Trees all O.K., tagged same.
Note - This corner lies 33.0 ft. north of $\frac{1}{4}$ Cor. Sec. 12 only, T30-2W.

FD. B.C. 9/93 BY AESKE M117-62

37

$\frac{1}{4}$ Corner to Sec. 6 only, T30-1W.
Found - 18x10x6 Basalt Stone, firmly in ground, " $\frac{1}{4}$ " on east face.
28" Pine, now down & burnt, N.71°E. 58.1 ft.
No trace of S.E. BT.
Set - Brass Cap at $\frac{1}{4}$ Cor.Mkd: County Surveyor's R T 30 S R
Office 2 $\frac{1}{4}$ | S 6 1
1968 W W

New BT's: 9" Pine N. 85° E. 12.0 ft. mkd. $\frac{1}{4}$ S 6 CS BT.
5" Pine S. 52° E. 3.5 ft. mkd. $\frac{1}{4}$ S6 CS BT.
Note - This corner lies 81.2 ft. north of $\frac{1}{4}$ Cor. Sec. 1, T30-2W.
Also lies 5.0 ft. south of fence corner running N. & E.

FD. 7/93 HAINES
FOR 81M - SEE
GIS FILE

38

$\frac{1}{4}$ Corner to Section 1 only, T30-2W.
Found - 12x10x8 Basalt Stone, firmly in ground, $\frac{1}{4}$ on W. face.
14" W.Oak S.70°W. 4.0 ft., found old axe work.
No trace of N.W. Bearing Tree.
Set - Brass Cap at $\frac{1}{4}$ Cor.Mkd: County Surveyor's R T 30 S R
Office 2 S 1 | $\frac{1}{4}$ 1
1968 W W

New BT's: 5" D.Fir N.71 $\frac{1}{2}$ °W. 9.6 ft. mkd. $\frac{1}{4}$ S1 CS BT.
10" W.Oak S.46 $\frac{1}{4}$ °W. 20.0 ft. mkd. $\frac{1}{4}$ S1 CS BT.
Note - This corner lies 81.2 ft. south of $\frac{1}{4}$ Cor. Sec.6 only, T30-1W.