

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

45

Section Corner to Sections 14 - 15 - 22 - 23.  
Found - Original Stone at corner marked with notches.  
1923 G.L.O. Brass Cap at corner, properly marked.  
26", now 29" Pine, N. 1° E. 82.5 ft., shows good scar.  
12", now 16" Oak, N. 75° W. 89.1 ft., opened for scribe "T30".  
New BT's: 11" D. Fir N. 70° E. 41.1 ft., scribed T30S RLW S14 CS BT.  
5" D. Fir N. 73° W. 24.5 ft. mkd. S15 CS BT.  
14" D. Fir S. 75° W. 27.7 ft. mkd. T30S RLW S22 CS BT.  
7" Pine S. 72° E. 40.4 ft. mkd. T30S RLW S23 CS BT.

46

Section Corner to Sections 15 - 16 - 21 - 22.  
Found - 18", now 23" W. Oak, N. 50° W. 66.0 ft., opened for scribe "B".  
Pine Stump Hole S. 66° E. 37.0 ft.  
No trace of N.E. nor S.W. BT's.  
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1968  
New BT's: 12" D. Fir N. 54° W. 3.0 ft. mkd. T30S RLW S16 CS BT.  
11" D. Fir N. 56½° E. 10.0 ft. mkd. T30S RLW S15 CS BT.  
14" D. Fir S. 53° E. 23.4 ft. mkd. T30S RLW S22 CS BT.  
12" D. Fir S. 53° W. 22.0 ft. mkd. T30S RLW S21 CS BT.

47

¼ Corner to Sections 25 and 36.  
Found - 1923 G.L.O. Brass Cap at ¼ Cor., properly marked.  
12", now 22" D. Fir, N. 16½° E. 97.7 ft., shows good scar.  
8", now 19" D. Fir S. 7½° W. 81.2 ft., opened for scribe "S".  
New BT's: 9" D. Fir N. 17½° W. 5.7 ft. mkd. ¼ S25 CS BT.  
9" D. Fir S. 22° E. 17.6 ft. mkd. ¼ S36 CS BT.

48

¼ Corner to Sections 26 and 35.  
Found - Corner Stone 20x14x14 with "¼" on north face.  
16", now 24" Red Fir, S. 60° E. 20.5 ft., opened & found scribing "5 B".  
16" Fir, now 16" Stob, N. 60° E. 13.2 ft., no trace of scribing.  
Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office 1968  
Rescribed: 24" R. Fir S. 60° E. 20.5 ft. scribed "¼ S35 CS BT".  
New BT: 24" Cedar N. 46° E. 20.6 ft. mkd. ¼ S26 CS BT.  
Note - This corner lies 130 ft. east of a creek.

49

Section Corner to Sections 26 - 27 - 34 - 35.  
Found - G.L.O. Brass Cap, 1923, properly marked in 1923.  
12", now 19" Cedar N. 27° E. 46.2 ft., shows good scar.  
20", now 36" D. Fir S. 75° E. 91.7 ft. shows good scar.  
18", now 26" Pine, S. 42° W. 54.8 ft., shows good scar.  
24" D. Fir, now snag, N. 2° W. 66.0 ft., shows good scar.  
New BT: 18" S. Pine N. 4° W. 42.2 ft. scribed T30S RLW S27 CS BT.  
Other BT's. O.K. & Tagged.

50

¼ Corner Section 27 only.  
Found - 1923 G.L.O. Brass Cap at ¼ Corner Mkd. properly.  
30", now 36" Cedar, S. 18° W. 25.1 ft., shows good Face.  
24" Pine, now 24" Stub, N. 70° W. 36.1 ft., shows scribing.  
No trace N.E. BT.  
New BT's: 6" D. Fir S. 80° W. 16.1 ft. mkd. "¼ S27 CS BT.  
6" D. Fir N. 31° W. 20.3 ft. mkd. "¼ S 27 CS BT.  
Note - The ¼ corner of Sec. 26 only, O.K., lies 30.4 ft. North and both corners lie on west slope.

John M. Powell  
Frank Jones & W. Penley  
January, 1968  
C. S. File No. 54/59