

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

58

Section Corner to Secs. 30 & 31, T30-1W. & Secs. 25 & 36, T30-2W.
Found - 36", now 40" D.Fir, S.45°E. 5.3 ft., bark scribe visible,

18" D.Fir, now blow-down, N.25°W. 11.2 ft.
No trace of N.E. or S.W. BT's.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1968

R	T 30 S	R
2	S 25 S 30	1
	W S 36 S 31	W

New BT's: 11" W.Fir N.4°W. 47.5 ft. mkd. T30S R2W S25 CS BT.
15" Yew N.37°E. 61.0 ft. mkd. T30S R1W S30 CS BT.
12" Yew S.50°E. 49.0 ft. mkd. T30S R1W S31 CS BT.
No trees available in S.W. Quadrant.

RE-RENEWED, SEE CORNER NO. #215

59

1/4 Corner to Section 34 only, T29-1W.

Found - 16x12x10 Stone mkd. "1/4".
30, now 34" D.Fir, N.40 1/2°E. 87.8 ft., shows good scar.
30"?, now 25" Pine, N.51 1/2°W. 79.2 ft., shows good scar.

Set - Brass Cap at 1/4 Cor.Mkd: County Surveyor's Office, 1968

T29S	R1W 1/4	S34
T30S		

Bearing Trees O.K. and tagged.

Note - This corner lies 33.0 ft. E. of 1/4 Sec. Cor. 3 only, T30-1W.
Also 25" Pine N.51 1/2°W. was used for both corners. See Below.
2/20/68

60

1/4 Corner to Section 3 only, T30-1W.

Found - Stone, out of place, marked "1/4".
10", now 28" S.Pine, S.45°E. 57.4 ft., shows good scar.
9"?, now 25" S.Pine, N.30°W. 56.1 ft., shows good scar.

Set - Brass Cap at 1/4 Cor.Mkd: County Surveyor's Office, 1968

T29S	R1W 1/4	S 3
T30S		

New BT: 15" S.Pine S.5°W. 19.6 ft. mkd. 1/4 S3 CS BT.
Note - This corner lies west of 1/4 cor. sec. 34 only, T29-1W 33.0 ft.
2/20/68

Section Corner to Sections 19 - 20 - 29 - 30.

Found - No trace of Corner Tree nor N.W. - N.E. BT's.
6" D.Fir Stob S.47°E. 23.1 ft., scribe visible, "BT".
12" D.Fir, now 20" dead, S.89°E. 2.9 ft. opened for scribe.

Set - Brass Cap at Cor.Mkd: County Surveyor's Office 1968

T 30 S R 1 W
S 19 S 20
S 30 S 29

New BT's: 6" D.Fir N.15°W. 28.8 ft. mkd. T30S R1W S19 CS BT.
24" D.Fir N.15 1/2°E. 26.5 ft. mkd. T30S R1W S20 CS BT.
11" D.Fir S.33°E. 33.4 ft. mkd. T30S R1W S29 CS BT.
35" D.Fir S.45°W. 44.9 ft. mkd. T30S R1W S30 CS BT.

RE-RENEWED, SEE CORNER NO. #203

62

1/4 Corner to Sections 15 and 22.

Found - Orig.18"W.Oak, now dead, N.85°W. 60.7 ft., opened for scribe.
Orig. 30" Pine, now down, S.6°E. 35.6 ft., no evidence left.

Set - Brass Cap at 1/4 Cor.Mkd: County Surveyor's Office 1968

T 30 S R 1 W
1/4 S 15
S 22

New BT's: 13" S.Pine N.48°W. 31.1 ft. mkd. 1/4 S15 CS BT.
12" W.Oak S.41°E. 54.3 ft. mkd. 1/4 S22 CS BT.

63

1/4 Corner to Sections 14 and 23.

Found - GLO Brass Cap, 1923, properly marked.
15", now 24" Pine, N.80°E. 12.5 ft., shows scribing.
No trace of SE. BT.

New BT: 24" D.Fir S.34°E. 32.4 ft. mkd. 1/4 S23 CS BT.
Note - This corner lies approx. 40 ft. north of a E-W cutting line.

John M. Powell
Frank Jones & W. Penley
February, 1968
C. S. File No. 54/59