

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

Twp. Corner to Sec. 1, 30-1W.-Sec. 36, T29-1W. & Sec. 31, T29-1E.

Found - Fir Stump, out of place, opened for scribe, marks "B S".  
By using 40" Pine Stump, line tree, 71.9 ft. south of corner:

Set - Brass Cap at Cor.Mkd: County Surveyors R T 29 S R  
Office 1 S 36 S 31  
1968 W S 1 E

Note - This corner 211.2 ft. north of  $\frac{1}{4}$  S31 only, T29S. R1E.  
New BT's: Laurel N. 55° W. Mkd: T29S R1W S36 CS BT.  
14" Cedar N. 51° E. 70.0 ft. mkd. T29S R1E S31 CS BT.  
No trees available in S.W. Quad.

70

6/12/68

Sec. Cor. to Sections 13 & 24, T30-1W. - SEE Cor. No. 130 &  
Found - Stone at sec. cor. grooves on S E edge. CHECK GOVT. PLAT.

12", now 36" D. Fir, S. 58° W. 38.0 ft., shows good scar.  
30", now 46" D. Fir, N. 50° W. 25.1 ft., shows good scar.  
Record S. 64° W. 19.8 ft., no trace of any tree at this point.

Set - Brass Cap at Cor.Mkd: County Surveyor's R T 30 S R  
Office 1 S 13 S 18 1  
1968 W S 24 S 18 E

Trees in good condition & tagged. Did not tie btwn. corners, too late.

$\frac{1}{4}$  Corner to Section 18 only, T30S. R1E.

Found - GLO Brass Cap at  $\frac{1}{4}$  Corner, 1923, properly marked.  
60", now 60" D. Fir, N. 58° E. (Rec. N. 62E) 96.0 ft., shows good scar.  
30", now 36" D. Fir, S. 3° E. 81.8 ft., shows good scar.

New BT's: 12" D. Fir S. 73° E. 21.9 ft. mkd.  $\frac{1}{4}$  S18 CS BT.  
10" D. Fir N. 42° E. 27.2 ft. mkd.  $\frac{1}{4}$  S18 CS BT.

Note - Did not tie btwn. corners, too late in day.

Section Corner to Sections 7 - 8 - 17 - 18.

Found - Corner Stone 15x10x8 mkd. with 4 grooves on S. & 5 grooves on E.  
9", now 14" D. Fir, N. 17° E. 23.8 ft., shows good scar.  
10", now 16" D. Fir, S. 24° E. 23.1 ft., shows good scar.  
12", now 18" D. Fir, N. 86° W. 15.2 ft., shows good scar.

Set - Brass Cap at Cor.Mkd: County Surveyor's T 30 S R 1 W  
Office S 7 S 8  
1968 S 18 S 17

Note - All Bearing Trees in good condition, did not mark new BT's.

$\frac{1}{4}$  Corner to Sections 8 and 17.

Found - Corner Stone 14x9x5 mkd. " $\frac{1}{4}$ ".  
24", now 32" D. Fir, N. 74° E. 19.1 ft., shows good scar.  
20", now 21" D. Fir, Stob, S. 40° W. 37.6 ft., shows scribing " $\frac{1}{4}$  S17".

Set - Brass Cap at Cor.Mkd: County Surveyor's T 30 S R 1 W  
Office  $\frac{1}{4}$  S 8  
1968 S 17

New BT: 10" D. Fir S. 37° E. 28.6 ft. mkd. " $\frac{1}{4}$  S17 CS BT".

Section Corner to Sections 9 - 8 - 16 - 17.

Found - Broken Stone at Corner with 4 grooves.  
24" Pine, now snag, S. 82° W. 9.2 ft., burnt face, faint "4" visible.  
24", now 31" Pine, N. 54° W. 102.3 ft., shows good scar.  
Remains of Oak about S. 60° E. 44.9 ft.

Set - Brass Cap at Cor.Mkd: County Surveyor's T 30 S R 1 W  
Office S 8 S 9  
1968 S 17 S 16

New BT's: 12" D. Fir N. 40 $\frac{1}{2}$ ° W. 29.2 ft. mkd: T30S R1W S8 CS BT.  
9" D. Fir N. 35° E. 19.5 ft. mkd. T30S R1W S9 CS BT.  
8" D. Fir S. 38° E. 13.4 ft. mkd. T30S R1W S16 CS BT.  
13" D. Fir S. 14° W. 29.2 ft. mkd. T30S R1W S17 CS BT.

-----

71

72

73

74

75

John M. Powell  
Frank Jones & W. Penley  
June, 1968  
C. S. File No. 54/59

RE-RENEWED, SEE CORNER NO. #180

RE-RENEWED, SEE CORNER NO. #195