

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1968 T 30 S R 1 W
 $\frac{1}{4}$ S 5 | S 4
 New BT's: 9" Hemlock N. 9° W. 19.7 ft. mkd. $\frac{1}{4}$ S 5 CS BT.
 16" D. Fir N. 33° E. 37.7 ft. mkd. $\frac{1}{4}$ S 4 CS BT.

83

$\frac{1}{4}$ Corner to Sections 8 and 9.
 Found - No trace of the corner stone nor N.E. BT.
 10", now 14" Maple, S. 52° W. 24.4 ft., found reverse scribing.
 Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1968 T 30 S R 1 W #186
 $\frac{1}{4}$ S 8 | S 9
 New BT's: 9" Hemlock N. 74° W. 34.6 ft. mkd. $\frac{1}{4}$ S 8 CS BT.
 22" Yew N. 52° E. 51.6 ft. mkd. $\frac{1}{4}$ S 9 CS BT.
 Note - This $\frac{1}{4}$ corner lies on N. slope, approx. 100' S. of a small swamp.

84

$\frac{1}{4}$ Corner to Sections 4 and 3.
 Found - 30", now 38" Fir Corner Tree, opened for scribe "3".
 12" W. Fir, now stobe, N. 87° W. 14.5 ft., opened for scribe " $\frac{1}{4}$ ".
 14" Hemlock, now rotten stump, S. 12° E. 26.4 ft.
 Set - Brass Cap on S. Side of Corner Tree Mkd: County Surveyor's Office, 1968 T 30 S R 1 W
 $\frac{1}{4}$ S 4 | S 3
 New BT's: 6" Yew S. 32° E. 13.0 ft. mkd. $\frac{1}{4}$ S 3 CS BT.
 26" D. Fir N. 30° W. 18.0 ft. mkd. $\frac{1}{4}$ S 4 CS BT.

85

$\frac{1}{4}$ Corner to Sec. 18, T30-1W and Sec. 13, T30-2W.
 Found - 38" D. Fir S. 10° E. (Rec. S. 10W) 5.3 ft., faint bark scribe " $\frac{1}{4}$ ",
 Tree opened before, "BT" visible. See Ren. #5.
 48" D. Fir, now stump, S. 50° W. (Rec. S. 50E) 7.9 ft.
 Find no other trees in area that come close to matching. Call on
 S. Umpqua fits good. Renew by using reverse bearings & original distance.
 Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1968 R T 30 S R
 2W $\frac{1}{4}$ S 13 | S 18 1W
 Reblz. & Rescbd: 38" D. Fir S. 10° E. 5.3 ft. scribed $\frac{1}{4}$ S 18 CS BT.
 New BT: 12" R. Fir N. 30° W. 10.8 ft. mkd. $\frac{1}{4}$ S 13 CS BT.

86

Sec. Cor. to Secs. 18 & 19, T30-1W. & Secs. 13 & 24, T30-2W.
 Found - Stone at Section Corner, 6x8x18.
 Orig. 8" D. Fir, now stob, S. 14° E. 7.9 ft., old axe work, "B" visible.
 Orig. 9" D. Fir, now rotten stump & hole, N. 75° W. 8.6 ft.
 20" D. Fir S. 53 $\frac{1}{2}$ ° E. 14.8 ft., bark scribed visible "T30S R1W S19 CS BT" #181
 18" D. Fir S. 79 $\frac{1}{2}$ ° W. 19.4 ft., bark scribe visible. (See Ren. #19, R2W)
 24" D. Fir N. 56° E. 20.0 ft. bark scribe visible. (possible O.B.T.)
 24" D. Fir N. 62 $\frac{1}{2}$ ° W. 48.2 ft., bark scribe visible. (See Ren. #19, R2W)
 Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1968 R T 30 S R
 2 S 13 | S 18 1
 W S 24 | S 19 W
 Bearing Trees all in good condition, O.K. and Tagged.

87

$\frac{1}{4}$ Corner Section 1 only, T30S. R1W.
 Found - Stone, firmly set at $\frac{1}{4}$ corner, mkd: " $\frac{1}{4}$ " on south face.
 12", now 32" D. Fir, N. 80° W. 17.8 ft., tree badly scared & burnt,
 scribe visible " $\frac{1}{4}$ S".
 12", now 34" D. Fir, S. 77° W. (Rec. S. 87W) 20.5 ft., has burnt cat face.
 Set - Brass Cap at Cor.Mkd: County Surveyor's Office, 1968 T 29 S R 1 W
 $\frac{1}{4}$ S 1
 T 30 S
 Reblzd. & Rescbd: 34" D. Fir S. 77° W. 20.5 ft. mkd. $\frac{1}{4}$ S 1 CS BT.
 New BT: 9" Hemlock S. 64° E. 14.0 ft. mkd. $\frac{1}{4}$ S 1 CS BT.
 Note - This corner lies 205.3 ft. E. of $\frac{1}{4}$ Corner Sec. 36 only, T29-1W.

John M. Powell
 Frank Jones & W. Penley
 June, 1968
 C. S. File No. 54/59