

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 1 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
June, 1968
C. S. File No. 54/59

1/4 Corner to Section 36 only, T29S. R1W. 88
Found - Stone, firmly set at 1/4 corner mkd: "1/4" on north face.
16", now 21" D. Fir, N. 6° E. 48.8 ft., some scribe work visible.
16", now 30" Pine, N. 28 1/2° W. 70.6 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office 1/4 S 36
1968 T 30 S

Bearing Trees O.K. and Tagged
Note - This corner lies 205.3 ft. W. of 1/4 Cor. Sec. 1, T30-1W., Ren.#87.

Section Corner to Secs. 3 & 4, T30-1W. & Secs. 33 & 34, T29-1W. 89
Found - 10", now 15" Cedar Corner Tree, shows good scars.
12", now 15" D. Fir, N. 70° E. 38.9 ft., shows good scar.
16", now 25" Cedar, S. 54° W. 12.5 ft., shows good scar.
12", now 16" Laurel, N. 56° W. 31.7 ft., shows scar, some scribe marks visible.
15" D. Fir, now dead, S. 10° E. 32.3 ft., opened for scribe "3".
Set - Brass Cap on S. side of Cor. Tree Mkd: T 29 S R 1 W
County Surveyor's S 33 S 34
Office S 4 S 3
1968 T 30 S

New BT: 6" Laurel S. 7° E. 28.0 ft. mkd. T30S R1W S3 CS BT.
All other BT's. O.K. and Tagged.

Sec. Cor. to Secs. 24 & 25 only, T30-1W. 90
Found - No trace of corner stone.
20" D. Fir, now down & burnt, N. 2° W. 23.8 ft., found scribe.
10" D. Fir, now rotten stump, S. 30° W. 19.8 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R
Office 1 S 24 S 19 1
1968 W S 25 E

New BT's: 10" D. Fir N. 2° W. 27.4 ft. mkd. T30S R1W S24 CS BT.
10" D. Fir S. 29° W. 18.2 ft. mkd. T30S R1W S25 CS BT.
14" D. Fir N. 33° E. 10.4 ft. mkd. T30S R1E S19 CS BT.
Note - This corner lies 236.3 S. of 1/4 Sec. 19 only, T30-1E., see below.

1/4 Corner to Section 19 only, T30-1E. 91
Found - G.L.O. Brass Cap properly marked in 1923.
50", now 60" D. Fir, N. 2° E. 235.0 ft., shows good scar.
Found probable S.E. BT., too many bees to check.
New BT's: 8" D. Fir S. 16° E. 12.7 ft. mkd. 1/4 S19 CS BT.
12" D. Fir N. 17° E. 4.3 ft. mkd. 1/4 S19 CS BT.
Note - This corner lies 236.3 ft. N. of Sec. Cor. to Secs. 24 & 25 only, T30-1W.

1/4 Corner to Section 12 only, T30-1W. 92
Found - Stone at 1/4 corner, "1/4" on west side.
Orig. 12" (?), now 28" W. Fir, S. 80° W. 37.0 ft., scribe visible, "S12 BT" (1923)
26" D. Fir, now stump, N. 42° W. 37.6 ft., shows good scar. (new BT) (1923)
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R
Office 1W 1/4 S 12 1E
1968

New BT's: 18" Cedar N. 74° W. 28.5 ft. mkd. 1/4 S12 CS BT.
SW. BT., O.K. and Tagged.

Section Corner to Sections 1 and 12 only, T30-1W. 93
Found - 24", now 26" Cedar Stump, N. 31° W. 88.1 ft., scribe visible "T30".
No trace of corner stone or S.W. BT. - Corner in heavily logged area.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R
Office 1 S 1 S 6 1
1968 W S 12 E

New BT's: 5" D. Fir N. 40° W. 19.0 ft. mkd. S 1 CS BT.
5" D. Fir N. 65° W. 19.5 ft. mkd. S 1 CS BT.
No other trees available.
Note - This corner lies 248.0 ft. S. of 1/4 Cor. Sec. 6 only, T30-1E, see over.