

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T.S. R. 1 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$ Cor. of sections 16 and 17.
Found- 15" W. Oak now 20" S.75°E. 16.5 ft. scribing found-"BT" no trace if NW BT.
Set - Brass cap at $\frac{1}{4}$ cor. mkd: County Surveyor's T30S RLW $\frac{1}{4}$ S17/S16 Office 1970
New BT's-6" Douglas Fir S.82°W. 16.5 ft. scribed $\frac{1}{4}$ S17 CS BT.
8" Douglas Fir S.43°E. 14.8 ft. scribed $\frac{1}{4}$ S16 CS BT.
Jan. 15, 1970

122

John M. Powell
& Crew
C.S. File
No. 54/59

Renew Cor. #3 of H.E.S. No. 195.
Found-Old cor. stone in place & mkd:"3 HES 195".on claim side.
Orig. 6" Yew, now 10", S.73 $\frac{1}{2}$ °W. 15.2 ft. alive, scribe visible on decaying blaze.
Set- Brass cap at cor. mkd: County Surveyor's T30S RLW (Reset old Stone alongside)Office 1970 cor.#3 HES 195
New BT's-9" D.Fir N.19°W. 18 ft. mkd: 3HES 195 CS BT.
18" D.Fir S.86°E. 17.1 ft. mkd: 3 HES 195 CS BT.
Note- This cor. lies on very steep Southerly slope, between road & Jackson Creek.

123

V.R.Tracy
& Crew
C.S.File No.
54/59

Renew Cor.#4 of H.E.S. 195.
Found- Old cor. stone firmly set & mkd. "X" on top & "4 HES 195" on claim side.
side. The only orig. B.T. is gone.
We find River calls to South & East, fit Orig. call distances.
Set- Brass cap at cor. mkd: County Surveyor's T30S RLW (Reset old Stone alongside)Office 1970 Cor.#4 HES 195
New BT's-10" D.Fir S.62°W. 4.2 ft. mkd: 4 HES 195 CS BT.
9" D.Fir S.32°E. 17.8 ft. mkd: 4 HES 195 CS BT.
Note- This cor. is also the north 1/16 cor. of secs. 22 & 23, & lies on NE. slope approx. 75 ft. East of top of spur sloping Southerly.

124

Sec. Cor. to Secs. 31 & 32, T29-1W and Secs. 5 & 6, T30-1W.
Found - 1 $\frac{1}{2}$ " Iron Bolt and Orig. Stone with 5 Notches on W. Side, Ren.#6.
Replaced Bolt with 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk stamped:
T 29 S R 1 W from which bears:
S 31 | S 32 Orig.BT, 30" Madrona, blowdown, N.88°E. 32.9 ft.
S 6 | S 5 Orig.BT, 22" W. Fir, blowdown, S.38°E. 32.9 ft.
T 30 S R 1 W 12" White Fir scribes visible, S.11°W. 18.9 ft.
R.L.S. 222 9" Black Oak BT., N.85°W. 9.6 ft.
1970 Orig.BT, 24" Fir, now stump,(Logged off) N.61°W. 25.1'.

125

$\frac{1}{4}$ Cor. to Section 31, T29-1W. and Sec. 6, T30-1W.
Found - 1" Iron Rod, See Ren. # 7.
Replaced Rod with 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:
T 29 S R 1 W from which bears:
 $\frac{1}{4}$ S 31 12" Fir N.4°E. 17.4 ft., shows good scar.
S 6 Orig.BT, found 30" Stump S.88°E. 31.8 ft.
T 30 S R 1 W 14" Alder S.66°E. 7.2 ft., scribes visible.
R.L.S. 222 21" Sugar Pine S.15°W. 8.7 ft.
1970 14" Fir N.75°W. 18.6 ft.
Orig.BT. found 30" Fir Stump N.70°W. 21.8 ft.

126

$\frac{1}{4}$ Corner to Sec. 32, T29-1W. and Sec. 5, T30-1W.
Found - 24"x20"x8" Ironstone with " $\frac{1}{4}$ " scribed on North face.
Set - 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:
T 29 S R 1 W from which bears:
 $\frac{1}{4}$ S 32 Orig.BT, 30" Stump, lying on face, shows good scar,
S 5 N.57°W. 10.6 ft.
T 30 S R 1 W Orig.BT, 30" Fir(Blowdown) shows good scar, S.34°W.
R.L.S. 222 25.7 feet.
1970 Scribed New BT: 8" Fir scribed ($\frac{1}{4}$ S32 BT)
N.70 $\frac{1}{2}$ °E. 36.3 ft.
Scribed New BT: 6" White Fir scribed ($\frac{1}{4}$ S5 BT)
S.64°W. 14.9 ft.

127

Left Orig. Stone Monument beside New Monument.

For Umpqua National Forest
By J. A. Hoffbahr
July 2, 1970 C.S. File 55/158
Map File M 40 - 4

RE-RENEWED CORNER NO. #218

MARCH 71